GE SILICONE CO -- RTV-103 ADHESIVE SEALANT -- 8040-00-865-8991

Product ID:RTV-103 ADHESIVE SEALANT MSDS Date:04/12/1991 FSC:8040 NIIN:00-865-8991 MSDS Number: BFTFR === Responsible Party === Company Name: GE SILICONE CO Address:260 HUDSON RIVER RD City:WATERFORD State:NY ZIP:12188-5000 Country:US Info Phone Num:518-237-3330/518-266-2641 Emergency Phone Num:518-23 7-3330/800-332-3390 CAGE:EO534 === Contractor Identification === Company Name: GE SILICONE CO Address:260 HUDSON RIVER RD City:WATERFORD State:NY ZIP:12188-5000 Country:US Phone:518-237-3330/518-266-2641 CAGE:EO534 Company Name: GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT Address:260 HUDSON RIVER RD Box:City:WATERFORD State:NY ZIP:12188 Country:US Phone:518-237-3330/800-332-3390 CAGE:01139

Ingred Name:METHYLTRIACETOXYS

ILANE, ALKYL TRIACETOXY SILANE \*98-2\* CAS:4253-34-3 RTECS #:VV4500000 Fraction by Wt: 1-5%

Ingred Name:TRADE SECRET COMPONENT Fraction by Wt: 10-30%

Ingred Name:NON-HAZARDOUS INGREDIENTS Fraction by Wt: 10-30%

Ingred Name:SILOXANES & SILICONES DI-ME HYDROXY-TERMINATED \*98-2\* CAS:70131-67-8 Fraction by Wt: 60-80%

LD50 LC50 Mixture:ORAL LD50 RAT >40,000 Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SKIN: UNCURED PRODUCT CONTACT IRRITATES SKIN, LIPS, GUMS & TONGUE. INHALATION: UNCURED PRODUCT CAUSES MODERATE RESPIRATORY IRRITATION. MOUTH, NOSE & THROAT IRRITATION. EYES: UNCURED PRODUCT IRRITATES EYES. Effects of Overexposure:EYE &NOSE IRRITATION FROM VAPORS. SKIN IRRITATION FROM UNCURED RTV-103 MAY OCCUR.RESPIRATORY IRRIT.

First

Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES & CONSULT PHYSICIAN.SKIN: WIPE OFF AND WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: MOVE PERSON TO FRESH AIR.

Extinguishing Media:ALL STANDARD FIRE FIGHTING AGENTS Fire Fighting Procedures:NONE REQUIRED Unusual Fire/Explosion Hazard:SENSITIVITY TO STATIC CHARGE NOT EXPECTED.

====== Accidental Release Measures =====

\_\_\_\_\_

Spill Release Procedures:WIPE, SCRAPE, OR SOAK UP W/INERT MATERIAL & PUT IN CONTAINER FOR DISPOSAL. WASH WALKING SURFACES W/DETERGENT & WATER TO REDUCE SLIPPING HAZARD. WEAR PROPER PROTECTIVE EQUIPMENT.

Handling and Storage Precautions: ACETIC ACID VAPOR WILL BE LIBERATED DURING APPLICATION AND CURING. ADEQUATE VENTILATION IS REQUIRED TO MAINTAIN BELOW TLV
Other Precautions: CURED RTV-103 REQUIRES
NO SPECIAL PRECAUTIONS. KEEP CONTAINER CLOSED WHEN NOT IN USE. AVOID SKIN & EYE CONTACT.

Respiratory Protection:USE IN A WELL VENTILATED AREA Ventilation:EXHAUST VENTILATION Protective Gloves:CLOTH GLOVES Eye Protection:SAFETY GLASSES RECOMMEND Other Protective Equipment:EYEWASH STATION Work Hygienic Practices:REMOVE CONTACT LENSES BEFORE USING SEALANT. DON'T HANDLE LENSES UNTIL SEALANT IS CLEANED FROM FINGERS, NAIL S & CUTICLE. Supplemental Safety and Health STATEMENT FROM G.E.CO, S.P.DEPT:RTV-103 CONTAINS NO HAZARDOUS INGREDIENTS AS DEFINED BY THE FEDERAL HAZARDOUS SUBSTANCES LABELING

ACT.

HCC:N1 Boiling Pt:B.P. Text:NONE Spec Gravity:1.06 Evaporation Rate & amp; Reference: