

DOW CORNING CORP -- SYLGARD 184 SILICONE ELASTOMETER CURING AGE -- 5970-00-899-4323  
===== Product Identification =====

Product ID:SYLGARD 184 SILICONE ELASTOMETER CURING AGE

MSDS Date:01/09/1989

FSC:5970

NIIN:00-899-4323

Kit Part:Y

MSDS Number: BFVGY

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone

Num:517-496-5900 OR 517-496-6000

Emergency Phone Num:517-496-5900

Preparer's Name:JACK L. SHENEBERGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

Company Name:MCKEOWN ROBERT CO. INC.

Address:111 CHAMBERS BROOK

RD.  
Box:City:SOMERVILLE  
State:NJ  
ZIP:08876  
Country:US  
Phone:908-218-9000  
CAGE:7B953

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PROPIETARY COMPONENT  
Fraction by Wt: 33%  
Other REC Limits:5 MG/M3 CEILING DUST

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: NO HEALTH HAZARD. CHRONIC: NO  
HEA  
LTH HAZARD.

Explanation of Carcinogenicity:NONE OF THE INGREDIENTS IN THIS PRODUCT  
IS LISTED BY NTP, IARC OR OSHA AS A CARCINOGEN.

Effects of Overexposure:EYES: MILD REDNESS AND DRYNESS. SKIN: NO  
ADVERSE EFFECT FOR SINGLE EXPOSURE. PROLONGED/REPEATED EXPOSURE MAY  
CAUSE IRRITATION. INHALATION: NO EFFECTS EXPECTED. INGESTION: SMALL  
AMOUNTS, NO EFFECT. LARGE AMOUNTS MAY CAUSE DIGESTIVE DISCOMFORT.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
=====  
First Aid Measures  
=====

First Aid:EYES: FLUSH WITH WATER. SKIN: WIPE OFF AND FLUSH WITH WATER.  
INHALATION: NO FIRST AID SHOULD BE NEEDED. INGESTION: NO FIRST AID  
SHOULD BE NEEDED.

=====  
Fire Fighting Measures  
=====

Flash Point Method:OC  
Flash Point:>250F,>121C  
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY  
CHEMICAL.  
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A  
FULL FACED S

ELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED  
CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE  
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN  
FOR SALVAGE OR DISPOSAL.

Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage

Precautions:STORE BELOW 90F (32C). USE REASONABLE  
CARE AND CAUTION.

Other Precautions:PROVIDE ADEQUATE VENTILATION. TRACES OF FORMALDEHYDE  
MAY FORM AT 302F (150C). PROVIDE GOOD VENTILATION WHEN HANDLING AT  
ELEVATED TEMPERATURES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. NIOSH/MSHA-APPROVED  
RESPIRATOR OR SCBA AS APPROPRIATE FOR EXPOSURE OF CONCERN.

Ventilation:MECHANICAL (GENERAL) VENTILATION TO KEEP EXPOSUR  
E LEVELS  
BELOW PEL.

Protective Gloves:RUBBER GLOVES FOR PROLONGED EXPOSURES.

Eye Protection:CHEMICAL SAFETY GOGGLES IF SPLASHING.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE  
EATING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

KEY1:N1. THIS IS PART B OF A TWO PART PRODUCT.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>300F,14

9C

Vapor Pres: