View NSN Online: https://aerobasegroup.ae/nsn/8010-00-901-1059

Product ID:745614 ENAMEL ALKYD SG GRAY 26152 MSDS Date:01/01/1985 FSC:8010 NIIN:00-901-1059 MSDS Number: BFVMN === Responsible Party === Company Name: PRATT AND LAMBERT INC Address:16116 E 13TH ST Box:2153 City:WICHITA State:KS ZIP:67201 Country:US Info Phone Num:316-733-1361 Emergency Phone Num:316-733-1361 CAGE:61196 === Contractor Identification === Company Name: PRATT AND LAMBERT INC Box:6027 City:CLEVELAND State:OH ZIP:44101-1027 Country:US Phone:216-566-2902 CAGE:61196 Ingred Name: MINERAL SPIRITS CAS:64475-85-0 RTECS #:PY8240000 Fraction by Wt: 35% ACGIH TLV:500 PPM Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;919

2 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE CAS:14464-46-1 RTECS #:VV7325000 OSHA PEL:SEE TABLE Z3 ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:TALC (CONTAINING NO ASBESTOS) CAS:14807-96-6 RTECS #:WW2710000 OSHA PEL:2 MG/M3 RDUST ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name: VOC. ORGANIC CMPD 3.7 LB/GAL LESS WATER & NPRS\* 444 G/L

LESS WATER VOC. 8.4 LB/GAL SOLIDS 1008 G/L SOLIDS CALCU RTECS #:9999999VO

Effects of Overexposure:INHALATION-ANESTHETIC,IRRITATION OF RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION.

First Aid:CONTACT-FLUSH SKIN AND EYES WITH WATER WHILE REMOVING CONTAMINATED CLOTHING. INHALATION-REMOVE TO FRESH AIR. CALL PHYSICIAN IF SYMPTOMS PERSIST.

Flash Point:104F, 40C TCC Lower Limits:1.10 Extinguishing Media:NFPA CLASS B EXTINGUISHER; POLYMER FOAM FOR LARGE FIRES Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTI LATE AREA. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

Handling and Storage Precautions: DO NOT STORE ABOVE 120F STORE LARGE QUANTITIES IN BUILDING DESIGNED TO COMPLY WITH OSHA 1910.106 Other Precautions: GROUND CONTAINERS WHEN POURING. AVOID FREE FALL OF LIQUID IN XS OF FEW INCHES DO NOT FLAME CUT, BRAZE OR WELD COATER MATERIAL WITHOUT BUR OF MINES APPROVED RESPIRATOR OR APPROPIATE VENTILATION ===== Respiratory Protection: OPEN AREA: BUR MINES MECH RESPIRATOR; CLOSED: BUR MINES CHEM/MECH FILTE Ventilation: GENERAL DILUTION OF LOCAL EXHAUST TO KEEP TLV BELOW LIMIT Protective Gloves: REG IF LONG CON Eye Protection: TO PROTECT VS SPLASHING Other Protective Equipment: PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING. Supplemental Safety and Health HCC:F2 В oiling Pt:B.P. Text:311-373F Vapor Density:ETHER Percent Volatiles by Volume:57 Stability Indicator/Materials to Avoid:YES Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS-INCINERATE IN APPROVED FACILITY-DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.