

FEL-PRO -- C-100 -- 8030-00-915-6123

=====  
Product Identification  
=====

Product ID:C-100

MSDS Date:01/01/1987

FSC:8030

NIIN:00-915-6123

MSDS Number: BFWHF

=== Responsible Party ===

Company Name:FEL-PRO

Emergency Phone Num:312-674-7700

CAGE:MO224

=== Contractor Identification ===

Company Name:FEL-PRO

CAGE:MO224

Company Name:FEL-PRO INC DIV OF FELT PRODUCTS MFG CO

Address:7450 N MCCORMICK

Box:1103

City:SKOKIE

State:IL

ZIP:60076-4046

Country:US

Phone:847-674-7700 OR 312-761-4500

CAGE:73165

=====  
Composition/Information on Ingredients  
=====

Ingred Name:LEAD MONOXIDE (LEAD OXIDE YELLOW)

CAS:1317-36-8

RTECS #:OG1750000

Fraction by Wt: 28%

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.15 MG/M3(PB); 8990

=====  
Hazards Identification  
=====

Effects of Overexposure:NONE EXPECTED.POSSIBLE REDNESS,IRRIT OF  
SKIN,EYE UPON PROLONG,REPEAT CONTACT IN SEN

SIT INDIVIDUALS.

=====  
First Aid Measures  
=====

First Aid:SKIN:WASH WITH SOAP AND WATER.IF IRRIT OCCURS,CONSULT PHYSICIAN.EYE:FLUSH WITH TEPID WATER 15 MINS HOLDING EYELIDS APART.CONSULT PHYSICIAN IMMEDIATELY.INGESTION:CONTAINS INORGANIC LEAD MONOXIDE;CONSUL T PHYSICIAN IMMEDIATELY.

=====  
Fire Fighting Measures  
=====

Flash Point:390F,199C COC  
Extinguishing Media:WATER FOG,DRY CHEMICALS,FOAM,CO\*2.  
Fire Fightin  
g Procedures:USE EXTING MEDIA.DO NOT DIRECT H\*2O DIRECTLY INTO FIRE.SUPP  
Unusual Fire/Explosion Hazard:SAME AS FOR PETRO GREASE FIRE,EXCEPT >750F,IN PRESENCE OF O\*2,MATRL MAY DECOMPOSE TO SULFUR OXIDES.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE SOURCES OF IGNITION.SCOOP,MOP UP OR ABSORB ON RAGS.COMPLETE CLEANUP WITH DETERGENT AND WATER OR HIGH FLASH POINT SOLVENT CLEANER WITH ADEQUATE VENTILATION.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:USE NORMAL STORAGE AND HANDLING AS FOR PETROLEUM GREASE PRODUCTS.AVOID IGNITION SOURCES.  
Other Precautions:KEEP OUT OF REACH OF CHILDREN.

=====  
Exposure Controls/Personal Protection  
=====

Ventilation:LOCAL EXHAUST,MECHANICAL(GENERAL)50 F.P.M. ACCEPTABLE  
Protective Gloves:NONE REQUIRED  
Eye Protection:SUFFICIENT TO PREV CONTAC  
Other Protective Equipment:NONE REQUIRED  
Supplemental Safety and Heal  
th  
MSDS PREP:23OCT85.SPECIAL FIRE-FIGHT:USE EYE PROTECTION.WEAR SCBA IN CONFINED AREA.CALL MFR FOR FLASH POINT METHOD.

=====  
Physical/Chemical Properties  
=====

HCC:N1  
Boiling Pt:B.P. Text:400F,204C  
Vapor Pres:0  
Spec Gravity:1.53  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:BLACK PASTE,SLIGHT PETROLATUM ODOR  
Percent Volatiles by Volume:NIL

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES  
STRONG

OXIDIZERS,I.E.,PEROXIDES,PERMANGANATES,NITRIC ACID

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:PYROLYSIS YIELDS CO,CO\*2,POSSIBLE SO\*X  
ABOVE 750F

===== Disposal Considerations =====

Waste Disposal Methods:USE CONTROLLED INCINERATION OR BURY IN A POSTED  
TOXIC SUBSTANCES LANDFILL IN ACCORDANCE WITH FEDERAL,STATE AND  
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is fo

rmulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.