

DUPONT E I DE NEMOURS & CO -- HALON 1301 FIRE EXTINGUISHER -- 4210-00-930-2625

=====
Product Identification
=====

Product ID:HALON 1301 FIRE EXTINGUISHER

MSDS Date:01/01/1987

FSC:4210

NIIN:00-930-2625

MSDS Number: BFXDW

=== Responsible Party ===

Company Name:DUPONT E I DE NEMOURS & CO

Address:FREON PRODUCTS DIVISION

City:WILMINGTON

State:DE

ZIP:19898

Country:US

Info Phone Num:302-774-2421

Emergen

cy Phone Num:800-441-7515

CAGE:23027

=== Contractor Identification ===

Company Name:DU PONT E I DE NEMOURS AND CO INC PETROCHEMICALS DEPT

Address:1251 BRANDYWINE BLDG

Box:City:WILMINGTON

State:DE

ZIP:19898

Phone:302-773-5676

CAGE:73925

Company Name:STOTTS-FRIEDMAN CO INC

Address:2608 E RIVER RD

Box:City:DAYTON

State:OH

ZIP:45439-0839

Country:US

Phone:513-298-5555

CAGE:7A884

Company Name:TETRA MFG CORP (CAGE CANCELLED)

Address:CAGE CANCELLED

City:WESTBURY

State:NY

ZIP:11590

Country:US

Phone:NO

NE
CAGE:23027

=====
Composition/Information on Ingredients
=====

Inged Name:1,1,2-TRICHLORO-1,2,2-TRIFLUOROETHANE (FREON 113) (SARA III)
CAS:76-13-1
RTECS #:KJ4000000
Fraction by Wt: 100%
Other REC Limits:1000 PPM
OSHA PEL:1000PPM/1250STEL
ACGIH TLV:1000PPM/1250STEL9192
Ozone Depleting Chemical:1

=====
Hazards Identification
=====

LD50 LC50 Mixture:TLV IS 1000 PPM
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:SHORTNESS OF BREATH, GIDDINESS, CARDIAC ARRHYTHMIAS.
Medical Cond Aggravated by Exposure:HEART AND LUNG DISEASES.

=====
First Aid Measures
=====

First Aid:INH:REMOVE TO FRESH AIR.CALL DOCTOR. DO NOT GIVE EPINEPHRINE OR SIMILAR DRUGS;EYE/SKIN:FLUSH WITH WATER.

=====
Fire Fighting Measures
=====

Extinguishing Media:PRODUCT IS A FIRE EXTINGUISHER.
Fire Fighting Procedures:COOL CYLINDERS WITH WATER.
Unusual Fire/Explosion Hazard:CYLINDERS WILL EXPLODE IN THE HEAT OF FIRE.

=====
Accidental Release Measures
=====

Spill Release Procedures:VENTILATE AREA,ESPECIALLY LOW PLACES WHERE HEAVY VAPOR MIGHT COLLECT.REMOVE OPEN FLAMES.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL,DRY WELL VENTED LOW FIRE RISK AREA. PROTECT FROM HEAT,SHOCK,FRICTION.

KEEP CONTAINERS
CLOSED.

Other Precautions:DO NOT HEAT ABOVE 125F.-FOR FURTHER INFO. SEE FREON
(R)BULLETINS S-35A,B-29C.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE AIR MASK IN CONC. ABOVE 10% BY VOLUME
Ventilation:MECH,ESPEC.IN LOW PLACES;LOCAL EXH,WHEN LG.AMTS.RELEASED
Protective Gloves:TYPE AS REQD
Eye Protection:SAFETY GLASSES
Other Protective Equipment:NONE
Supplemental Safety and Health
UNDATED MSDS/VAP.PRESS. 12158MM HG@77F/

=====
Physical/Chemical Properties
=====

HCC:G3
Boiling Pt:B.P. Text:-72F,-58C
Vapor Pres:SUP
Vapor Density:8.7
Spec Gravity:1.538
Evaporation Rate & Reference:RAPID
Solubility in Water:0.03%@77F
Appearance and Odor:COLORLESS LIQUID-SLIGHT ETHEREAL ODOR
Percent Volatiles by Volume:100.

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
LIQ.CONTACT W/ALK&ALK.EARTH METALS-POWDERED AL,ZN,BE,ETC.
Stability Co
Condition to Avoid:OPEN FLAMES OR HIGH TEMPS.
Hazardous Decomposition Products:HF,HBR,FREE BR*2,POSSIBLY CARBONYL
HALIDES.

=====
Disposal Considerations
=====

Waste Disposal Methods:NONE

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate an

d

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.