

KOPPERS CO, INC -- L-95A-66 ACRYLIC LACQUER,WHITE (17875) -- 8010-00-935-6609

=====
Product Identification
=====

Product ID:L-95A-66 ACRYLIC LACQUER,WHITE (17875)

MSDS Date:01/01/1985

FSC:8010

NIIN:00-935-6609

MSDS Number: BFXTF

=== Responsible Party ===

Company Name:KOPPERS CO, INC

Country:US

Emergency Phone Num:213-726-8666

CAGE:LO336

=== Contractor Identification ===

Company Name:KOPPERS CO, I

NC

CAGE:LO336

Company Name:KOPPERS CO., INC.

Address:950 KOPPERS BLDG.

Box:City:PITTSBURGH

State:PA

ZIP:15219

Phone:(412) 227-2000

CAGE:6V069

=====
Composition/Information on Ingredients
=====

Ingred Name:N-BUTYL ALCOHOL (SARA III)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 3.00%

OSHA PEL:100 PPM

ACGIH TLV:S, C 50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:CYCLOHEXANONE (SARA III)

CAS:108-94-1

RTECS #:GW1050000

Fraction by Wt: 1.70%

OSHA PEL:S, 50 P

PM
ACGIH TLV:S, 25 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)
CAS:111-15-9
RTECS #:KK8225000
Fraction by Wt: 8.70%
OSHA PEL:S,100 PPM
ACGIH TLV:S, 5 PPM; 9192

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 2.70%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 1.10%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:IRRIT TO EYES, NOSE & THROAT FROM VAPORS AT OR ABOVE 50 PPM. HIGHER CONCENTRATIONS: DROW, DIZ, COMA

=====
===== First Aid Measures =====

First Aid:INH: REMOVE TO FRESH AIR. IF NOT BREATHING; ARTIF RESPIR PREFERABLY MOUTH-TO-MOUTH. CALL MD. EYES: FLUSH W/WATER & CONTACT MD. SKIN: WASH THOROUGHLY W/SOAP & WATER. WASH CLOTHING BEFORE REUSE. INGEST: CALL MD! NO INDUCED VOMIT!

=====
===== Fire Fighting Measures =====

Flash Point:23F TCC
Lower Limits:1.0
Upper Limits:11.2
Extinguishing Media:WATER FOG, FOAM, DRY CHEMICAL OR CO*2
Fire Fighting Procedures:COOL CLOSED CONTAINERS W/WATER. AIR-SUPPLY EQUIP CL AREA.
Unusual Fire/Explosion Hazard:KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAMES.

=====

=== Accidental Release Measures =====

Spill Release Procedures:RECOVER ALL POSSIBLE, THEN WIPE UP W/RAGS,
SAWDUST, ETC.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED AND UPRIGHT TO
PREVENT LEAKAGE. AVOID FLAMES,OPEN
LIGHTS,WELDING,SMOKING,SPARKS,ETC.

Other Precautions:MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN
CONFINED AREAS,TANK OR PIT WITHOUT ADEQUATE VENTILATION.

=====

Exposure Controls/Personal Protection =====

Respiratory Protection:ORGANIC CANISTER IF OXYGEN CONTENT ADEQUATE &
VAPOR CONCENT