

SPRINGVILLE MFG CO INC -- LACQUER ACRYLIC GREEN 14187 -- 8010-00-935-7070

=====
Product Identification
=====

Product ID:LACQUER ACRYLIC GREEN 14187

MSDS Date:01/01/1987

FSC:8010

NIIN:00-935-7070

MSDS Number: BFXVL

=== Responsible Party ===

Company Name:SPRINGVILLE MFG CO INC

Address:8798 NORTH ST

City:SPRINGVILLE

State:NY

ZIP:14141-9648

Country:US

CAGE:61190

=== Contractor Identification ===

Comp

any Name:SPRINGVILLE MFG CO INC

Address:8798 NORTH ST

Box:City:SPRINGVILLE

State:NY

ZIP:14141-9648

Country:US

CAGE:61190

=====
Composition/Information on Ingredients
=====

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR
1910.1025),(CRO3 CEILING 0.1 MG/M3)

CAS:7758-97-6

RTECS #:GB2975000

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.05MG/M3(CR)A2;8990

Ingred Name:CYCLOHEXANONE (SARA III)

CAS:108-94-1

RTECS #:GW1050000

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Q

ty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
Hazards Identification
=====

Effects of Overexposure:EYES:IRRIT;SKIN:TOXIC,DEFAT,IRRIT;INHAL:IRRIT
OF RESP,NOSE,THROAT,CNS DEPRESSION,HEAD,NAUSEA,DIZZINS

=====
First Aid Measures
=====

First Aid:INHAL:REMOVE FR EXPOSURE & PROVIDE FRESH AIR.SPLASH EYES-FLUSH
IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR 15 MIN.SPLASH SKIN:REMOV
CLOTHING & WASH ALL AFFECTED AREA WITH WATER.INGEST:DO NOT INDUCE
VOMITING.CONSULT
A CR . IMMEDIATELY IN ALL CASES

=====
Fire Fighting Measures
=====

Flash Point:24F/-4.4C(ESTIMATED)
Extinguishing Media:CLASS B EXTINGUISHING, CARBON DIOXIDE, DRY CHEM OR ALCOHOL
FOAM
Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS, WATER MAY BE
INEFFECTIVE.
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED.ISOLATE FROM
HEAT,ELECTRICAL EQUIPMENT,SPARKS & OPEN FLAME.DO NOT APPLY TO VERY HOT SURFACES

=====
Accidental Release Measures
=====

Spill

Release Procedures:REMOV ALL SOURCES OF IGNIT(FLAMES,HOT SURFACES,ELECTRICAL,STATIC OR FRICTIONAL SPARKS).VENTILAT AREA & AVOID BREATHING VAPORS.REMOV W/INERT ABSORB & NON-SPRAKING TOOLS.STEPS MUST BE TAKN TO PREVNT CON TAM OF GROUND WATR OR STREAMS.

==== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOV 120F STORE LG QUANTITIES IN COMPLIA W/OSHA 1910.106.CONTNRS SHLD BE GROUNDED & BONDED TO THE RECEIVING CONTNR.

Other Precautions:DO NOT CUT OR WELD ON EMPTY CONTAINER. DO NOT USE UNTIL ALL SAFETY PRECAUTIONS HAE BEEN READ & FULLY UNDERSTOOD BY THE USER.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPRVD MECH RESPIRAT TO REMOV OVERSPRAY WHN SPRAYING IN OUTDR

Ventilation:PROVID GEN DILUT/LOC EXHAUST BRNT TO KP CONCENT BELO ACEP TL

Protective Gloves:SOLVENT,IMPERME

Eye Protection:SAFETY EYEW R

Other Protective Equipment:PROTECTV E QPMT TO PRVNT SKN CONTCT.SE

OSHA,29 1910.1025

Supplemental Safety and Health

MSDS DATE 6/21/86:CONTAINS LEAD AND CR;INGESTION;G.I

IRRIT,NAUSEA,VOMITING,CAN BE FATAL;CHRONIC EXPOSURE:BRAIN DAMAGE,LUNG CANCER DUE TO INSOLUBLE CHROMATE,LIVER DAMAGE.NUMBNESS,TREMORS,COLIC

==== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:86-314F

Vapor Density:>1.0

Evaporation Rate & Reference: