View NSN Online: https://aerobasegroup.com/nsn/8010-00-935-7072

AMERON INDUSTRIAL COATINGS DIVISION -- 794-504 -- 8010-00-935-7072

======== Product Identification ===========

Product ID:794-504 MSDS Date:01/01/1987

FSC:8010

NIIN:00-935-7072

MSDS Number: BFXVR === Responsible Party ===

Company Name: AMERON INDUSTRIAL COATINGS DIVISION

Emergency Phone Num:316-733-1361

CAGE:09869

=== Contractor Identification ===

Company Name: AMERON INDUSTRIAL COATINGS DIVISION

Address:20 1 N BERRY ST Box:City:BREA

State:CA

ZIP:92621-3904 Country:US

Phone:714-529-4597

CAGE:09869

====== Composition/Information on Ingredients ========

Ingred Name: ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000 Fraction by Wt: 3.9%

OSHA PEĹ:400 PPM/500 STEL ACGIH TLV:400 PPM/500STEL;9192

Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000 Fraction by Wt: 26.0%

OSHA PEL:200 PPM/300 STEL ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:50

00 LBS

DOT Rpt Qty:5000 LBS

Ingred Name: TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 12.4%

OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: CYCLOHEXANONE (SARA III)

CAS:108-94-1

RTECS #:GW1050000 Fraction by Wt: 22.7% OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

========== Hazards Identification ================

Effects of Overexposure:INHALE:ANESTHETIC,IRR ITATION OF RESPIRATORY TRACT,ACUTE NERVOUS SYSTEM DEPRESSION

First Aid:INCASE OF CONTACT, FLUSH SKIN AND EYES WITH PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH AIR. CALL A PHYSICIAN IF SYMPTOMS PERSIST

Flash Point:45F,7C TCC

Lower Limits: 1.0

Extinguishing Media:CARBON DIOXIDE/DRY CHEMICAL-SMALL;POLYMER FOAM-

LARGE FIRE

Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS AVAILABLE FOR FIREMEN

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE DUE TO PRESSURE BUILD UP

======== Accidental Release Measures ==========

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION(FLAMES HOT SURFACES,AND ELECTRICAL,STATIC,OR FRICTIONAL SPARKS)AVOID BREATHING VAPORS.VENTILATE AREA.REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

=====

======== Handling and Storage ===========
Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS ONE FLAMMABLE (OR COMBUSTIBLE)LIQUID Other Precautions:DO NOT TAKE INTERNALLY,CONTAINERS SHOULD BE GROUNDED WHEN POURING,AVOID FREE FALL IN EXCESS OF A FEW INCHES,DO NOT FLAME CUT,BRAZE,OR WELD COATED MATERIAL WITHOUT VENTILATION
====== Exposure Controls/Personal Prote ction ========
Respiratory Protection:APPROVED BUREAU OF MINES RESPIRATORS W/PROPER FILTER OR HOOD Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY&WELDING Protective Gloves:ALOT OF CONTACT Eye Protection:USE EYEWEAR IF SPLASHING Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING Supplemental Safety and Health BP 79-153C. EFFTS. OF OVEREXPOSURE-HEADACHE DIZZINESS ETC. OR
COMA.PRIMARY IRRITATION FOR SKIN OR EYE CONTACT ==================================
HCC:F3 Boiling Pt:B.P. Text:174-308F Evaporation Rate & Dercent Volatiles by Volume:70.0
========= Stability and Reactivity Data =========

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.INCINERATE IN APPROVED FACILITY.DO NOT

INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this informati on to their particular situation.