View NSN Online: https://aerobasegroup.com/nsn/8010-00-935-7079

Product ID:LACQUER, ACRYLIC (F /NAVAL WEAPONS SYS) AERBLK MSDS Date:01/01/1987 FSC:8010 NIIN:00-935-7079 MSDS Number: BFXWN === Responsible Party === Company Name: ILLINOIS BORNZE POWDER & PAINT CO Address:300 EAST MAIN STREET City:LAKE ZURICH State:IL ZIP:60047-2580 Country:US Info Phone Num:312-488-8001 Emergency Phone Num:800-228-5635 CAGE:MO302 === Contractor Identification === Company Name: ILLINOIS BORNZE POWDER & PAINT CO Address:300 EAST MAIN STREET **City:LAKE ZURICH** State:IL ZIP:60047-2580 Country:US Phone:312-488-8001 CAGE:MO302 Company Name: ILLINOIS BRONZE PAINT COMPANY Address:300 EAST MAIN STREET **City:LAKE ZURICH** State:IL ZIP:60047-2580 Country:US Phone:800-228-5635 CAGE:91794

Ingred Name:IOSBUTANE/PROPANE MIXTURE (50:50 MOL WT%) Fraction by Wt: 29.4% ACGIH TLV:UNK

Ingred Name:METHYLENE CHLORIDE (DICHLOROMETHANE) (SARA III) CAS:75-09-2 RTECS #:PA8050000 Fraction by Wt: 29.3% Other REC Limits:NONE RECOMMENDED OSHA PEL:500 PPM; Z-2 ACGIH TLV:50 PPM, A2; 9394 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 22.2% OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:10 00 LBS

Effects of Overexposure:INHAL:ANEST:IRRIT OF THE RESPIRAT TRACT OR ACUTE NERVS SYS DEPRESS CHARACT BY HDACHE,DIZZ,STAGG(SUPP

First Aid:FUMES-REMOV FR EXPOS.GET FRESH AIR.SPRAY(EYES)FLUSH IMMED W/LG QNTITIES OF RUNNING WATER F/AT LEAST 15 MIN.TAKE TO DR;SPRAY SKIN.WIPE OFF W/TOWEL.REMOVE REMAIN W/MINERAL SPIRITS,TURPENTINE OR LACQ THI

NNER, IN CASE OF LACQ. WASH W/SOAP & WATER.

Flash Point:-40F -40C
Lower Limits:1.3%
Extinguishing Media:USE NFPA CLASS B EXTING(CARBON DIOXIDE,DRY CHEM OR FOAM)
Fire Fighting Procedures:WEAR GOGG & SELF-CONTAIN-BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:CANS WILL RUPT FR INTERN PRESSURE AT ABOUT 190F & DISCHG FLAMBL CONTENTS.TOXIC FUMES IF HEAT TO DECO

======== Accidental Release Measures ========

========

Spill Release Procedures: REMOV ALL SOURCES OF IGNIT (FLAMES, HOT SURFAC & ELECTR, STATIC OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. REMOV INERT ABSORBENT.

Handling and Storage Precautions:DO NOT STORE ABOV 120F.STORE LG QNTITIES IN BLDGS DESIGNED & PROTECTED F/STORAGE OF NFPA CLASS 1A FLAMMABLE LIQUIDS

Other Precautions:DO NOT SPRAY IN EYES.DO NOT PUNCT OR INCINERAT CNS.DO NOT STICK

PIN,NAIL OR ANY OTHER SHARP OBJCTS INTO OPENING ON TOP OF CN.DO NOT TAKE INTERN.DO NOT FLAME CUT,BRAZE OR WELD.APPRVD RESPIR/VEN

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:F/CASUAL USE NONE REQD Ventilation:DILUTION OR EXHAUST TO KEEP BELOW TLV Protective Gloves:NONE Eye Protection:NO SPEC PROTECTON REQD Supplemental Safety and Health OVEREXPOS:GAIT,CONFUSION,UNCONSCIOUSNESS OR COMA.SKIN OR EYE CONTACT: PRIMARY IRRIT.

HCC:V3 Boiling Pt:B.P. Text:42-391F Vapor Density:HEAV Evaporation Rate & amp; Reference:PROPELLANT-FASTER Percent Volatiles by Volume:90

Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products:HYDROGEN CHLORIDE,CARBON MONOXIDE,PHOSGENE

Waste Disposal Methods: DISPOSE OF IN ACCORDA

NCE W/LOC STATE & FED

REGULATIONS.INCINERATE IN APPRVD FACILITY.DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional ad vice to verify and

assume responsibility for the suitability of this information to their particular situation.