

KOPPERS COMPANY, INC -- L-1511 -- 8010-00-941-8712

=====
Product Identification
=====

Product ID:L-1511

MSDS Date:01/01/1985

FSC:8010

NIIN:00-941-8712

MSDS Number: BFYJY

=== Responsible Party ===

Company Name:KOPPERS COMPANY, INC

Emergency Phone Num:213-726-8666

CAGE:EO463

=== Contractor Identification ===

Company Name:KOPPERS CO INC

Address:5431 DISTRICT BLVD

Box:City:VERNON

State:CA

ZIP:90040

C

Country:US

CAGE:71191

Company Name:KOPPERS COMPANY, INC.

CAGE:EO463

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM

ACGIH TLV:200 PPM/300STEL;9394

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TO

LUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (HEXONE) (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:50 PPM/75 STEL; 9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:VAPORS- 50PPM IRRITATE EYES,NOSE&THROAT. HIGHER
CONC-DROWSINESS,DIZZINESS FOLLOWED BY COMA.

=====
===== First Aid Measures =====

First Aid:VAPORS-REMOVE TO FRESH AIR. IF NOT BREATHING GIVE ARTIFICIAL
RESPIRATION. CALL DOCTOR. SKIN-WASH THOROUGHLY W SOAP & WATER.
EYES-FLUSH W LGE AMTS WATER FOR 15 MIN.-GET MEDICAL AID.
INGESTION-DO NOT IN DUCE VOMITING.CALL DOCTOR IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point:26F, -3 TOC
Extinguishing Media:WATER,F
OG, DRY CHEM OR CO2
Fire Fighting Procedures:AIR SUPPLIED EQUIP/ENCLOSED AREA. COOL FULL
CONTAINERS.WATER
Unusual Fire/Explosion Hazard:KEEP AWAY FROM HEAT, SPARK OR OPEN FLAME.

=====
===== Accidental Release Measures =====

Spill Release Procedures:RECOVER ALL POSSIBLE, THEN WIPE UP W RAGS,
SAWDUST, ETC. REMOVE ALL SOURCES OF IGNITION.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED. AVO

ID FLAMES,
WELDING, SMOKING, SPARKS, OPEN LIGHTS, ETC.
Other Precautions: MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN
CONFINED AREAS, TANK OR PIT WO ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Ventilation: LOCAL & MECHANICAL
Protective Gloves: RUBBER
Eye Protection: GOGGLES
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC: V3
Vapor Density: >AIR
Evaporation Rate & Reference: FAST
Solubility in Water: SLIGHT
Appearance and Odor: TYPICAL PAINT ODOR
Percent Volatiles by Volume: 74.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

===== Disposal Considerations =====

Waste Disposal Methods: IN ACCORD LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.