

DRILUBE COMPANY -- DRILUBE #6A -- 9150-00-948-6912

===== Product Identification =====

Product ID:DRILUBE #6A
MSDS Date:10/28/1986
FSC:9150
NIIN:00-948-6912
MSDS Number: BFYSS
=== Responsible Party ===
Company Name:DRILUBE COMPANY
Address:711 W BROADWAY
City:GLENDALE
State:CA
ZIP:91204-1009
Country:US
Info Phone Num:213-245-1804
Emergency Phone Num:(213) 245-1804
CAGE:HO746
=== Contractor Identifi
cation ===
Company Name:DRILUBE CO
Address:711 W BROADWAY
Box:City:GLENDALE
State:CA
ZIP:91204-1009
Country:US
Phone:818-240-8144
CAGE:06186
Company Name:DRILUBE COMPANY
Address:711 WEST BROADWAY
Box:City:GLENDALE
State:CA
ZIP:91204
Country:US
Phone:213-245-1804
CAGE:HO746

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 37.0%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL ACETATE (SARA III)

CAS:141-78-6

RTECS #:AH5425000

Fraction by Wt: 12.0%

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 7.0%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:2-BUTOXYETHANOL

CAS:111-76-2

RTECS #:KJ8575000

Fraction by Wt: 5.0%

OSHA PEL:

S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

Ingred Name:MOLYBDENUM DISULFIDE

CAS:1317-33-5

RTECS #:QA4697000

Fraction by Wt: 9.0%

OSHA PEL:10 MG/M3 TDUST (MO)

ACGIH TLV:10 MG/M3 (MO); 8990

Ingred Name:MODIFIED EPOXY

Fraction by Wt: 17.0%

Ingred Name:CATALYST

Fraction by Wt: 0.03%

Ingred Name:ADDITIVES

Fraction by Wt: 9.0%

Ingred Name:OTHER COMPONENTS

Fraction by Wt: 4.0%

Ingred Name:INGREDIENTS #06,07,08,09 WERE ADDED FROM AN OLD MSDS DATED
AUG 30,1977.(MORE DETAILED INFORMATION)

RTECS #:99999

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:ACUTE:DRYING OF SKIN:EYE
IRRITATION;ANESTHETIC EFFECTS,HEADACHE,DIZZINESS,NAUSEA,UPPER
RESPIRATORY IRRITATION. CHRONIC:NO DATA AVAILABLE.
Effects of Overexposure:DRYING SKIN;EYE IRRITN;INHALN:MAY CAUSE
ANESTHESIA,HEADACHE,DIZZ,NAUSEA,UPPER RESPTRY IRRITN,ETC.
Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MA
Y BE
WORSEN.

=====
First Aid Measures
=====

First Aid:INHALN:REMOVE TO FRESH AIR,ATTN;SKIN:WASH W MILD SOAP
SOLN;EYES:FLUSH W WATER FOR AT LEAST 15 MIN.GET MED ASST:IN SEVERE
IRRITN/CASES OF SKIN & EYES CALL PHYS.INGEST:GET MED ATTN.DO NOT
INDUCE VOMITIN G.

=====
Fire Fighting Measures
=====

Flash Point:65F/17.2C (TCC)
Lower Limits:1.0
Upper Limits:10.0
Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL,FOAM

Fire Fighting Procedures:WATER SPRAY IS INEFFECTIVE.WATER IS USED TO
COOL CONTAINER
Unusual Fire/Explosion Hazard:KEEP CONTAINERS CLOSED.ISOLATE FROM
HEAT,ELECTRICAL EQUIPMENT,SPARKS & OPEN FLAME

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION(FLAMES,HOT
SURFACES & ELECT.STATIC OR FRICTIONAL SPARKS.AVOID BREATHING
VAPORS.VENTILATE AREA.REMOVE SPILL WITH NON-SPARKING TOOLS.

=====
Handl

ing and Storage =====

Handling and Storage Precautions:STORE BELOW 120F.STORE LARGE
QUANTITIES IN BLDG FOR STORAGE OF OSHA CLASS 1 FLAMM LIQDS.KEEP
CONTNRS AGAINST PHYSICAL DAMAGE & AWAY FROM SOURCE OF IGN
Other Precautions:RESTRICTED VENTILATION AREA:BUREAU OF MINES APPROVED
CHEMICAL MECHANICAL FILTERS.DO NOT TAKE INTERNALLY.CONTAINER SHOULD
BE GROUNDED WHEN POURING.WHENEVER H*2O IS USED.USE FOG NOZZLE

===== Exposure Controls/Personal Protection ===
=====

Respiratory Protection:AIR SUPPLIED MASK IN CONFINED AREAS.
Ventilation:LOCAL EXHAUST IS PREFERRED TO CONTROL TLV.
Protective Gloves:RUBBER
Eye Protection:CHEM SPLASH GOGGLES
Other Protective Equipment:APRON
Supplemental Safety and Health
MSDS FROM DRIULUBE COMPANY DATED:10/28/86;; SPEC REF:MIL-L-46010B.

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:195-230F
Spec Gravity:1.066
Solubility in Water:NEGLIGIBLE
Appearance and Odor:GRAY
TO BLACK SOLUTION,CHARACTERISTIC ODOR.
Percent Volatiles by Volume:79.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING MATL & CORROSIVE MATERIALS.
Stability Condition to Avoid:SOURCE OF HEAT,SPARK,IGNITION,OPEN
FLAME,ETC.
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON
MONOXIDE & CO*2

===== Disposal Considerations =====

Waste Disposal Methods:INCIN

ERATE IN APPROVED FACILITY UNDER CONTROLLED
CONDITIONS.DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verif
y and
assume responsibility for the suitability of this information to their
particular situation.