View NSN Online: https://aerobasegroup.com/nsn/6810-00-949-0257

## 

Product ID:HEXANES MSDS Date:01/01/1987

FSC:6810

NIIN:00-949-0257

MSDS Number: BFYTT === Responsible Party ===

Company Name: MALLINCKRODT INC., SCIENCE PRODUCTS DIVISION

Address: PARIS BYPASS

Box:M City:PARIS State:KY ZIP:40361 Country:US

Info Phone Num:314-982-5000 Emergency Phone Num:314-9

82-5000 CAGE:62910

=== Contractor Identification ===

Company Name: MALLINCKRODT SPECIALTY CHEMICALS CO

Address:222 RED SCHOOL LANE

Box:City:PHILLIPSBURG

State:NJ ZIP:08865 Country:US

Phone:908-859-2151

CAGE:62910

======= Composition/Information on Ingredients ========

Ingred Name: HEXANE (N-HEXANE)

CAS:110-54-3

RTECS #:MN9275000 Fraction by Wt: >99% OSHA PEL:500 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

======== Hazards Identification =========

======
Effects of Overexposure:INH:MILD IRRITNT;ING:CAUSES NAUSEA,ABDOMNL PAIN,BLURD VISION;SKIN:IRRITATION,DRYNSS;EYES:IRRITN.
======================================
First Aid:INHAL:RMV TO FRESH AIR.IF NEEDED,GIVE CPR/OXYGEN.GET MD;INGEST:GIVE SEVRL GL OF WATER.DO NOT INDUCE VOMITG.IMMED GET MD;SKIN:FLUSH W/LG QTY OF H*2O FOR 15 MIN.REMV CONTMNTD CLOTHES.GET MD;EYES:IMMED F LUSH W/PLENTY OF H*2O FOR AT LEAST 15 MIN.GET MD.
======================================
Flash Point:-21.7C(-7F)-CC Autoignition Temp:Autoignition Temp Text:225C Lower Limits:1.1 Upper Limits:7.5
Extinguishing Media:DRY CHEMICALS,FOAM,CO*2;WATER SPRAY TO KEEP EXPSD CANS COOL
Fire Fighting Procedures:USE H*20 TO COOL EXPD CONTRS. USE SCBA & FULL PROT.CLTHG.
Unusual Fire/Explosion Hazard:ABOVE FLASH POINT,VAP-AIR MIXTURES ARE EXPLOSIVE.CONTACT W/OXIDIZERS MAY CAUSE FIRE & EXPLOSION.
========= Accidental Release M easures ====================================
Spill Release Procedures:RMV IGN SOURCES.VENT AREA.USE RESP PROTCTION & PROTCTV CLOTHG.KEEP OUT OF SURF H*2O,SEWRS/CONFND AREAS;SM SPILL:ABSORB W/PAPER TOWELS.EVAP UNDER FUME HOOD THEN BURN CAREFULLY;LG SPILL:DIKE AREA.CONTAI N & RECOVER SPILL IF POSS;SHOVL RESDUE INTO DRUMS.
======================================
Handling and Storage Precautions:PROTCT AGAINST PHYSICAL DAMAGE.STORE IN COOL,DRY WELL VNTLTD AREA AWAY FM IGN/HEAT SOURCES,OXIDZG MATL.OUTSIDE OR DETACHED STORAGE IS PREFERRED. Other Precautions:KEEP AWAY FROM HEAT,SPARKS,FLAMES.KEEP CONTNRS
CLOSED.USE W/ADEQUATE VENT.AVOID BRTHG MIST.WASH THOROUGHLY AFTER

HNDLG.BOND/GROUND CONTNRS WHEN TRNSFRG LIQUID.USE NON-SPARKG TYPE TOOL & EQUIP.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: SCBA, SUPPLIED AIR RESPIRATOR Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.

Protective Gloves: IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES
Other Protective Equipment:FULL PROTECTIVE CLOTHING,SAFETY SHOWER,EYE
WASH STATION
Supplemental Safety and Health
MSDS FROM MFR DATED 31JAN85,CONFORMS TO OSHA HAZ COMM STD

HCC:F2

Boiling Pt:B.P. Text:68C(157F)

Vapor Pres:124 Vapor Density:3.0 Spec Gravity:0.7

Evaporation Rate & Evaporation R

Solubility in Water: NEGLIGIBLE

Appearance and Odor:CLEAR VOLATILE LIQUID.GASOLI

NE-LIKE ODOR.

======== Stability and Reactivity Data =========

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS.DINITROGE TETRAOXIDE Stability Condition to Avoid:HEAT, IGNITION SOURCES Hazardous Decomposition Products:CO, CO\*2

======= Disposal Considerations ===========

Waste Disposal Methods:LG SPILL & LOT SIZES OF HAZ WASTE CAN BE ATOMIZED IN A RCRA APPRVD COMBUSTION CHAMBER OR DISPOSED OF IN A RCRA APPROVED LAND FILL FACILITY.D
O NOT FLUSH TO SEWER.ENSURE COMPLIANCE W/FED,STATE & LOCAL R EGS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibili

