

FILTRON CO.,INC. -- FA4396 -- 5915-00-952-3045

=====
Product Identification
=====

Product ID:FA4396
MSDS Date:01/01/1985
FSC:5915
NIIN:00-952-3045
MSDS Number: BFYYF
=== Responsible Party ===
Company Name:FILTRON CO.,INC.
Address:148 SWEET HOLLOW RD
City:OLD BETHPAGE
State:NY
ZIP:11804-1315
Country:US
Emergency Phone Num:914-699-2000
CAGE:MO240

==== Contractor Identification ====

Company Name:FILTRO
N CO INC
Address:148 SWEET HOLLOW RD
Box:City:OLD BETHPAGE
State:NY
ZIP:11804-1315
Country:US
Phone:914-699-2000
CAGE:81831
Company Name:FILTRON CO.,INC.
Address:148 SWEET HOLLOW RD
Box:City:OLD BETHPAGE
State:NY
ZIP:11804-1315
Country:US
CAGE:MO240

=====
Composition/Information on Ingredients
=====

Ingred Name:POLYCHLORINATED BIPHENYLS (PCBS) (SARA III)
CAS:1336-36-3
RTECS #:TQ1350000
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

=====
Hazards Identification
=====

=====

Effects of Overexposure:MAY CAUSE IRRITATION TO EYES, NOSE, AND THROAT
AND A SKIN RASH MAY INJURE LIVER

===== First Aid Measures =====

First Aid:EYES: FLUSH W/WATER IMMED. SKIN: WASH W/SOAP IMMED. INHALE
REMOVE TO FRESH AIR, RESPIR. AS NEEDED INGEST: MEDICAL ATTN. GIVE
LARGE QTY OF WATER, INDUCE VOMITING, BUT DO NOT MAKE UNCONSCIOUS
PERSON VOM IT.

===== Fire Fighting Measures =====

Extingui
shing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE
Fire Fighting Procedures:DO NOT USE WATER, WEAR RESPIRATOR AND
PROTECTIVE CLOTHING
Unusual Fire/Explosion Hazard:TOXIC GASES AND VAPORS I.E. HYDROGEN
CHLORIDE CARBON MONOXIDE

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. EVACUATE
UNPROTECTED PERSONS. STOP LEAK W/O RISK. WEAR SCBA & PROTECTIVE
CLOTHING. ABSORB LIQUID W/NONCOMB ABSORB. PLACE IN CLOSED CONTAINE
R
FOR DISPOSAL. VENTILATE AREA. D O NOT CONTAMINATE SEWER OR GROUND
WATER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED
AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP
CONTAINERS TIGHTLY CLOSED
Other Precautions:CHLORODIPHENYLS MAY ATTACK SOME TYPES OF RUBBER AND
PLASTIC.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NI

OSH/MSHA/MESA APPROVD SCBA
Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.
Protective Gloves:IMPERVIOUS
Eye Protection:GOGGLES/FACE SHIELD
Other Protective Equipment:WEAR FULL PROTECTIVE CLOTHING.
Supplemental Safety and Health
OVEREXPOS:CAN CAUSE FORMATION OF CYSTS.CAUSES STILLBIRTHS.IRRITATES
EYES,NOSE,THROAT.

===== Physical/Chemical Properties =====

HCC:Z3
Appearance and Odor:PALE YELLOW VISCOUS LIQUID W/HYDROCARBON ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:HIGH TEMPERATURES,IGNITION SOURCES
Hazardous Decomposition Products:HYDROGEN CHLORIDE, CO, & OTHER
TOXIC/IRRITATING GASES/FUMES.

===== Disposal Considerations =====

Waste Disposal Methods:CONTROLLED DISPOSAL REQD. GEN. V.HIGH TEMP
INCINERATION. IN ACCORDANCE WITH ALL LOCAL, STATE, & FEDERAL
REGULATIONS. PERMITTED DISPOSAL OP
ERATOR REQUIRED.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their

particular situation.