

ERGON LUBE OIL DIV, ERGON INC-MFR(PHIPPS PROD-DIS) -- MIL-L-26087B, GRADE II, LUBRICATING OIL -- 9150-00-965-2399

===== Product Identification =====

Product ID: MIL-L-26087B, GRADE II, LUBRICATING OIL

MSDS Date: 01/01/1987

FSC: 9150

NIIN: 00-965-2399

MSDS Number: BFZRW

=== Responsible Party ===

Company Name: ERGON LUBE OIL DIV, ERGON INC-MFR(PHIPPS PROD-DIS)

Emergency Phone Num: (901) 775-1247

CAGE: MO392

=

== Contractor Identification ==

Company Name: ERGON INC LUBE OIL DIV

Address: 1989 CHANNEL AVE

Box: City: MEMPHIS

State: TN

ZIP: 38113

Country: US

Phone: 901-775-1247

CAGE: 43928

Company Name: ERGON LUBE OIL DIV, ERGON INC-MFR(PHIPPS PROD-DIS)

CAGE: MO392

===== Composition/Information on Ingredients =====

Ingred Name: PARAFFINIC BRIGHT STOCK HYDROCARBONS

ACGIH TLV: 5MG/CUM(MIST)

Ingred Name: PARAFFINIC SOLVENT NEUTRAL PETROLEUM HYDROCARBON

===== Hazards Identification =====

Effects of Overexposure: SKIN: MAY IRRIT ON PROLONGED CONTACT; EYES: SPLASH MAY IRRIT/CAUSE REDNESS; INGEST: GI IRRIT, NAUSEA, VOMIT

===== First Aid Measures =====

First Aid: SKIN: WASH W. SOAP & H*2O EYES: FLUSH W. H*2O. INGESTED: GIVE 2 GLASSES H*2O; INDUCE VOMITING. CALL A PHYSICIAN. INHALE: REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. IF UNCONS DO NOT TAKE ANYTHING BY MOUTH.

===

=====
Fire Fighting Measures
=====

Flash Point:399F/204C (COC)

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.

Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*2O SPRAY TO COOL
CONTR.

Unusual Fire/Explosion Hazard:MAY IGNITE BY HEAT,SPARK,FLAME,AIR
EXPOSURE;MAY REIGNITE,CONTACT W H*2O PRODUCES FLAMM GAS.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE IGNITION S

SOURCES,VENTILATE AREA

WELL.ABSORB WITH VERMICULITE OR OTHER MATERIALS, SUCH AS
SAWDUST,RAGS,PAPER & PLACE IN CLOSED CONTAINER. USE NON SPARKING
TOOLS. WEAR PROPER PROTECTIVE EQUIPMENT DURING CLEAN UP.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED,LOW
FIRE RISK AREA. PROTECT FROM PHYSICAL DAMAGE.KEEP CONTAINERS
CLOSED. MAINTAIN STANDARD HYGIENE FOR CHEM HANDLING

Other Precautions:NOT KN
OWN TO MFR.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE SHOULD BE NEEDED

Ventilation:LOCAL EXHAUST TO CAPTURE VAP/MIST/FUMES;USE EXPLOSION PROOF

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES/FACE SHIELD

Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED CONTACT.

Supplemental Safety and Health

MSDS FROM ERGON INC DATED:5/9/86; SPEC REFERENCE: MIL-L-26087B, GRADE
II.

=====
Physical/Chemical Properties
=====

HCC:V6

Boiling Pt:B.P. Text:575F/302C

Vapor Pres:5.0

Spec Gravity:0.87

Evaporation Rate & Reference: