

CONSOLIDATED MOTOR OIL,INC. -- CONSOLMO A/W HYDRAULIC OIL 46 -- 9150-00-966-8833

===== Product Identification =====

Product ID:CONSOLMO A/W HYDRAULIC OIL 46

MSDS Date:01/20/1989

FSC:9150

NIIN:00-966-8833

MSDS Number: BFZXZ

=== Responsible Party ===

Company Name:CONSOLIDATED MOTOR OIL,INC.

Address:1773 PINE AVE

Box:427

City:VINELAND

State:NJ

ZIP:08360-3442

Country:US

Info Phone Num:609-691-1066

Eme

rgency Phone Num:609-691-1066

CAGE:9Z316

=== Contractor Identification ===

Company Name:CONSOLIDATED MOTOR OIL CO INC

Address:1773 PINE AVE

Box:427

City:VINELAND

State:NJ

ZIP:08360-3442

Country:US

Phone:609-691-1066

CAGE:9Z316

===== Composition/Information on Ingredients =====

Ingred Name:REFINED PETROLEUM OIL

Fraction by Wt: >99%

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:ANTIWEAR RUST AND OXIDATION INHIBITOR ADDITIVES (CONTAINS
ZINC DIALKYLDIT

HIOPHOSPHATE)
Fraction by Wt: 15 G/KG
Routes of Entry: Inhalation:NO Skin:UNKNOWN Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NONE NOTED.
Effects of Overexposure:EYES:IRRITATION. SKIN:DERMATITIS.
INGESTION:NAUSEA,VOMITING,DIARRHEA.
Medical Cond Aggravated by Exposure:NONE NOTED.

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH LARGE AMOUNTS OF WATER. SKIN:WASH WITH SOAP
AND WATER.REMOV
E CONTAMINATED CLOTHING. INGESTION:DO NOT INDUCE
VOMITING.SEEK MEDICAL HELP.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:>424F,>218C
Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE,WATER FOG.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND
PROTECTIVE CLOTHING.USE WATER SPRAY TO COOL FIRE EXPOSED
CONTAINERS.
Unusual Fire/Explosion Hazard:DIRECT WATER STREAM MAY CAUSE FROTHING.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE LIQUID.ABSORB REMAINING LIQUID IN
INERT ABSORBENT AND PLACE IN APPROPRIATE DISPOSAL CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED
AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP
CONTAINERS TIGHTLY CLOSED
Other Precautions:DO NOT APPLY HEAT OR FLAME TO CONTAINERS.

=====

Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT REQUIRED.USE ORGANIC RESPIRATOR IN
MIST CONCENTRATION.

Ventilation:NORMAL ROOM VENTILATION.

Protective Gloves:NITRILE.

Eye Protection:CHEM SPLASH GOGGLES

Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS & LEGS.

Work Hygienic Practices:WASH HANDS AFTER HANDLING. LAUNDER CONTAMINATED
CLOTHING BEFORE REUSE.

Supplemental Safety and Health
NONE.

===== Physical/Chemical Properties =====

HCC:V6

Vapor Pres:NEGLIGIBLE

Vapor Density:>1.0

Spec Gravity:0.88

Evaporation Rate & Reference:NEGLIGIBLE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AMBER COLOR LIQUID W/PETROLEUM OIL ODOR

Percent Volatiles by Volume:NEGLIG

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:NONE.

Hazardous Decomposition Products:FROM BURNING,EMITS CO,CO*2,TRACES

OXIDES OF S, P, & ZN.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN APPROVED INCINERATOR OR DISPOSE OF
IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL,STATE & FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants

this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.