

GULF OIL COMPANY,U.S. -- HARMONY 68 (FORMERLY HARMONY 53) -- 9150-00-966-8835

=====  
Product Identification  
=====

Product ID:HARMONY 68 (FORMERLY HARMONY 53)

MSDS Date:01/01/1985

FSC:9150

NIIN:00-966-8835

MSDS Number: BFZYJ

=== Responsible Party ===

Company Name:GULF OIL COMPANY,U.S.

Emergency Phone Num:(713) 651-0693

CAGE:GO897

=== Contractor Identification ===

Company Name:GULF OIL CO U.S. A DIV

OF GULF OIL CORP

Box:1519

City:HOUSTON

State:TX

ZIP:77001

Country:US

CAGE:34252

Company Name:GULF OIL COMPANY - U.S.A.

CAGE:GO897

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM HYDROCARBON-LUBE OIL STOCK

ACGIH TLV:5 MG/CUM (MIST)

=====  
Hazards Identification  
=====

Effects of Overexposure:SKIN IRRIT,DERMATITIS.EYE

IRRIT.INHAL:HEADACHE,DIZZINESS,CNS DEPRESSION.

=====  
First Aid Measures  
=====

First Aid:SKIN CONTACT:REMOVE CONTAMINATED CLOTHING & WASH W/SOAP &  
WATER.EYE CONTACT:FLUSH W/COPIOUS AMTS OF WATER.INHAL:REMOVE TO  
FRESH AIR.INGESTION:GIVE 2-4 OZ OF OLIVE OR VEGETABLE OIL & 1-2 OZ  
OF ACTIVATE D CHARCOAL.GET MEDICAL AID IMMEDIATELY.

=====  
Fire Fighting Measures  
=====

Flash Point:218C; 425F PMCC

Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL,FOAM ARE PREFERRED

Fire Fighting Procedures:USE FOAM & WATER SPRAY CARE

FULLY TO AVOID

EXCESSIVE FROTHING

Unusual Fire/Explosion Hazard:USE WATER TO COOL FIRE EXPOSED

CONTAINERS.SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURE.

===== Accidental Release Measures =====

Spill Release Procedures:STOP FLOW,ELIMINATE SOURCES OF IGNITION,AVOID EXCESSIVE INHALATION & SKIN CONTACT.ABSORB WITH INERT MATERIAL SUCH AS SAND OR VERMICULITE.STORE IN CLOSED CONTAINERS PENDING DISPOSITION.OBSERVE GOVERNMENTAL SPILL & WATER QUALITY

REGULATIONS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS TIGHTLY CLOSED.STORE AWAY FROM HEAT & OPEN FLAME.DO NOT STORE OR MIX W/STRONG OXIDANTS.WEAR OIL-IMPERVIOUS CLOTHING

Other Precautions:AVOID SKIN CONTACT & INHALATION OF VAPORS,MISTS,FUMES.REMOVE CONTAMINATED CLOTHING PROMPTLY & LAUNDER BEFORE REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AS REQUIRED IF TLV IS EXCEEDED OR IF MISTS/SPRAYS ARE PRESENT

Ventilation:AS NEEDED TO KEEP HOT VAPORS & MISTS BELOW TLV.

Protective Gloves:RECOMMENDED

Eye Protection:GOGGLES,SAFETY GLASSES

Other Protective Equipment:APRON,ETC MADE OF BUTYL RUBBER,PVA,POLYETHYLENE,NEOPRENE

Supplemental Safety and Health

MIL-H-46001C, GRADE 3; UNIT OF ISSUE: 55 GAL DRUM.POUR POINT:-12C; 10F.FIRE POINT: 268C;515F (COC).VAPOR PRESSURE IS NEGLIGIBLE.

===== Physical/Chemical Properties =====

=====

HCC:V6

Boiling Pt:B.P. Text:393C; 740F

Vapor Density:>1

Spec Gravity:0.8767

Evaporation Rate & Reference:ESSENTIALLY ZERO

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR,PALE-COLORED OIL

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS SUCH AS CHLORINE & CONCENTRATED OXYGEN.

Stability Condition to Avoid:AVOID HIGH HEAT OR OPEN FLAME.

Hazardous Decomposition Pro

ducts:CARBON MONOXIDE,CO\*2

===== Disposal Considerations =====

Waste Disposal Methods:OBSERVE FED,STATE & LOCAL REGULATIONS.WHEN  
DISPOSING OF LARGE QUANTITIES,RECLAMATION MAY BE COST EFFECTIVE.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be ac  
curate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.