

EASTMAN KODAK -- ISOPROPYL ALCOHOL -- 6810-00-983-8551

=====  
Product Identification  
=====

Product ID:ISOPROPYL ALCOHOL

MSDS Date:01/01/1985

FSC:6810

NIIN:00-983-8551

MSDS Number: BGBLS

=== Responsible Party ===

Company Name:EASTMAN KODAK

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151

Emergency Phone Num:716-722-5151

CAGE:5K871

=== Contractor Iden

tification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8

050000  
Fraction by Wt: 99.0%  
OSHA PEL:400 PPM/500 STEL  
ACGIH TLV:400 PPM/500STEL;9192

=====  
Hazards Identification  
=====

Effects of Overexposure:EYE:IRRIT,BURNING,POSS  
DAMAGE.SKIN:IRRIT,BURNING.INH:IRRIT,NARCOS,HDACH.INGEST:NAUS,VOMIT,  
POSS DEATH

=====  
First Aid Measures  
=====

First Aid:EYE:IRRIGATE W/WATER FOR 15 MINUTES,CALL MD.SKIN:FLUSH  
W/WATER,REMOVE CONTAMINATED CLOTHING.INH:REMOVE TO FRESH  
AIR,REST  
ORE/SUPPORT BREATHING IF NEEDED,GIVE OXYGEN IF BREATHING  
DIFFICULT.INGEST:CALL M D IMMED.DILUTE W/WATER.INDUCE VOMIT IF  
CONSCIOUS.

=====  
Fire Fighting Measures  
=====

Flash Point:53F,12C,TCC  
Lower Limits:2.3  
Upper Limits:12.8  
Extinguishing Media:DRY CHEMICAL,CARBON DIOXIDE,ALCOHOL FOAM  
Fire Fighting Procedures:WEAR SCBA,USE WATER SPRAY TO COOL HEAT EXPOSED  
CANS.  
Unusual Fire/Explosion Hazard:MODERATE EXPLOSION HAZARD WHEN EXPOSED TO  
HEAT OR FLAM  
ES.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:KEEP SPARKS AND FLAME AWAY-PROVIDE GOOD  
VENTILATION.ABSORB MATERIAL IF POSSIBLE,OTHERWISE FLUSH AWAY WITH  
WATER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED  
Other Precautions:AVOID INHALATION OF VAPORS & REPEATED OR PROLONGED  
CONTACT WITH SIN OR CLOTHING. DO NOT TAKE INTERNALLY.WASH  
THOROUGHLY A

FTER HANDLING.DO NOT EAT OR SMOKE IN AREAS OF STORAGE  
OR USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:MULTIPURPOSE GAS MASK OR SELF CONTAINED  
APPARATUS

Ventilation:LOCAL-AS NEEDED

Protective Gloves:RUBBER

Eye Protection:GOGGLES

Other Protective Equipment:AS REQUIRED TO AVOID SKIN  
CONTACT,EYEWASH,SAFETY SHOWER

Supplemental Safety and Health

ITEM IS GRADE A OF FED SPEC TT-I-735A.

===== Physical/Chemical Properties ====  
=====

HCC:F2

Boiling Pt:B.P. Text:180F, 82C

Vapor Pres:33

Vapor Density:2.07

Spec Gravity:0.780

Evaporation Rate & Reference:1.6 (BU AC=1)

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR COLORLESS LIQUID. ALCOHOL ODOR

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZERS

Stability Condition to Avoid:OPEN FLAMES & SOURCES OF IGNITION

Hazardous Decomposition Products:CARBON MO

NOXIDE,CARBON DIOXIDE & TOXIC

FUMES

===== Disposal Considerations =====

Waste Disposal Methods:PLACE ABSORBED MATERIAL IN CONTAINERS SUITABLE  
FOR SHIPPING FLAMMABLE WASTES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
discl

aims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.