

DOW CORNING CORP -- DOW CORNING 77 PART ASSEMBLY PASTE -- 9150-00-985-7317

=====
Product Identification
=====

Product ID:DOW CORNING 77 PART ASSEMBLY PASTE

MSDS Date:06/11/1990

FSC:9150

NIIN:00-985-7317

MSDS Number: BGBXH

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone Num:517-496-5900

Emergency

Phone Num:517-496-5900

Preparer's Name:JACK L. SHENEGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

Company Name:E / M CO. DIV OF MORGAN CHEMICAL PRODUCTS INC

Address:100 COOPER CIR

Box:3969

City:PEACHTREE CI

TY
State:GA
ZIP:30269
Country:US
Phone:770-261-4835 / FAX: 770-631-0833
CAGE:8F024
Company Name:E/M CORP
Address:6940 FARMDALE AVE
City:NORTH HOLLYWOOD
State:CA
ZIP:91605-6210
Country:US
Phone:317-497-6100
CAGE:11770

=====
===== Composition/Information on Ingredients =====

Ingred Name:MOLYBDENUM DISULFIDE
CAS:1317-33-5
RTECS #:QA4697000
Fraction by Wt: 65%

Ingred Name:LITHIUM 12 HYDROXYSTEARATE (LITHIUM STEARATE)
CAS:7620-77-1
Fraction by Wt: 3.0%

Ingred Name:2,6-CIS-DIPHENYLHEXA
METHYLCYCLOTETRASIOXANE
CAS:33204-76-1
RTECS #:GZ4390000
Fraction by Wt: 121C
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS SUCH AS SULFUR
DIOXIDE.

=====

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP EXCESS GREASE. REMOVE RESIDUE IN ABSORBENT MATERIAL, AND PLACE IN APPROPRIATE DISPOSAL CONTAINER. FLUSH AREA WITH SOAP AND WATER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. KEEP AWAY FROM OPEN FLAMES & HIGH TEMPERATURES.

Other
Precautions:THESE PRECAUTIONS ARE FOR ROOM TEMPERATURE HANDLING. USE AT ELEVATED TEMPERATURES WILL REQUIRE ADDED PRECAUTIONS. TRACES OF BENZENE AND FORMALDEHYDE (CARCINOGENS) MAY FORM IF HEATED IN AIR ABOVE 300F (149C).

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:SUFFICIENT MECHANICAL (GENERAL) VENTILATION TO MAINTAIN EXPOSURE BELOW PEL.

Protective Gloves:NEOPRENE RUBBER AS REQUIRED.

Eye Protection:

SAFETY GLASSES RECOMMENDED.

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

PREVIOUSLY DOW CORNING USE TO CALL MOLYKOT 77 PASTE. MATERIAL IS THE SAME BUT NAME IS CHANGED.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:NOT APPLCBL

Vapor Pres: