

COLUMBIA CHASE CORP.,HUMISEAL DIV -- HUMISEAL 1B15 AEROSOL -- 5970-00-990-4924  
===== Product Identification =====

Product ID:HUMISEAL 1B15 AEROSOL

MSDS Date:01/01/1987

FSC:5970

NIIN:00-990-4924

MSDS Number: BGCCR

=== Responsible Party ===

Company Name:COLUMBIA CHASE CORP.,HUMISEAL DIV

Address:26-60 BROOKLYN QUEENS EXPRESSWAY WEST

Box:445

City:WOODSIDE

State:NY

ZIP:11377-0445

Country:US

Info Phone

Num:718-932-0800

Emergency Phone Num:718-932-0800

CAGE:EO647

=== Contractor Identification ===

Company Name:COLUMBIA CHASE CORPORATION

Box:445

CAGE:EO647

Company Name:HUMISEAL DIVISION/CHASE CORPORATION

Address:26-60 BROOKLYN QUEENS EXPRESSWAY WEST

Box:City:WOODSIDE

State:NY

ZIP:11377

Country:US

Phone:718-932-0800

CAGE:99109

===== Composition/Information on Ingredients =====

Ingred Name:AROMATICS

Fraction by Wt: 46.0%

ACGIH TLV:200 PPM

Ingred Name:DICHLORODIFLUOROMETHANE (S

ARA III)  
CAS:75-71-8  
RTECS #:PA8200000  
OSHA PEL:1000 PPM  
ACGIH TLV:1000 PPM; 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS  
Ozone Depleting Chemical:1

=====  
Hazards Identification  
=====

Effects of Overexposure:INHALATION:DIZZINESS,HEADACHE,NAUSEA;CAUSES  
SKIN & EYE DISCOMFORT BY DEFATTING ACTION.

=====  
First Aid Measures  
=====

First Aid:SKIN CONTACT:REMOVE SATURATED CLOTHING & WASH SKIN WITH SOAP  
& WATER;EYES-IRRI  
GATE WITH WATER;INHALATION-REMOVE PATIENT TO FRESH  
AIR;INGESTION-CONSULT PHYSICIAN PROMPTLY

=====  
Fire Fighting Measures  
=====

Flash Point:45F TCC  
Lower Limits:1.4  
Upper Limits:6.7  
Extinguishing Media:CARBON DIOXIDE,FOAM,DRY CHEMICAL  
Fire Fighting Procedures:FIGHT AS FLAMMABLE LIQUID FIRE;USE SELF  
CONTAINED BREATHER  
Unusual Fire/Explosion Hazard:N.A.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE S  
OURCES OF IGNITION.PROVIDE VENTILATION  
AND/OR RESPIRATORY PROTECTION.ABSORB SPILLS WITH INERT  
MATERIAL(SAND,VERMICULITE,ETC.).

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE AWAY FROM HEAT,SPARK OR OPEN  
FLAME.CONTACT WITH PURE PROPELLANT MAY PRODUCE"FROST-BITE".  
Other Precautions:AVOID PROLONGED SKIN CONTACT & BREATHING OF VAPOR.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:O

ORGANIC VAPOR TYPE RESPIRATOR

Ventilation:LOCAL EXHAUST OR MECHANICAL(EXPLOSION PROOF) TO KEEP AT TLV

Protective Gloves:RUBBER

Eye Protection:SAFETY GOGGLES

Other Protective Equipment:N.A.

Supplemental Safety and Health

VAPOR PRESSURE OF ITEM IS 26 MM HG.ON CONDITIONS TO AVOID UNDER  
STABILITY IN SECTION VI ARE:HALOGEN ACIDS,AND CARBONYL HALIDES IN  
ADDITION TO THOSE GIVEN UNDER CONDITIONS TO AVOID,STABILITY

===== Physical/Chemical Properties =====

HCC:V3

Boiling

Point: B.P. Text:230F

Specific Gravity:0.87

Evaporation Rate & Reference: BUTYL ACETATE-1.9

Solubility in Water:NEGLIGIBLE

Appearance and Odor:WATER CLEAR LIQUID WITH AROMATIC SOLVENT ODOR

Percent Volatiles by Volume:96.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

REACTS WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:PROPELLANT DECOMPOSES AT GAS FLAME TEMP.TO  
HALOGENS,HALIDES

Hazardous Decomposition Products:CARB

MONOXIDE,CARBON DIOXIDE &

POSSIBLY OXIDES OF NITROGEN

===== Disposal Considerations =====

Waste Disposal Methods:DUMP INTO AN APPROVED LANDFILL SITE OR ALLOW TO  
EVAPORATE TO ATMOSPHERE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate

urate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.