

AIR PRODUCTS AND CHEMICALS INC -- HELIUM, OR LIQUID HELIUM -- 6830-01-008-3431

=====
Product Identification
=====

Product ID:HELIUM, OR LIQUID HELIUM

MSDS Date:06/01/1990

FSC:6830

NIIN:01-008-3431

MSDS Number: BGCYF

=== Responsible Party ===

Company Name:AIR PRODUCTS AND CHEMICALS INC

Address:7201 HAMILTON BLVD

Box:538

City:ALLENTOWN

State:PA

ZIP:18195-1501

Country:US

Info Phone Num:215-481-6311

E

Emergency Phone Num:800-523-9374

CAGE:00742

=== Contractor Identification ===

Company Name:AIR PRODUCTS AND CHEMICALS INC

Address:7201 HAMILTON BLVD

Box:City:ALLENTOWN

State:PA

ZIP:18195-1501

Country:US

Phone:800-345-3148/ 800-752-1597

CAGE:00742

=====
Composition/Information on Ingredients
=====

Ingred Name:HELIUM; (INERT GAS)

CAS:7440-59-7

RTECS #:MH6520000

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:SUPDAT:TO AIR PRODS W/RESIDUAL PRESS, CYL VALVE TIGHTLY
CLSD & VALVE CAP

IN PLACE.
RTECS #:9999999ZZ

Ingred Name:OTHER PREC:FLOW INTO STOR CNTNR. AVOID DRAGGING,
ROLLING/SLIDING CYLS, EVEN FOR SHORT DIST. USE SUITABLE HAND (ING
4)
RTECS #:9999999ZZ

Ingred Name:ING 3:TRUCK. FOR ADDNL HNDLG REC ON COMPRESSED GAS CYLS,
CONSULT COMPRESSED GAS ASSOC PAMPHLET P-1. STORE LIQ (ING 5)
RTECS #:9999999ZZ

Ingred Name:ING 4:CNTNRS & CYLS IN WELL-VENT AREAS. KEEP CYLS AWAY FROM
SOURCES OF HEAT. STOR SHOULD NOT BE IN HEAVY TRAFFIC (ING 6)
RTECS #:9999999ZZ

Ingre
d Name:ING 5:AREAS TO PVNT ACCIDENTAL KNOCKING OVER/DMG FROM
PASSING/FALLING OBJECTS. VALVE CAPS SHOULD REMAIN ON CYLS (ING 7)
RTECS #:9999999ZZ

Ingred Name:ING 6:NOT CONNECTED FOR USE. SEGREGATE FULL & EMPTY CYLS.
STOR AREAS SHOULD BE FREE OF COMBUST MATL. AVOID EXPOS (ING 8)
RTECS #:9999999ZZ

Ingred Name:ING 7:TO AREAS WHERE SALT/CORR CHEMS ARE PRESENT. GASEOUS
HELIUM CNTNRS MEET DOT SPECIFICATION/AMERICAN SOCIETY (ING 9)
RTECS #:9999999ZZ

Ingred Name:ING 8:OF MECHANICAL ENGINEE
RS (ASME) CODES. LIQ HELIUM IS
STORED IN VACUUM-INSULATED CNTNRS MEETING DOT (ING 10)
RTECS #:9999999ZZ

Ingred Name:ING 9:SPECIFICATIONS/ASME CODES. LIQ HELIUM IN EXPOS PIPING
CAN ACTUALLY CAUSE AIR TO CONDENSE & LIQUEFY. (ING 11)
RTECS #:9999999ZZ

Ingred Name:ING 10:NITROGEN IN THIS LIQ CAN EVAP MORE RAPIDLY, LEAVING
OXYG ENRICHED LIQ BEHIND. UTILIZE OXYG-COMPAT (ING 12)
RTECS #:9999999ZZ

Ingred Name:ING 11:INSULATING MATLS & MINIMIZE EXPOS PIPING SURF AREAS.
USE ONLY METALS

& MATLS COMPAT W/EXTREMELY LOW TEMP.(ING 13)

RTECS #:9999999ZZ

Ingred Name:ING 12:AVOID USE OF CARBON STEEL & OTHER METALS WHICH BECOME BRITTLE @ LOW TEMPS. COMPRESSED GAS CYLS SHOULD NOT(ING 14)

RTECS #:9999999ZZ

Ingred Name:ING 13:BE REFILLED EXCEPT BY QUALIFIED PRODUCERS OF COMPRESSED GASES. SHIPMENT OF COMPRESSED GAS CYL FILLED (ING 15)

RTECS #:9999999ZZ

Ingred Name:ING 14:W/OUT PERMISSION OF OWNER IS VIOLATION OF FEDERAL LAW. IF OXYG DEFICIENT ATM ARE SUSPECTED/CAN OCCUR, (ING 16)

RTECS #:9999999ZZ

Ingred Name:ING 15:USE OXYG MONITORING EQUIP TO TEST FOR OXYG DEFICIENT ATM.

RTECS #:9999999ZZ

Ingred Name:VENT:NORMAL CONCENTRATION OF HELIUM IN WORK AREAS.

RTECS #:9999999ZZ

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:HELIUM IS NONTOXIC, BUT CAN ACT AS

SIMPLE ASPHYXIANT BY DISPLACING AMT OF OXYG IN AIR NEC TO SUPPORT LIFE. HELIUM IS ODORLESS & NONTOXIC, BUT MAY PRDCE SUFFOCATION BY DILUTING CONC OF OXYG IN AIR BELO W LEVELS NEC TO SUPPORT LIFE. PERS, INCLUDING RESCUE WORKERS, SHOULD NOT ENTER AREAS WHERE OXYG CONC IS(EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:HLTH HAZ:BELOW 19.5%, UNLESS PROVIDED W/SCBA/AIRLINE RESP. EXPOS TO OXYG-DEFICIENT ATMOSPHERES MAY PRDCE DIZZ, N

AUS, VOMIT, LOSS OF CONSCIOUSNESS, & DEATH. DEATH MAY RSLT FROM ERRORS IN JUDGMENT, CONF USION/LOSS OF CONSCIOUSNESS WHICH PVNTSSELF-RESCUE. AT LOW OXYG CONCS UNCONSCIOUSNESS & DEATH MAY OCCUR IN (SUPDAT)

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INGEST:CALL MD IMMEDIATELY . PERSONS SUFFERING FROM LACK OF OXYG SHOULD BE MOVED TO AREAS W/NORM ATMOSPHERES. SCBA MAY BE REQD

TO PVNT ASPHY OF RESCUE WORKERS. ASSISTED RESP & SUPP OXYG SHOULD B E GIVEN IF VICTIM IS NOT BRTHG. IF CRYOGENIC LIQ/COLD BOIL-OFF GAS CONTACTS WORKER'S SKIN/EYES, FROZEN TISS SHOULD BE FLOODED/SOAKED W/TEPID WATER (105-115F; 41-46C). DO NOT USE HOT WATER. (SUPDAT)

=====
Fire Fighting Measures
=====

Extinguishing Media:NOT APPLICABLE. MEDIA SUITABLE FOR SURROUNDING FIRE

Fire Fighting Procedures:NOT APPLICABLE. USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:CYLINDER(S) EXPOSED TO INTENSE HEAT OR FIRE MAY VENT RAPIDLY OR EXPLODE.

=====
Accidental Release Measures
=====

Spill Release Procedures:AVOID SKIN CONTACT WITH LIQUID OR COLD BOIL-OFF GAS. FLUSH LIQUID SPILL WITH WATER TO DISPERSE. VENTILATE ENCLOSED AREAS TO PREVENT FORMATION OF OXYGEN-DEFICIENT ATMOSPHERES CAUSED BY EVAPORATION OF L LIQUID HELIUM OR THE RELEASE OF GASEOUS HELIUM.

Ne
utralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:PVNT CONT OF LIQ HELIUM/COLD BOIL-OFF GAS W/EXPOSED SKIN. PVNT ENTRAPMENT OF LIQ IN CLSD SYS. USE ONLY IN WELL-VENTILATED AREAS.

Other Precautions:COMPRESSED GAS CYLS CONTAIN HELIUM AT EXTREMELY HIGH PRESS & SHOULD BE HANDLED W/CARE. USE A PRESS-REDUCING REGULATOR WHEN CONNECTING TO LOWER PRESS PIPING SYS. SECURE CYLS WHEN IN USE.

NEVER USE DIRE CT FLAME TO HEAT A COMPRESSED (ING 2)

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH/MSHA APPRVD SCBA IN OXYG-DEFICIENT ATMOSPHERES. CAUTION! AIR PURIFYING RESPIRATORS WILL NOT FUNCTION. THEIR USE MAY RESULT IN ASPHYXIATION.

Ventilation:NATRL/MECH WHERE GAS IS PRESENT. LOC/MECH (GEN):AS NEC. VENTS SHOULD BE SITUATED TO AVOID HIGHER THAN NORM CONC (ING 17)

Protective Gloves:LEATHER

Eye Protection:CHEM GOGGLES & FA

CESHIELD.

Other Protective Equipment:NONE

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

EFFECTS OF OVEREXPOSURE:SEVERE W/OUT WARNING. EXTENSIVE TISSUE DAMAGE/BURNS CAN RESULT FROM EXPOSURE TO LIQUID HELIUM/COLD HELIUM VAPORS. FIRST AID PROCEDURE:CRYOGENIC BURNS WHICH RESULT IN BLISTERING/DEEPER TISSUE FREEZING SHOULD BE SEEN PROMPTLY BY PHYSICIAN. WASTE DISPOSAL METHOD:TO AIR PROCEED WITH RESIDUAL PRESSURE, THE CYLINDER VALVE TIGHTLY CLOSED & VALVE CAP IN PLACE.

===== Physical/Chemical Properties =====

Boiling Point:Boiling Point Text:-452F,-269C

Melt/Freeze Point:Melt/Freeze Point Text:-458F,-272C

Vapor Density:0.0114@32F

Specific Gravity:0.138 @ 32F

Evaporation Rate & Reference:NOT KNOWN

Solubility in Water:0.861% @ 68F

Appearance and Odor:HELIUM IS COLORLESS AND ODORLESS IN BOTH GASEOUS AND LIQUID STATES.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE.

Stability Condition to Avoid:NONE.

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:ALLOW LIQUID HELIUM TO EVAPORATE IN WELL-VENTILATED LOCATION REMOTE FROM WORK AREAS. VENT HELIUM GAS SLOWLY TO WELL-VENTILATED OUTDOOR LOCATION REMOTE FROM WORK AREAS. DO NOT ATTEMPT TO DISPOSE OF RESIDUAL HELIUM IN COMPRESSED GAS CYLINDERS. RETURN CYLINDERS (SUPPLY DATA)

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by element

nts of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.