

FISKE BROTHERS REFINING CO. -- LUBRIPLATE 930-A -- 9150-01-016-5348

=====
Product Identification
=====

Product ID:LUBRIPLATE 930-A

MSDS Date:01/01/1987

FSC:9150

NIIN:01-016-5348

MSDS Number: BGDQY

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO.

Emergency Phone Num:201-589-9150

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD

ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL,UNSPECIFIED

ACGIH TLV:5 MG/CUM (MIST)

Ingred Name:INORGANIC THICKENER(AS THICKENING AGENT)

Ingred Name:ADDITIVES

=====
Hazards Identification
=====

====

Effects of Overexposure:EYE:CONTACT MAY IRRITATE; SKIN:PROLNGD/RPTD.
CONTACT MAY IRRITATE;INGEST:LOW ORDER ACUTE ORAL TOXTY

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH W/CLEAR H*20 FOR 15-MIN. IF IRRITAT. CONTINUES,GET
MED ATTN.; SKIN:REMOVE CONTAMIN. CLOTHNG & WASH THOROUGHLY W/SOAP &
WARM H*20. IF INJECTED UNDER SKIN,GET IMMEDIATE MED. ATTN.;
INHAL:REMOV E TO FRESH AIR; INGEST: GET IMMED. MED.ATTN.

===== Fi
re Fighting Measures =====

Flash Point:400F/204.4C COC
Lower Limits:1.
Upper Limits:7.
Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE OR WATER SPRAY.
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL
CONTR.
Unusual Fire/Explosion Hazard:DONOT STORE/MIX W/STRONG OXIDANTS. EMPTY
CONTAINERS RETAIN RESIDUE; DONOT CUT, DRILL,/WELLD!!

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE,WASH
REMAINDER W/SUITABLE
PETROL. SOLVENT OR ADD ABSORBENT. KEEP PETROL. PRDS. OUT OF SEWERS
& WATER COURSES. ADVISE IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS
& WATER COURSES.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED,LOW
FIRE RISK AREA. PROTECT FROM PHYSICAL DAMAGE.KEEP CONTAINERS
CLOSED. MAINTAIN STANDARD HYGIENE FOR CHEM HANDLING
Other Precautions:AVOID BREATHING OIL MIST. REMOVE OI
L-SOAKED CLOTHING
& LAUNDRER BEFORE REUSE. CLEANSE SKIN THOROUGHLY AFTER CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQMNTS UNDER ORDINARY
CONDITIONS/ADEQUATE VENT.
Ventilation:LOCAL EXHAUST TO ELIMINATE MISTS/FUMES/GASES.
Protective Gloves:OIL-RESISTANT
Eye Protection:SAFETY/CHEM GOGGLES
Other Protective Equipment:USE OIL-RESISTANT APRON, IF NEEDED.
Supplemental Safety and Health
MSDS DATE:5/86(OTH.P/N:930-AAA,930-AA,9

30-2)

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>550F/>288C

Vapor Pres:5.

Spec Gravity:0.955

Evaporation Rate & Reference:(N-BUAC =1),