

BF GOODRICH CO THE AEROSPACE DIV -- A-68-B ADHESIVE PART A -- 8040-01-016-5354

=====
Product Identification
=====

Product ID:A-68-B ADHESIVE PART A

MSDS Date:01/01/1985

FSC:8040

NIIN:01-016-5354

MSDS Number: BGDQZ

=== Responsible Party ===

Company Name:BF GOODRICH CO THE AEROSPACE DIV

Address:150 DIVISION DR

City:WILMINGTON (FORMALLY IN AKRON,OH)

State:NC

ZIP:28401

Country:US

Info Phone Num:919-25

1-8000

Emergency Phone Num:919-251-8000

CAGE:03481

=== Contractor Identification ===

Company Name:BF GOODRICH CO THE MOLDED PRODUCTS DIV

Address:500 S MAIN ST

Box:City:AKRON

State:OH

ZIP:44318

Country:US

Phone:216-374-3000

CAGE:03481

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPROPYL ACETATE

CAS:108-21-4

RTECS #:AI4930000

Fraction by Wt: 40%.

OSHA PEL:250 PPM/310 STEL

ACGIH TLV:250 PPM/310STEL;9192

Ingred Name:GASOLINE

CAS:8006-61-9

RTECS #:LX3300000

Fr

action by Wt: 40%.
OSHA PEL:300 PPM/500 STEL
ACGIH TLV:300 PPM/500STEL;9192

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 8%.
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9192

=====
Hazards Identification
=====

Effects of Overexposure:NARCOSIS&ASPHYXIATION IN VERY HIGH CONC.EYE
CON
TACT MAY CAUSE SEVERE IRRIT.AVOID SKIN CONTACT

=====
First Aid Measures
=====

First Aid:INHAL:MOVE TO FRESH AIR.CALL MD.EYE:IMMED FLUSH W/WATER AT
LEAST 15 MINUTES.CALL MD.SKIN:WASH THOROUGHLY W/SOAP &
WATER.INGESTION:DO NOT INDUCE VOMITING.IMMEDIATELY CALL MD.PRODUCT
IS HARMFUL OR FATAL IF SWALLOWED.

=====
Fire Fighting Measures
=====

Flash Point:0F TOC
Lower Limits:1.4
Upper Limits:7.8
Extinguishing Media:
CO*2,FOAM OR DRY CHEMICAL
Unusual Fire/Explosion Hazard:VAPORS MAY BE IGNITED,CAUSING FLASH FIRE
OR EXPLOSION

=====
Accidental Release Measures
=====

Spill Release Procedures:AVOID BREATHING VAPORS;REMOVE SOURCES OF
IGNITION.SCRAPE UP ON PAPER AND PUT INTO A CONTAINER

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED IN A COOL,DRY
PLACE,AWAY FROM SOURCES OF IGNITION.FLAMMABLE MIX

TURE.USE ONLY IN

WELL VENTILATED AREA.

Other Precautions:EMPTY CONTAINERS MAY BY HAZARDOUS,OBSERVE ALL PRECAUTIONS.PRODUCT IS HARMFUL OR FATAL IF SWALLOWED!

=====
===== Exposure Controls/Personal Protection =====

Ventilation:MECHANICAL-YES

Protective Gloves:IMPERVIOUS

Eye Protection:SPLASH-PROOF GOGGLES

Supplemental Safety and Health

A-75-B BY B.F.GOODRICH IS SAME EXCEPT FOR COLOR.PART B FOR SHIS PRODUCT IS A-53-B BY B.F.GOODRICH UNDER NSN 6850-00-009-0227.MIX RATI

O IS 40:1 (A:B) BY VOLUME

=====
===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:105 TO 286F

Vapor Pres:200

Vapor Density:3.41

Spec Gravity:0.869

Evaporation Rate & Reference:4.2 BUTYL ACETATE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLACK,VISCOUS LIQUID W/ACETATE ODOR

Percent Volatiles by Volume:88.

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Pro

ducts:CO,CO*2,HYDROCHLORIC ACID

=====
===== Disposal Considerations =====

Waste Disposal Methods:MFR SUGGESTS BURN OR BURY.DISPOSE IN ACCORDANCE W/LOCAL,STATE, AND FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disc

laims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.