

3M COMPANY-TELCOMM PRODUCTS DIVISION -- SCOTCHCAST 4407, PART B -- 5975-01-017-5697
===== Product Identification =====

Product ID:SCOTCHCAST 4407, PART B
MSDS Date:11/13/1985
FSC:5975
NIIN:01-017-5697
Kit Part:Y
MSDS Number: BGDSV
=== Responsible Party ===
Company Name:3M COMPANY-TELCOMM PRODUCTS DIVISION
Address:3M CENTER
City:ST PAUL
State:MN
ZIP:55144-1000
Country:US
Emergency Phone Num:612-733
-1110
CAGE:55203
=== Contractor Identification ===
Company Name:MINNESOTA MINING AND MFG CO TELCOMM MARKETS DIV
Address:3M AUSTIN CTR
Box:City:AUSTIN
State:TX
ZIP:79769-2963
Country:US
Phone:800-426-8688
CAGE:55203

===== Composition/Information on Ingredients =====

Ingred Name:HYDROCARBON POLYOL (WT% RANGE:80-90%)
Fraction by Wt: 85%.
Other REC Limits:NONE

Ingred Name:PLASTICIZER (WT% RANGE:10-20%)
Fraction by Wt: 15%.
Other REC Limits:NONE

Ingred Name:ALIPHATIC AMINE (WT%

RANGE:0.1-0.5%)
Fraction by Wt: 0.3%
Other REC Limits:NONE

===== Hazards Identification =====

LD50 LC50 Mixture:ACUTE ORAL (RAT) LD50 < 5ML/KG
Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:LOW ACUTE TOXICITY HAZARD, NO CHRONIC EFFECTS REPORTED. SEE CARCINOGEN NOTE.
Effects of Overexposure:EYE:SL IRRT. SKN:SL IRRT. MODERATE TO SEVERE IRRT IF CURED MATERIAL FO
RCIBLY REMOVED FROM SKIN. INHL: IRRT, POSS
ASTHMA SYMPTOMS. INGEST: GI TRACT IRRT POSSIBLE, POSSIBLE IRREVERSIBLE EFFECT (SEE CARC INOGEN NOTE).
Medical Cond Aggravated by Exposure:ANY PRE-EXISTING SENSITIVITY OR ALLERGY IN EXPOSED TISSUE.

===== First Aid Measures =====

First Aid:EYE: FLUSH 15 MIN W/AMPLE WATER. SKIN: REMOVE CONTAMINATED CLOTHING/FOOTWEAR. WASH EXPOSED SKIN W/SOAP & WATER. INHAL: REMOVE VICTIM TO FRESH AIR. INGEST: IF C
ONSCIOUS, GIVE TWO GLASSES WATER &
CALL P HYSICIAN OR POISON CENTER, TRY TO DETERMINE DOSE.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:>270F/>132C
Extinguishing Media:CO*2, FOAM, DRY CHEMICAL
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:AVOID EXCESS HEAT & IGNITION SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:COLLECT PART B SPILL W/ABSORBENT, PLACE IN
C
LOSABLE CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:USE ONLY W ADEQUATE VENTILATION. AVOID EYE/SKN CONTACT. DO NOT INHALE OR INGEST.
Other Precautions:CURED MATERIAL IS DIFFICULT TO REMOVE FROM SKIN. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE CCROV RESPIRATOR
Ventilation:LOCAL
Protective Gloves:IMPERVIOUS
Eye Protection:GO

GGLES, SAFETY GLASSES
Other Protective Equipment:NONE
Supplemental Safety and Health
3M MSDS DOC# 10-3071-7, DTD 13NOV85. 3M ID# IS 80-6100-6040-4.KEY1:N1.

===== Physical/Chemical Properties =====

HCC:N1
Vapor Pres:NEG
Spec Gravity:1.005
Viscosity:450 CPS
Solubility in Water:INSOLUBLE
Appearance and Odor:AMBER OILY LIQUID
Percent Volatiles by Volume:NEG

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
N
ONE
Stability Condition to Avoid:AVOID EXCESS HEAT & IGNITION SOURCES.
Hazardous Decomposition Products:CARBON OXIDES, TRACES OF HCN, NITROGEN
OXIDES

===== Disposal Considerations =====

Waste Disposal Methods:LANDFILL OR INCINERATE IAW ALL LAWS & REGS.
CURED RESIN MAY BE LANDFILLED, PART A NOT AN EPA HAZWASTE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of
Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.