

BEL-RAY COMPANY,INC -- MOLYLUBE SILICONE LH-10 GREASE -- 9150-01-019-0669

=====  
Product Identification  
=====

Product ID:MOLYLUBE SILICONE LH-10 GREASE

MSDS Date:01/01/1985

FSC:9150

NIIN:01-019-0669

MSDS Number: BGDWY

=== Responsible Party ===

Company Name:BEL-RAY COMPANY,INC

Emergency Phone Num:201-938-2421

CAGE:KO301

=== Contractor Identification ===

Company Name:BEL-RAY COMPANY INC.

Address:1201

BOWMAN AVE

Box:526

City:FARMINGDALE

State:NJ

ZIP:07727

Country:US

Phone:732-938-2421

CAGE:12474

Company Name:BEL-RAY COMPANY,INC.

Box:526

CAGE:KO301

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MOLYBDENUM DISULFIDE

CAS:1317-33-5

RTECS #:QA4697000

Fraction by Wt: 10.0%

OSHA PEL:10 MG/M3 TDUST (MO)

ACGIH TLV:10 MG/M3 (MO); 8990

Ingred Name:SILICA

Fraction by Wt: 7.0%

ACGIH TLV:30 MG(DUST)/CUM

Ingred Name:SOLIDS, HAZARD UNKNOWN,UNIDENTIFIED; % WT BY DIFFEREN

CE  
Fraction by Wt: 83.0%

=====  
Hazards Identification  
=====

Effects of Overexposure:MFR STATES THAT NO KNOWN ADVERSE EFFECTS FROM EXPOSURE

=====  
First Aid Measures  
=====

First Aid:SKIN:WASH WITH SOAP AND WATER. EYES: FLUSH WITH WATER.  
INHALED: REMOVE TO FRESH AIR. REMOVE CONTAMINATED CLOTHING.

=====  
Fire Fighting Measures  
=====

Flash Point:530F-COC

Lower Limits:1.0%

Upper Limit

s:6.0%

Extinguishing Media:CO\*2, FOAM, DRY CHEM & H\*2O FOG.

Fire Fighting Procedures:FOR ENCLOSED AREAS USE AIR SUPPLIED RESCUE EQUIPMENT

Unusual Fire/Explosion Hazard:NONE

=====  
Accidental Release Measures  
=====

Spill Release Procedures:USE PROTECTV GLOVES FOR CLEAN-UP; WIPE,CONTAIN & RECOVER.PLACE IN COVERED CONTAINERS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED

AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED

Other Precautions:NONE

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NONE SHOULD BE NEEDED

Ventilation:NORMAL ROOM VENTILATION.

Protective Gloves:AS REQUIRED

Eye Protection:AS REQUIRED

Other Protective Equipment:USE GOOD INDUSTRIAL HYGIENIC PRACTICES.

Supplemental Safety and Health

MSDS FM MFR DATED:11-30-81

=====  
Physical/Chemical Pro

perties =====

HCC:V6

Boiling Pt:B.P. Text:IBP >600F

Vapor Pres:.02

Vapor Density:>10

Spec Gravity:1.2

Solubility in Water:NEGLIGIBLE

Appearance and Odor:GREASE.

Percent Volatiles by Volume:1.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS SUCH AS CONCENTRATED OXYGEN/CHLORINE

Hazardous Decomposition Products:CO,CO\*2 & SULFUR COMPOUNDS.

===== Disposal Considerations =====

===

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE &  
DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE  
INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS. MFR NOTES:REMOVE  
TO LANDFILL OR USE LICENS D WASTE OIL DISPOSAL CONTCTR.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants  
this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.