View NSN Online: https://aerobasegroup.ae/nsn/6750-01-022-8410

EASTMAN KODAK COMPANY -- 190 1685 FLEXICOLOR BLEACH, PART B -- 6750-01-022-8410

Product ID:190 1685 FLEXICOLOR BLEACH, PART B

MSDS Date:08/02/1988

FSC:6750

NIIN:01-022-8410

Kit Part:Y

MSDS Number: BGFDN === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650 Country:US

Info Phone Num:716-722-5151

Eme

rgency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

======= Composition/Information on Ingredients ========

Ingred Name: AMMONIUM (ETHYLENEDINITRILO) TETRAACETO-FERRATE (III)

CAS:21265-50-9

Fraction by Wt: 40-45%

Ingred Name: AMMONIA (SARA III)

CAS:7664-41-7

RTECS #:BO0875000

Fracti

on by Wt: 6.0% Other REC Limits:NONE SPECIFIED OSHA PEL:50 PPM ACGIH TLV:25 PPM/35 STEL; 9293
EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS
Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 45-55%
======================================
LD50 LC50 Mixture:ORAL(RAT):0.5 - 5.0 G/KG Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:CAUSES SKIN AND EYE IRRITATION. Effec
ts of Overexposure:PER MFR,PRODUCT IS OF LOW HAZARD.HOWEVER, SOLUTION MAY IRRITATE EYES & MAY CAUSE SKIN ALLERGIC REACTION ON REPEATED OR PROLONGED SKIN EXPOSURE.
======================================
First Aid:INHALATION: REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED; EYES/SKIN:FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MIN; INGESTION: RINSE MOUTH. GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SY MPTOMS OF OVEREXPOSURE.
======================================
Flash Point:NONE Extinguishing Media:EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHINGG TO PREVENT CONTACT W/SKIN & EYES. Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE

PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

======== Accidental Release Measures ===========

Spill Release Procedures:ELIMINATE IGNI

TION SOURCES. STOP LEAK. EVACUATE AREA.DO NOT TOUCH SPILLAGE.SMALL SPILL: ABSORB WITH INERT ABSORBENT. PLACE IN CLOSED CONTAINER. FLUSH AREA WITH WATER. LARGE SPILL: DIKE AHEAD FOR LATER DISPOSAL. NOTIFY AUTHORITIES. ============= Handling and Storage ========================== Handling and Storage Precautions: STORE IN COOL, DRY, WELL VENTILATED AREA, PROTECT FROM PHYSICAL DAMAGE, AVOID ANY PHYSICAL CONTACT, KEEP CONTAINERS TIGHTLY CLOSED Other Precautions: AVOID SKIN, EY ES & CLOTHG CONTACT: AVOID CONTACT W/METALS; LD50 ORL-RAT:0.5-5.0GM/KG; PH(APPROX) OF SOLN:7.0 ===== Exposure Controls/Personal Protection ======== Respiratory Protection: NONE SHOULD BE NEEDED Ventilation:MECHANICAL(GENERAL) RECOMMENDED, LOCAL EXHAUST IF NEEDED Protective Gloves: IMPERVIOUS Eye Protection: CHEMICAL/SAFETY GOGGLES Other Protective Equipment: NONE STATED. BUT GOOD INDUSTRL HYGEIN PRACTICE SHOULD BE FOLLOWED. Supplemental Safety and Health PER MFR 9/24/86, 3 PART PROD OF CAT #155 5655 WAS CHANGED TO A 2 PARTS KIT, CAT #190 1685 EFFECTIVE 10/14/80; THIS IS PART B OF 2 PART KIT OF NEW FORMULA; PART B SOLUTION #5459; 2 PARTS KIT OF 190 168 5 WAS EFFECTIVE UNTIL DEC 86 WHEN TRADE NAME & CAT NOWERE CHANGED TO 106 5895.FLEXICOLOR BLEACH II. PART B: KEY1=N1 ======== Physical/Chemical Properties ============= HCC:N1 Boiling Pt:B.P. Text:212F/100C Vapor Pres:18MMHG@100 Vapor Density:0.6 Spec Gravity:1.29 pH:7.0 Solubility in W ater:COMPLETE Appearance and Odor:OPAQUE, REDDISH-BROWN SOLUTION; SLIGHT AMMONIACAL **ODOR** Percent Volatiles by Volume:55 ======== Stability and Reactivity Data ========== Stability Indicator/Materials to Avoid:YES PER MFR, METALS Stability Condition to Avoid: EXCESSIVE HEAT Hazardous Decomposition Products: MAY EMIT AMMONIA AND OXIDES OF CARBON & NITROGEN ON COMBUSTION. ======= Disposal Considerations ============

Waste Disposal Methods: KEEP IN CO

VERED DRUMS, PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document sh

ould seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.