

BORDEN INC., KRYLON DEPT. -- KRYLON 1605 DOVE GRAY (NEW FORMULA) -- 8010-01-027-4852
===== Product Identification =====

Product ID:KRYLON 1605 DOVE GRAY (NEW FORMULA)

MSDS Date:01/01/1987

FSC:8010

NIIN:01-027-4852

MSDS Number: BGFRP

=== Responsible Party ===

Company Name:BORDEN INC., KRYLON DEPT.

Address:180 E BROAD ST

City:COLUMBUS

State:OH

ZIP:43215-3705

Country:US

CAGE:EO688

=== Contractor Iden

tification ===

Company Name:BORDEN CHEMICAL CO

Address:180 E BROAD ST

Box:City:COLUMBUS

State:OH

ZIP:43215-3705

Country:US

Phone:614-225-6124

CAGE:86142

Company Name:BORDEN INC., KRYLON DEPT

Address:FORD & WASHINGTON ST

City:NORRISTOWN

State:PA

ZIP:19404

Country:US

Phone:(215) 278-2456

CAGE:EO688

===== Composition/Information on Ingredients =====

Ingred Name:BUTYLALCOHOL 0.2-2.5%

ACGIH TLV:S,C 50 PPM

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000
Fraction by Wt: 8-17%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 6-14%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 2-3%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DO
T Rpt Qty:1000 LBS

Ingred Name:ACETONE
Fraction by Wt: 36.5%
ACGIH TLV:750 PPM

===== Hazards Identification =====

Effects of Overexposure:INH:MAY BE HARMFUL;LIQ/VAP MAY IRRIT NOSE,
THROAT, LUNGS. SKIN/EYES:IRRIT. INGEST:MAY BE HARMFUL

===== First Aid Measures =====

First Aid:INGEST:DO NOT INDUCE VOMITING;CALL PHYSICIAN IMMED.
SKIN:IMMED FLUSH W/WATER FOR AT LEAST 15MIN;IF IRRIT PERSISTS,CALL
A PHYSICIAN. E

YES:IMMED FLUSH W/WATER 15MIN W/EYELIDS APART;CALL
MD. INH:REMOE TO FRESH AIR; GIVE ARTIF,RESP OR O*2 IF NEC;CALL MD.

===== Fire Fighting Measures =====

Flash Point:N/A AEROSOL

Extinguishing Media:DRY CHEMICAL,CO*2, FOAM. WATER MAY BE INEFFECTIVE

Fire Fighting Procedures:USE WATER TO COOL FIRE EXPOS CANS. WEFR SCBA

Unusual Fire/Explosion Hazard:EXTREM FLAM;UNDER PRESSURE. HI TEMP MAY
BURST CANS; AVOIDALL HEAT/IGNIT SOURCES, DIRECT SUN.

=====

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. SOAK UP
W/ABSORBENT MATERIAL & REMOVE TO A CHEMICAL DISPOSAL AREA. PREVENT
ENTRY INTO NATURAL BODIES OF WATER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT TEMPERATURES OVER
120F. WASH THOROUGHLY AFTER HANDLING. AVOID PROLONGED OR REPEATED
CONTACT W/EYES,SKIN OR CLOTHING.

Other Precautions:USE

W/ADEQUATE VENTILATION. AVOID BREATHING VAPOR OR
MIST. HANDLE IAW GOOD INDUSTRIAL HYGIEINE & SAFETY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD RESP PROT DEPENDING ON
CONDITIONS OF USE/TLV EXPOS

Ventilation:LOCAL EXHAUST IN VOLUME & PATTERN ADEQ TO KEEP BELOW TLV

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES IF CONTACT LIKELY

Supplemental Safety and Health

DATE OF PREP:06/30/86 . ADD INGRED: METHYL ISOBUTYL KETONE

2-4%+

2-PROPANOL 1-METHOXY-, ACETATE, 7-8%+ PROPANE, 16-17%.

===== Physical/Chemical Properties =====

HCC:V3

Vapor Density:>1.0

Spec Gravity: