View NSN Online: https://aerobasegroup.com/nsn/9150-01-035-5390

QUAKER STATE PIL REFINING CORP -- SUPER QUADROLUBE GEAR LUBRICANT (SAE 75W) -- 9150-01-035-5390

============= Product Identification ========================

Product ID:SUPER QUADROLUBE GEAR LUBRICANT (SAE 75W)

MSDS Date:02/01/1991

FSC:9150

NIIN:01-035-5390

MSDS Number: BGGJF === Responsible Party ===

Company Name: QUAKER STATE PIL REFINING CORP

Address:255 ELM ST

Box:989

City:OIL CITY

State:PA

ZIP:16301-1412

Country:US

Inf

o Phone Num:814-676-2726

Emergency Phone Num:814-676-2726

CAGE:77493

=== Contractor Identification ===

Company Name: EMULTEC INDUSTRIAL PRODUCTS INC

Address:1150 HAYDEN DR SUITE 100

Box:City:CHARROLLTON

State:TX ZIP:75006 Country:US

Phone:972-417-1288

CAGE:0WA27

Company Name: QUAKER STATE CORPORATION Address: 255 E JOHN CARPENTER FREEWAY

Box:City:IRVING

State:TX ZIP:75062 Country:US

Phone:800-562-5928


CAGE:77493

====== Composition/Information on Ingredients ========

Ingred Name:ADDI

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INGESTION & INHALATION- NOT EXPECTED TO BE ACUTELY TOXIC BY INGESTION OR INHALATION. SKIN- MINOR IRRITATION FOLLOWING PROLONGED AND/OR REPEATED CONTACT. EYES- MAY CAUSE MINOR IRRITATION. NO CHRONIC EFFECTS. Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER. Medi
cal Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.
======================================
First Aid:INGESTION- IF LARGE QUANTITIES OF THIS MATERIAL ARE INGESTED, GIVE VICTIM WATER. INDUCE VOMITING AND CONTACT A PHYSICIAN. SKIN-WASH SKIN THOROUGHLY WITH SOAP AND WATER. LAUNDER SOILED CLOTHING INH ALATION- INHALATION UNLIKELY. IF IRRITATION EXISTS, REMOVE PERSON FROM EXPOSURE. CONTACT PHYSICIAN IF DISCOMFORT CONTINUES. EYES- FLU
SH WITH WATER FOR 15 MINUTES. CONTACT A PHYSICIAN IF NEEDED.
======================================
Flash Point Method:PMCC Flash Point:295F,146C Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM AND WATER SPRAY. ON LARGE STORAGE FIRES, WATER SPRAY MAY BE INEFFECTIVE. Fire Fighting Procedures:LARGE STORAGE FIRES INVOLVING THIS MATERIAL AND/OR OTHER LUBRICATING PRODUCTS, DO NOT ENTER ANY ENCLOSED OR CONFINED SPACE WITHOUT FULL PROTECTIVE EQUIPM ENT. Unusual Fire/Explosion Hazard:NONE
========= Accidental Release Measures ===========
Spill Release Procedures:CLEAN UP SPILLS AS SOON AS POSSIBLE. ABSORB LARGE SPILLS WITH COMMERCIALLY AVAILABLE ABSORBENT MATERIALS, SUCH AS ABSORBENT CLAY.
============ Handling and Storage ===============
Handling and Storage Precautions:DO NOT STORE NEAR HIGH HEAT OR OPEN FLAMES.
Other Precautions:AVOID PROLONGED OR FREQUENTLY REPEATED SKIN CONTACT WI

TIVES.



======== Disposal Considerations =============

Waste Disposal Methods: PLACE CONTAMINATED MATERIAL IN DISPOSABLE CONTAINERS AND BURY IN AN APPROVED LANDFILL

## SITE PER LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.