

MOBIL OIL CORP. -- MOBILUBE HD 80W-90, MIL-L-2105C -- 9150-01-035-5391

===== Product Identification =====

Product ID:MOBILUBE HD 80W-90, MIL-L-2105C

MSDS Date:01/01/1985

FSC:9150

NIIN:01-035-5391

MSDS Number: BGGJK

=== Responsible Party ===

Company Name:MOBIL OIL CORP.

Emergency Phone Num:(212) 883-4242

CAGE:3U278

=== Contractor Identification ===

Company Name:MOBIL CORP

Address:150 E 42ND ST

Box:

City:NEW YORK

State:NY

ZIP:10017-5612

Country:US

Phone:212-883-4242

CAGE:57635

Company Name:MOBIL OIL CORP.

Address:3225 GALLOWS RD

City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:1-800-662-4525

CAGE:3U278

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: >90%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:ADDITIVES &/OR OTHER INGRED.

Fraction by Wt: PINT

INGEST IMMEDIATELY GIVE 1 TO 2 GLASSES WATER &  
CALL MD FOR WAY TO INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point:375F COC  
Extinguishing Media:CO\*2, FOAM, DRY CHEMICAL  
Fire Fighting Procedures:FIREGIGHTERS MUST USE SELF-CONTAINED BREATHING APPARATUS  
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB ON FIRE RETARIDANT TREATED SAWDUST, DIATOMACEOUS EART  
H OR OTHER ABSORBENT. SCRAPE UP & REMOVE. DISPOSE  
OF IN APPROVED HAZARDOUS WASTE DISPOSAL FACILITY. IMMEDIATE REPORT  
SPILLS THAT COULD REACH ANY WSTERWAY INCLUDING INTERMITTENT DRY CREEKS.

===== Handling and Storage =====

Handling and Storage Precautions:NO SPECIAL PRECAUTIONS REQUIRED

===== Exposure Controls/Personal Protection =====

Respiratory Protection:MFR RECM NO SPECIAL REQ UNDER NORMAL CONDITIONS  
OF USE W/ ADEQ VENTL  
V  
entilation:NO SPECIAL REQ RECM BY MFR UNDER MORMAL USE W/ADEQ VENTIL.  
Protective Gloves:SEE OTHER PROT  
Eye Protection:SEE OTHER PROT EQUIP  
Other Protective Equipment:USE GOOD PERSONAL HYGIENE & NORMAL  
INDUSTRIAL EYE PROT PRACT  
Supplemental Safety and Health  
VAPOR PRESSURE: MM HG 20C 600F  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:ASTM 7.0 VISCOUS LIQUID;MILD ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG O

## XIDIZERS

Stability Condition to Avoid:STRONG OXIDATION

Hazardous Decomposition Products:NITROGEN OXIDES, PHOSPHORUS OXIDES,  
SULFUR OXIDES, CO

### ===== Disposal Considerations =====

Waste Disposal Methods:MFR RECM DILUTE WASTE W/ A SOLVENT. TO REDUCE  
ITS VISCOSITY, & DISPOSE BY SUPERVISED INCINERATION IN COMPLIANCE  
W/LOCAL REGULATIONS. DISPOSAL MUST BE IAW FED, STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.