

CITIES SERVICE COMPANY -- CITGO PREMIUM GEAR OIL 80W-90 -- 9150-01-035-5393

=====
Product Identification
=====

Product ID:CITGO PREMIUM GEAR OIL 80W-90

MSDS Date:01/01/1985

FSC:9150

NIIN:01-035-5393

MSDS Number: BGGLW

=== Responsible Party ===

Company Name:CITIES SERVICE COMPANY

Emergency Phone Num:918-561-2211

CAGE:71476

=== Contractor Identification ===

Company Name:CITIES SERVICE CO

Address:CI

TIES SERVICE BLDG

Box:300

City:TULSA

State:OK

ZIP:74102

Country:US

Phone:918-561-5165, FOR MED:318-491-6215

CAGE:71476

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM OIL, REFINED

Fraction by Wt: >80%

Ingred Name:ADDITIVES

=====
Hazards Identification
=====

Effects of Overexposure:INH: DROWSINESS,DIZZ,HDCH,NAUS,LUNG IRRIT,CHEM
PNEUMONITIS. EYES: IRRITATION. SEE SUP DATA

=====
First Aid Measu

res
=====

First Aid:INH: REMOVE TO FRESH AIR. RESP SUPPORT IF NECESSARY. SEEK
MEDICAL AID. EYES: FLUSH WITH WATER FOR 15 MINUTES. SEEK MEDICAL
AID. SKIN: WASH WITH SOAP & WATER(SUBCUTANEOUS INJECTION IS A
MEDICAL EMERGEN CY - SEEK MEDICAL AID IMMED. SEE OTHER PRECAUTIONS

=====
Fire Fighting Measures
=====

Flash Point:360F, 182C

Extinguishing Media:CO*2, DRY CHEMICAL, FOAM OR WATER FOG

Fire Fighting Procedures:NONE

Unusual Fire/E

xplosion Hazard:WATER MAY CAUSE FROTHING. THERMAL
DECOMPOSITION PRODUCT CO*2, CO.

===== Accidental Release Measures =====

Spill Release Procedures:FOLLOW ACCEPTED INDUSTRIAL PRACTICES AND/OR
LOCAL, STATE AND FEDERAL REGULATIONS. CHECK BEFORE HANDLING.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN METAL CONTAINER BELOW 120F.
KEEP AWAY FROM IGNITION SOURCES. DOT HAZARD LABEL NOT REQUIRED.

Ot

her Precautions:FIRST AID/ INGEST: DO NOT INDUCE VOMITING, CALL MD.
ASPIRATION MAY CAUSE CHEMICAL PNEUMONITIS OR LIPOID PNEUMONIA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPRVD ORGANIC RESP IF VAPOR CONC
EXCEEDS TLV.

Ventilation:SUFFICIENT TO KEEP BELOW TLV.

Protective Gloves:OIL IMPERVIOUS

Eye Protection:SAFETY SPLASH GOGGLES

Supplemental Safety and Health

5 GALLON PAIL: VAPOR PRESSURE AT 25C IS 1

Spec Gravity:0.89

Eva

poration Rate & Reference: