

PRODUCTS RESEARCH & CHEMICAL CORP. -- PR-1538 AMBER,PART A -- 5970-01-037-5044

===== Product Identification =====

Product ID:PR-1538 AMBER,PART A

MSDS Date:01/01/1987

FSC:5970

NIIN:01-037-5044

MSDS Number: BGGVJ

=== Responsible Party ===

Company Name:PRODUCTS RESEARCH & CHEMICAL CORP.

Emergency Phone Num:213-240-2060

CAGE:DO563

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL

L, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

Company Name:PRODUCTS RESEARCH & CHEMICAL

Address:NOW DBA COURTAULDS AEROSPACE

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Phone:818-240-2060

CAGE:DO563

===== Composition/Information on Ingredients =====

Ingred Name:4,4'-METHYLENE BIS (2-CHLOROANILINE) MOCA (SARA III)

CAS:101-14-4

RTECS #:CY1050000

Fraction by Wt: 10%

OSHA PEL:S, 0.0

2 PPM
ACGIH TLV:S, 0.01 PPM,A2; 9394
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:POLYURETHANE POLYMER
CAS:9009-54-5
RTECS #:TR7875000
Fraction by Wt: 75%
ACGIH TLV:0.14 MG/CUM

===== Hazards Identification =====

Effects of Overexposure:IRRITATION TO SKIN,EYES AND MUCOUS MEMBRANES.

===== First Aid Measures =====

First Aid:SKIN:WASH THOROUGHLY WITH SOAP AND WATER.EYES:FLUSH THOROUGHLY WITH LARGE AMOUNTS OF WATER,
;GET MEDICAL
ATTENTION.INGESTION:INDUCE VOMITING.INHALATION:REMOVE VICTUM TO FRESH AIR.

===== Fire Fighting Measures =====

Flash Point:>200F TOC
Lower Limits:UNK
Upper Limits:UNK
Extinguishing Media:FOAM,DRY CHEMICAL
Fire Fighting Procedures:WEAR AIR SUPPLIED RESPIRATOR WHEN FIGHTING FIRE.
Unusual Fire/Explosion Hazard:EMISSION OF TOXIC FUMES.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE I
GNITION SOURCES.KEEP UNPROTECTED
PERSONS AWAY FROM HAZARD AREA.ABSORB EXCESS WITH RAGS,PAPER TOWELS,OTHER ABSORBENT MATL.CLEAN SPILL AREA WITH METHYL ETHYL KETONE.

===== Handling and Storage =====

Handling and Storage Precautions:PRODUCT IS MOISTURE SENSITIVE,KEEP IN TIGHTLY CLOSED CONTAINERS IN SHELTERED AREA.PROTECT FROM PHYSICAL DAMAGE.AVOID ACUTE FIRE HAZARDS.

===== Exposure Controls/Personal Protection =====

Respir

atory Protection:RESPIRATOR RECOMMENDED FOR SENSITIVE
INDIVIDUALS.

Ventilation:LOCAL EXHAUST TO MINIMIZE TOXIC FUMES.

Protective Gloves:RUBBER

Eye Protection:GOGGLES/FACE SHIELD

Other Protective Equipment:USE PROTECTIVE HAND CREAM

Supplemental Safety and Health

MSDS DATED 11/12/85

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:UNK

Vapor Pres:UNK

Vapor Density:UNK

Spec Gravity:1.05

Evaporation Rate & Reference:UNK

Solubility in Water:NEG

LIGIBLE

Appearance and Odor:AMBER OR BLACK SYRUP;SLIGHT IRRITATING ODOR.

Percent Volatiles by Volume:1

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:IGNITION SOURCES

Hazardous Decomposition Products:TOXIC VAPORS OF AMINE AND TOLYLENE
DIISOCYANATE

===== Disposal Considerations =====

Waste Disposal Methods:PLACE ABSORBED MATL IN TIGHTLY SEALED CONTAINERS
AND DIS

POSE IN ACCORDANCE WITH LOCAL,STATE,AND FEDERAL
REGULATIONS.DO NOT INCINERATE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume

responsibility for the suitability of this information to their particular situation.