

EASTMAN KODAK COMPANY -- 156 6553,REVERSAL BATH,PROCESS E-6 -- 6750-01-042-0872

===== Product Identification =====

Product ID:156 6553,REVERSAL BATH,PROCESS E-6

MSDS Date:03/10/1990

FSC:6750

NIIN:01-042-0872

Kit Part:Y

MSDS Number: BGHFL

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151

Eme

rgency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 65-70%

Other REC Limits:NONE SPECIFIED

Ingred Name:SODIUM PROPIONATE

CAS:137-40-6

RTECS #:UF7525000

Fraction

by Wt: 15-20%
Other REC Limits:NONE SPECIFIED

Ingred Name:SUBSTITUTED PHOSPHONATE (KODAK ACCESSION # 049335)
Fraction by Wt: 1-5%
Other REC Limits:NONE SPECIFIED

Ingred Name:SUBSTITUTED PHOSPHONATE (KODAK ACCESSION # 049334)
Fraction by Wt: 1-5%
Other REC Limits:NONE SPECIFIED

Ingred Name:STANNOUS CHLORIDE
CAS:7772-99-8
RTECS #:XP8700000
Fraction by Wt: 1-5%
Other REC Limits:NONE SPECIFIED

Ingred Name:PROPIONIC ACID (SARA III)
CAS:79-09-4
RTECS #:UE5950000
Fraction by Wt: 1-5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:10 PPM
ACGIH TLV:10 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MANUFACTURER STATES THAT THIS MATERIAL
IS EXPECTED TO BE A LOW HAZARD BY INHALATION, EYE AND SKIN CONTACT,
AND INGESTION. MAY CAUSE IRRITATION OF EYES, SKIN, AND RESPIRATORY

TRACT ESPECIALLY IN SENSITIZED INDIVIDUALS.
Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS
LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.
Effects of Overexposure:SLIGHT IRRITATION ON EXPOSURE.
Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS
OR WITH A PRE-EXISTING DISEASE INVOLVING THE SKIN MAY BE AT
INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:EYES:IMMEDIATELY FLUSH WITH

H PLENTY OF WATER FOR 15 MINUTES

HOLDING EYELIDS OPEN. GET IMMEDIATE MEDICAL ATTENTION. SKIN:REMOVE
CONTAMINATED CLOTHING AND SHOES. WASH SKIN WITH SOAP AND WATER. GET
MEDICAL ATTENTION. INGESTION:DRINK 1-2 GLASSES OF WATER. GIVE
NOTHING BY MOUTH IF UNCONSCIOUS. CALL A PHYSICIAN AT ONCE.

===== Fire Fighting Measures =====

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL AS APPROPRIATE FOR SURROUNDINGS.

Fire Fighti

ng Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL
FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE RESIDUE WITH LARGE AMOUNTS OF WATER BY
FLUSHING TO THE SEWER. DISCHARGE MAY BE GOVERNED BY LOCAL LA
W.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS TIGHTLY CLOSED WHEN
NOT IN USE AND AWAY FROM STRONG OXIDIZING AGENTS.

Other Precautions:AVOID CONTACT WITH EYES. WASH THOROUGHLY AFTER
HANDLING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AN APPROPRIATE NIOSH-APPROVED RESPIRA
TOR FOR

ORGANIC VAPOR SHOULD BE WORN IF NEEDED.

Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY ADEQUATE.

Protective Gloves:NEOPRENE OR NATURAL RUBBER

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR
FOOTWEAR.

Supplemental Saf

ety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES.
LAUNDER CONTAMINATED CLOTHING PRIOR TO REUSE.

===== Physical/Chemical Properties =====

HCC:C3

Boiling Pt:B.P. Text:>212F,>100C

Vapor Pres:18 @20C

Vapor Density:0.6

Spec Gravity:1.203

pH:5.94

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR SOLUTION

Percent Volatiles by Volume:65

===== Stability and Reactivity Data =====

Stability Indicator/Materi

als to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:CARBON DIOXIDE AND PROBABLY CARBON
MONOXIDE AS WELL AS OXIDES OF PHOSPHORUS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH ALL
APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This inf

ormation is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.