View NSN Online: https://aerobasegroup.ae/nsn/6750-01-045-0326

EASTMAN KODAK COMPANY -- 189 5234,EKTAMATIC A10 ACTIVATOR(PRE 2/81) 6750-01-045-0326

============= Product Identification ==================

Product ID:189 5234, EKTAMATIC A10 ACTIVATOR (PRE 2/81)

MSDS Date:02/13/1981

FSC:6750

NIIN:01-045-0326

MSDS Number: BGHKB === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650 Country:US

Info Phone Num:716-722-515

1

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

======= Composition/Information on Ingredients ========

Ingred Name: POTASSIUM HYDROXIDE (SARA III)

CAS:1310-58-3

RTECS #:TT2100000 Fraction by Wt: 07.5% OSHA PEL:C, 2 MG/M3 ACGIH TLV:C 2 MG/M3; 9192

EPA Rpt Qty:1000 LBS

DOT R

Ingred Name:WATER (90-95%) CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 92.5%
======================================
Effects of Overexposure:EYES:CONTACT CAN CAUSE SEVERE BURNS.SKIN:REPEAT CONTACT MAY CAUSE IRRITATION.
======================================
First Aid:EYES:IMMEDIATELY FLUSH W/WATER 15 MIN.SKIN:FLUSH WITH WATER 15 MIN.INHALED:REMOVE TO FRESH AIR.GIVE CPR OR OXYGEN IF NEED,REMOVE CONTAMI NATED CLOTHING.GET IMMEDIATE MEDICAL ATTENTION.
======================================
Flash Point:NONE Extinguishing Media:NOT KNOWN. Fire Fighting Procedures:NOT KNOWN. Unusual Fire/Explosion Hazard:NOT LISTED.
========= Accidental Release Measures ==========
Spill Release Procedures:ELIMINATE IGNITION SOURCES.EVACUATE UNPROTECTED PERSONS.STOP LEAK W/O RISK.WEAR PROTECTIVE CLOTHING AND SAFETY GLASSES.CONTAIN/DIKE SPILL.MFR RECOMMENDS NEUTRALIZING WITH SODIUM BISULFATE/SODA ASH,FLU SH TO SEWER W.H*2O.
======================================
Handling and Storage Precautions:STORE IN COOL,DRY,WELL-VENTED,LOW FIRE RISK AREA.PROTECT FROM PHYSICAL DAMAGE.KEEP CONTAINERS CLOSED.AVOID STRONG ACIDS. Other Precautions:CONTAINERS HAZARDOUS WHEN AMPTY(RETAIN(S) PROTECT RESIDUE(S).AVOID PROLONGED OR REPEATED CONTACT.REMOVE AND WASH CONTAMINATED CLOTHING.
====== Exposure Controls

pt Qty:1000 LBS

/Personal Protection ========
Respiratory Protection:NONE NORMALLY NEEDED Ventilation:MECHANICAL(GENERAL)/LOCAL EXHAUST Protective Gloves:IMPERVIOUS/RUBB Eye Protection:SAFETY/CHEM GOGGLES Other Protective Equipment:PROTECTIVE CLOTHES TO PREVENT SKIN CONTACT. Supplemental Safety and Health ITEM IS ONE PART PRODUCT.DURING 1982,MFR REPLACED FORMULATION OF THIS CAT NO WITH FORMULATION OF CAT # 186 5567;SEE PNI-B, THIS NSN FOR NEW CAT # DATA.
========== Physical/Chemical Pro perties ==========
HCC:B1 Boiling Pt:>100.C, 212.F Vapor Pres:17 Vapor Density:0.6 Spec Gravity:1.11 Solubility in Water:COMPLETE Appearance and Odor:OFF-WHITE LIQUID-ODORLESS Percent Volatiles by Volume:87
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES STRONG ACIDS Hazardous Decomposition Products:NONE
Diamond Considerations

======= Disposal Considerations ===========

Waste Disposal Methods:NEUTRALIZE SPILL WITH SODI UM BISULFATE/SODA

ASH.FLUSH TO SEWER WITH LARGE AMTS OF WATER.DISPOSAL SHOULD BE IN ACCORDANCE WITH ALL FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this docume

nt should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.