View NSN Online: https://aerobasegroup.ae/nsn/6750-01-050-7789

Product ID:192 7698, FLEXCOLOR DEVLPR, PART-C (PRE 4/86) MSDS Date:03/01/1979 FSC:6750 NIIN:01-050-7789 Kit Part:Y **MSDS Number: BGJBB** === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info Phone Nu m:716-722-5151 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Ingred Name:4-(N-ETHYL-N-2-HYDROXYETHYL)-2-METHYLPHENYLENEDIAMINE SULFATE; WT % RANGE:15-20% (DISSOCIATES TO 10-15% H\*2SO\*4 IN WATER) CAS:25646-77-9 RTECS #:KJ6477000 Fraction by Wt: 17.0% Other REC Limits:1MG/CUM (H\*2SO\*4) OSHA PEL:17.5 Ingred Name:WATER; WT % RANGE:80-85 CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 82.5% Routes of Entry: Inhalation:UNKNOWN Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:NOT KNOWN Effects of Overexposure: INHALED: GAS(SO\*2) IRRITATS; EYE/SKIN: CONTACT W LIQ/GAS IRRITATS.REPEAT

LERGY.

First Aid:INHAL:REMOVE FROM EXPOSURE;EYES:FLUSH IMMEDIATELY WITH PLENTY OF WATER-GET MEDICAL ATTENTION SKIN:FLUSH IMMEDIATELY WITH PLENTY OF WATER

Flash Point:NONE Extinguishing Media:EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTUR ER.

Spill Release Procedures:STOP LEAK WITHOUT RISK.EVACUATE UNPROTECTED PERSONS.NEUTRALIZE WITH SODIUM BICARBONATE.DILUTE WITH COPIOUS AMOUNTS OF WATER AND FLUSH TO SEWER IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL EFFLUENT LAWS.

Handling and Storage Precautions:STORE IN COOL,DRY,LOW FIRE RISK AREA.KEEP TIGHTLY SEALED PROTECT FROM PHYSICAL DA MAGE.STORE AWAY

FROM MINERAL ACIDS AND STRONG ALKALI.

Other Precautions: ROUTINE USE OF A NON-ALKALINE (ACID) TYPE HAND CLEANER WILL HELP MINIMIZE THE POSSIBILITY OF ALLERGIC SKIN REACTION

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE SHOULD BE NEEDED Ventilation:MECHANICAL(GENERAL) RECOMMENDED.LOCAL EXHAUST IF NEEDED Protective Gloves:IMPERVIOUS Eye Protection:SAFETY GLASSES Other Protective Equipment:AS NECESSARY TO PREVENT SKIN CONTACT

Supplemental Safety and Health

ITEM IS A 3 PART KIT; THIS ENTRY DESCRIBES PART C OF OLD FORMULATION.EFFECTIVE DATE OF FORMULATION CHANGE IS NOT KNOWN; SOLUTION NO:3650, AND ACCESSION #UNKNOWN OF THIS PART; SEE PNI E FOR NEW FORMULA TION OF THIS PART; ALSO SEE PNI A, B,& DFOR OTHER PARTS; NOTE:CORR LIQ NOS IS BETTER THAN SULFURIC ACID,UN1830; KEY1:C1

HCC:C2 Boiling Pt:B.P. Text:212F/100C Vapor Pres:17 Vapo r Density:0.6 Spec Gravity:1.08 Solubility in Water:COMPLETE Appearance and Odor:REDDISH-BROWN,SULFUR DIOXIDE ODOR Percent Volatiles by Volume:62%

Stability Indicator/Materials to Avoid:YES MINERAL ACIDS AND STRONG ALKALI Hazardous Decomposition Products:SUFLUR DIOXIDE

Waste Disposal Methods:NEUTRALIZE WITH SODIUM BICARBONATE.DILUTE THEN FLUSH TO SEWER W ITH COPIOUS AMOUNTS OF WATER.FEDERAL,STATE AND

LOCAL EFFLUENT LAWS TAKE PRECEDENCE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and a

ssume responsibility for the suitability of this information to their particular situation.