View NSN Online: https://aerobasegroup.ae/nsn/6525-01-061-1694

EASTMAN KODAK COMPANY -- 121 6944,RP X-OMAT DEVL REPL,PT B(SEE SUPP)

6525-01-061-1694

============= Product Identification ===============

Product ID:121 6944,RP X-OMAT DEVL REPL,PT B(SEE SUPP)

MSDS Date:07/30/1980

FSC:6525

NIIN:01-061-1694

MSDS Number: BGJSZ === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650 Country:US

Emergency Phone Num: (716

) 722-5151 CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

======= Composition/Information on Ingredients ========

Ingred Name: DIETHYLENE GLYCOL (50-55%)

CAS:111-46-6

RTECS #:ID5950000 Fraction by Wt: 52.5%

Ingred Name: ACETIC ACID (SARA III)

CAS:64-19-7

RTECS #:AF1225000 Fraction by Wt: 37.5%

OSHA PEL:10 P

PMACGIH TLV:10 PPM/15 STEL; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name:1-PHENYL-3-PYRAZOLIDINONE (5-10%) CAS:92-43-3 RTECS #:UQ8750000 Fraction by Wt: 07.5% =========== Hazards Identification ========================== Effects of Overexposure: INH: VAP MAY CAUSE IRRITN; EYES: LIQ CONTCT MAY CAUSE BURNS; SKIN: LIQ CAUSES IRRIT/ALLERGIC REACTION. First Aid:GET MED ATTN IF IRRITATION OF EYES/SKIN PERSIST S. ============ Fire Fighting Measures ========================= Flash Point:NONE Extinguishing Media:CO*2, FOAM, DRY CHEM. Fire Fighting Procedures: NONE Unusual Fire/Explosion Hazard:NONE Spill Release Procedures: ELIM IGN SOURCES. STOP LEAK W/O RISK. WEAR PROTECTV EQUIPMNT; NEUTRALIZE SM SPILL W/SPDIUM BICARBONATE. FLUSH TO SEWER IAW FED. STATE & LOCAL REGS: LG SPILL: DIKE FAR AHEAD W/COMMERCIAL ABSORBENT FOR LA TER D ISPOSAL OR PUMP LIQ TO COVERED DRUMS. ========== Handling and Storage =============== Handling and Storage Precautions: STORE IN COOL, DRY, WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED Other Precautions: NONE KNOWN ====== Exposure Controls/Personal Protection ========

Respiratory Protection: AN APPROVED ORGANIC ACID RESPIRATOR IF VENTILATION IS INADEQUATE Ventilation: MECH(GEN)O

R LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY/CHEM GOGGLES
Other Protective Equipment: AS NECESSARY TO PREVENT SKIN CONTACT
Supplemental Safety and Health
THIS IS PART B OF 3 PARTS PRODUCT;PART B CAT #122 6240 WAS CHANGED TO
141 8151 & TO 162 0509 RESPECTIVELY. WITH THE CHANGE OF CAT #,MFR
ALSO CHANGED THE FORMULATION BUT KEPT THE SAME NSN.NEW FORMULATIO N
& NEW CAT # UNDER PNI-B OF THIS NSN; FOR PART A SEE NSN
6525-01-061-
1693 AND FOR PART C SEE NSN 6525-01-061-4366.
1093 AND FOR PART C SEE INSIN 0323-01-001-4300.
========== Physical/Chemical Properties =============
HCC:C2
Boiling Pt:B.P. Text:>212F/100C
Vapor Pres:15
Vapor Density:2.07
Spec Gravity:1.11
pH:2.0
Solubility in Water:COMPLETE
Appearance and Odor:ORANGISH OR LIGHT BROWN,VINEGAR ODOR
Percent Volatiles by Volume:70
========== Stability and Reactivity Data ===========
Stability Indicator/Materials to Avoid:YES
ALKALINE SOLUTIONS,STRONG OXIDIZERS/FLAMMABLE LIQUIDS.
S
tability Condition to Avoid:NONE KNOWN
========== Disposal Considerations ==============
Waste Disposal Methods:OR FOLLOW STEP OF NEUTRALIZATION IAW EFFLUENT
LAWS OF FED,STATE & LOCAL.
Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims a

Il liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.