View NSN Online: https://aerobasegroup.ae/nsn/6750-01-066-3215

Product ID:1216951 DACOMATIC DR-5 BLCH&RPLSH R-NEWFORM MSDS Date:07/30/1984 FSC:6750 NIIN:01-066-3215 MSDS Number: BGKBS === Responsible Party === Company Name:EASTMAN KODAK CO. Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Emergency Phone Num:716-722-5151

CAGE:19139 === Contractor Identification === Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139

Ingred Name:SULFAMIC ACID, WT% RANGE 15-20% CAS:5329-14-6 RTECS #:WO5950000 Fraction by Wt: 17.0%

Ingred Name:SODIUM DICHROMATE, WT% RANGE 1-5% CAS:10588-01-9 RTECS #:HY7700000 Fraction by Wt: 3% OSHA PE L:0.205 MG(MR)/CUM REL ACGIH TLV:0.05 MG(CR /CUM EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

Ingred Name:WATER, WT% RANGE 75-80% CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 80%

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic:BURNA, ALLERGIC REACTIONS. Explanation of Carcinogenicity:SODIUM DICHRDMATE IS TUMORIGEN AND ANIMAL INDEFINITE CARCINOGEN. Medical Cond Aggravated by Exposure :ANY PREXISTING ALLERGY OR SENSITIVITY.

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.R EMOVE & LAUNDER CONTMNTD CLOTHG/SHOES BEFORE RE-US

Flash Point:NONE Extinguishing Media :CO*2,DRY CHEM Fire Fighting Procedures:USE SELF-CONTND BRTHG APP;COOL EXPOSD CONT W/WATER SPRAY. Unusual Fire/Explosion Hazard:NONE KNOWN

Spill Release Procedures:WEAR FULL PROTECTIVE CLOTHING.DO NOT TOUCH DAMAGED CONTAINER OR SPILLAGE. IF CONTAINER LEAKING,COVER W DAMP TOWEL KEPT WET W LIQUID BLEACH. SPILLS:DIKE FOR LATER DISPOSAL CLEAN UP UNDER DIRECTION OF E XPERT.CONTACT CDC(404-633-5313)ATLANTA,GA.

=

Handling and Storage Precautions: AVOID CONTACT W/CLOTHING AND OTHER COMBUSTIBLES.

Other Precautions:WARNING:CAUSES BURNS.MAY CAUSE ALLERGIC SKIN REACTION.AVOID CONTACT W EYES,SKIN & CLOTHING.

======= Exposure Controls/Personal Protection ==========

Ventilation:LOCAL EXHAUST:NONE SHOULD BE NEEDED; MECH(GEN):RECOMMENDED.
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY/CHEM GOGGLES
Other Protective Equipment
:AS NEEDED BY LOCAL AUTHORITIES.
Work Hygienic Practices:REMOVE AND WASH ALL CONTAMINATED CLOTHING THOROUGHLY.
Supplemental Safety and Health
NEW FORMULA ENTRY PER MSDS #84-0061 DATED 30JUL84. SEE PNI=A FOR MATERIAL MANUFACTURED BEFORE JULY84.KEY1:C4.

HCC:C4 Boiling Pt:>100.C, 212.F Vapor Pres:18 Vapor Density:0.6 Spec Gravity:1.14 pH:2.0 Evaporation Rate & amp; Reference:0.4 (BUAC=1) Solubility in Water:COMPLETE Appea rance and Odor:AMBER SOLUTION,ODORLESS Percent Volatiles by Volume:80

Stability Indicator/Materials to Avoid:YES ALKALAIS, COMBUSTIBLE MATERIALS. Stability Condition to Avoid:UNK Hazardous Decomposition Products:NONE KNOWN

Waste Disposal Methods: DISPOSE VIA LICENSED DISPOSAL FACILITY OR CHEMICALLY TREAT LAW ALL LAWS & REGS. DO NOT FLUSH TO WATERWAYS OR

SEWER SYSTEM.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.