

TEXACO ING. -- 02316 MULTIGEAR LUBT EP SAE 80W-90 -- 9150-01-071-6222

=====  
Product Identification  
=====

Product ID:02316 MULTIGEAR LUBT EP SAE 80W-90

MSDS Date:01/01/1987

FSC:9150

NIIN:01-071-6222

MSDS Number: BGKKY

=== Responsible Party ===

Company Name:TEXACO ING.

Emergency Phone Num:914-831-3400 EX.204

CAGE:MO827

=== Contractor Identification ===

Company Name:TEXACO INC

Box:509

City:BEACON

Sta

te:NY

ZIP:12508-0509

Country:US

Phone:914-831-3400

CAGE:7B131

Company Name:TEXACO ING.

CAGE:MO827

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SOLVENT-DEWAXED HEAVY PARAFFINIC PETROLEUM,CAS#64742-65-0  
(TLV AS OIL MIST 5.0 MG/CUM)

Fraction by Wt: 57.5%

ACGIH TLV:5MG/CUM(OILMIST)

Ingred Name:HYDROTREATED C25 BRIGHT STOCK BASED LUBRICATING  
OIL,CAS#72623-83-7 (TLV AS OIL MIST)

Fraction by Wt: 42.5%

ACGIH TLV:5MG/CUM(OILMIST)

Ingred Name:ADDITIVE (PACKAGE

CONTAINING BORON,P AND SULFUR

Fraction by Wt: 7.5%

ACGIH TLV:NOT SPECIFIED

=====  
Hazards Identification  
=====

Effects of Overexposure:EYES:SL TO MOD IRRITATION;SKIN:IRRIT,REDNESS  
EDEMA OR DRYING OF SKIN;MAY IRRITATE RESPIRATORY TRACT.

=====  
First Aid Measures  
=====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O\*2 IF  
NEED;EYES/SKIN:FLUSH W LG AMTS H\*2O FOR 15 MIN;INGEST:RINSE MOUTH;  
GET MEDICAL ATTENTION FOR  
EYES, BREATHING DIFFICULTY, OR OTHER  
SYMPTOMS OF OVEREXPOSURE.

=====  
Fire Fighting Measures  
=====

Flash Point:360F/182C (COC)  
Extinguishing Media:WATER SPRAY,DRY CHEMICAL,FOAM,CO\*2,FOAM  
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN CONFINED AREA.  
Unusual Fire/Explosion Hazard:NONE NOTED

=====  
Accidental Release Measures  
=====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;WIPE UP OR  
ABSORB ON SUITABLE  
MATERIAL AND SHOVEL UP AND RECOVER FOR PROPER  
DISPOSAL.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED  
AREA;KEEP AWAY FROM HEAT,OPEN FLAME;KEEP CONTAINER CLOSED WHEN NOT  
IN USE.  
Other Precautions:AVOID CONTACT WITH SKIN,EYES AND CLOTHES;WASH  
THOROUGHLY AFTER EACH USE.DO NOT BREATHE VAPORS/MIST;DO NOT USE  
CONTAMINATED CLOTHES.

=====  
Exposure Controls/Personal Protection  
=====

=====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF > TLV

Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION

Protective Gloves:NEOPRENE

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:FULL PROTECTIVE CLOTHING,SAFETY SHOWER,EYE WASH STATION

Supplemental Safety and Health

MSDS DATED:04/16/86.

===== Physical/Chemical Properties =====

HCC:V6

Spec Gravity:0.9030

Solubility in Water:

NEGLIGIBLE

Appearance and Odor:RED,GREEN BLOOM

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE NOTED

Stability Condition to Avoid:HEAT,OPEN FLAMES

Hazardous Decomposition Products:CO,CO\*2,ALDEHYDE,KETONE,COMBUSTION PRODUCTS OF N,S.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer

(provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.