

KINDT COLLINS CO THE -- WAX 13 (SHEET) -- 9160-01-086-0145

===== Product Identification =====

Product ID:WAX 13 (SHEET)

MSDS Date:11/01/1985

FSC:9160

NIIN:01-086-0145

MSDS Number: BGLCZ

=== Responsible Party ===

Company Name:KINDT COLLINS CO THE

Address:12651 ELMWOOD AVE

City:CLEVELAND

State:OH

ZIP:44111-5911

Info Phone Num:216-252-4122

Emergency Phone Num:216-252-4122

Preparer's Name:PAUL A. GUIN

N

CAGE:33629

=== Contractor Identification ===

Company Name:KINDT COLLINS CO

Address:12651 ELMWOOD AVENUE

Box:City:CLEVELAND

State:OH

ZIP:44111-5911

Country:US

Phone:216-252-4122/CHEMTREC 800-424-9300

CAGE:33629

===== Composition/Information on Ingredients =====

Ingred Name:PRECISE COMPOSITION IS PROPRIETARY INFORMATION AVAILABLE TO
A PHYSICIAN IN EVENT OF A MEDICAL EMERGENCY.

RTECS #:9999999ZZ

Fraction by Wt: >99%

ACGIH TLV:2MG/CUM (MFR)

Ingred Name:THIS PRODUCT IS NOT

HAZARDOUS AS DEFINED BY THE OSHA HAZARD
COMMUNICATION STANDARD, CFR TITLE 29 1910.1200.
RTECS #:9999999ZZ

===== Hazards Identification =====

LD50 LC50 Mixture:N/K TLV/TWA FOR PARAFFIN WAX FUME=2MG/M3

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MOLTEN WAX FUMES MAY BE SLIGHTLY
IRRITATING TO EYES AND RESPIRATORY TRACT. MOLTEN WAX WILL CAUSE
BURNS ON CONTACT
WITH SKIN.

Explanation of Carcinogenicity:NOT LISTED

Effects of Overexposure:MOLTEN WAX FUMES MAY CAUSE SLIGHT IRRITATION TO
EYES AND RESPIRATORY TRACT. MOLTEN WAX WILL CAUSE BURNS ON CONTACT
WITH SKIN.

Medical Cond Aggravated by Exposure:NONE KNOWN

===== First Aid Measures =====

First Aid:FOR HOT WAX ON SKIN, COOL WITH WATER. APPLY ICE WATER OR
PACKS TO BURNED AREA IF LESS THAN 10% OF THE BODY. DO NOT REMOVE
WAX. GET MEDICAL ATTENTION. FO

R EYE CONTACT, FLUSH WITH WATER FOR
AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. FOR INGESTION, CONSULT
MEDICAL PERSONNEL. INHALATION: REMOVE VICTIM TO FRESH AIR. GET
MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:NOT SPECIFIED

Extinguishing Media:USE WATER FOG, FOAM, DRY CHEMICAL OR CO2. DO NOT
USE A DIRECT STREAM OF WATER. COOL FIRE-EXPOSED CONTAINERS WITH
WATER.

Fire Fighting Procedures:DO NOT ENTER CONFINED FIRE SPACE
WITHOUT

PROPER PROTECTIVE EQUIPMENT INCLUDING A NIOSH APPROVED
SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:PRODUCT WILL FLOAT AND CAN BE REIGNITED
ON SURFACE OF WATER. WAX MAY BURN ALTHOUGH NOT READILY IGNITABLE

===== Accidental Release Measures =====

Spill Release Procedures:MAY BURN ALTHOUGH NOT READILY IGNITABLE. USE
CAUTION WHEN CLEANING UP LARGE MOLTEN SPILLS. LARGE MOLTEN SPILL:
SHUT OFF SOURCE OF LEAK IF SAFE TO DO S

DURING COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods: PLACE IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.