View NSN Online: https://aerobasegroup.ae/nsn/6525-01-098-5797

Product ID:153 1151, RP X-OMAT DEVLPR REPLNSHR, PART C MSDS Date:01/01/1985 FSC:6525 NIIN:01-098-5797 MSDS Number: BGLRZ === Responsible Party === Company Name: EASTMAN KODAK COMPANY Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139

Ingred Name:ALDEHYDE BISULFITE PRODUCT(ALDEHYDE SODIUM SULFITE; % WT RANGE:20-25% Fraction by Wt: 22.5%

Ingred Name:GLUTARALDEHYDE CAS:111-30-8 RTECS #:MA2450000 Fraction by Wt: 12.5% OSHA PEL:C 0.2 PPM ACGIH TLV:C 0.2 PPM; 9192

Ingred Name:WATER;CAS #7732-18-5; %

WT RANGE:60-70% CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 65.0%

Effects of Overexposure:INH:VAP MAY IRRIT RESP TRACT;EYES:CAUSES EYE BURNS;SKIN:PROLNGD/REPEATD CONTACT CAUSES IRRITN/ALLRGY

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O\*2 IF NEED;EYES:FLUSH W LG AMTS H\*20 FOR 15 MIN;SKIN:FLUSH W LG AMTS H\*20;INGEST:RINSE MOUTH.IMMEDIATE

LY GET MED ATTN IF SKIN/EYES IRRIT OR ALLERGY REACTION DEVEL OPS, LAUNDR CONTMNTD CLOTHG.

Flash Point:NONE

Extinguishing Media:CO\*2, FOAM, DRY CHEM.

Fire Fighting Procedures:WEAR SCBA & PROTECTIVE CLOTHING TO PREVENT SKIN/EYE CONTACT.

Unusual Fire/Explosion Hazard: EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

Spill Rele

ase Procedures:AVOID INHALATION & SKIN CONTACT.WEAR SUITABLE PROTECTIVEEQUIPMENT;NEUTRALIZE SM SPILL W/SODIUM METABISULFITE.FLUSH TO SEWER IN ACID-FREE SEWER IAW FED STATE & LOCAL REGULATIONS;LG SPILL:DIKE FAR AHEAD & PUMP LIQ TO SALVAGE TANK FOR DISPOSL/NEUTRLIZ.

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAI NERS TIGHTLY CLOSED.AVOID MINERAL ACIDS. Other Precautions:MAY CAUSE SKIN IRRITATION & ALLERGIC SKIN REACTION;AVOID CONTACG W/SKIN,EYES,& CLOTHING.AVOID BREATHING VAPOR.USE W/ADEQUATE VENTILATION;READ CAUTION LABEL ON THE CONTAINER BEFORE USE.

======= Exposure Controls/Personal Protection ===============

Respiratory Protection: AN NIOSH-APPROVD ORGANIC VAPOR RESP OR FORMALDEHYDE VAP. Ventilation: MECHANICAL (GENERAL) RECOMMENDED, LOCAL EXHAUST IF NEEDED Protective Gloves: IMPE RVIOUS Eye Protection: SAFETY/CHEM GOGGLES Other Protective Equipment: NON-ALKALINE (ACID) TYPE HAND CLEANR MINIMZ SKIN ALLRGY ACTION Supplemental Safety and Health MSDS FM MFR DATED: 5/18/83; PART C OF 3 PART PRODUCT; PH APPROX 3.0; SEE P/N IND A & B, UNDER THIS NSN FOR PART A & B PART B DATA.KEY1; N1.

HCC:C1 Boiling Pt:B.P. Text:>212F(>100C Vapor Pres:18 Vapor Density:0.8 Spec Gravity:1.16 Solubility in Water:COMPLETE Appeara nce and Odor:CLEAR TO LIGHT BROWN SOLUTION;ALDEHYDE ODOR. Percent Volatiles by Volume:80%

Stability Indicator/Materials to Avoid:YES MINERAL ACIDS Hazardous Decomposition Products:SULFUR DIOXIDE,CO,CO\*2.

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE,

& LOCAL REGULATIONS.MFR

NOTES, NEUTRALIZE W/SOD METABISULFITE. FLUSH TO SEWER IAW EXISTING REGS FOR DISPOSAL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent profess ional advice to verify and assume responsibility for the suitability of this information to their particular situation.