

GENERAL PLASTICS MFG COMPANY -- LAST-A-FOAM,FRL-3602 PART A -- 9330-01-112-6383

=====
Product Identification
=====

Product ID:LAST-A-FOAM,FRL-3602 PART A

MSDS Date:01/01/1985

FSC:9330

NIIN:01-112-6383

MSDS Number: BGMHZ

=== Responsible Party ===

Company Name:GENERAL PLASTICS MFG COMPANY

Address:4910 BURLINGTON WAY

Box:9097

City:TACOMA

State:WA

ZIP:98409-2833

Country:US

CAGE:28014

=== Contractor I

dentification ===

Company Name:GENERAL PLASTICS MFG CO

Address:4910 BURLINGTON WAY

Box:9097

City:TACOMA

State:WA

ZIP:98409-2833

Country:US

Phone:206-473-5000

CAGE:28014

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYLENE BISPHENYL ISOCYANATE (MDI) (SARA III)

CAS:101-68-8

RTECS #:NQ9350000

Fraction by Wt: 50%

OSHA PEL:C, 0.02 PPM

ACGIH TLV:0.005 PPM; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:HI-POLYMERS OF SIMILIAR STRUCTURE

Fraction by Wt: 50%

===== Hazards Identification =====

Effects of Overexposure:IRRITATES MUCOUS MEMBRANE,CHEST
TIGHTNESS.IRRITATES RESPIRATORY TRACT,COUGHING,HEADACHE,BREATH SHO

===== First Aid Measures =====

First Aid:SKIN:WASH W/SOAP & WATER FOR AT LEAST 15 MIN.EYES:WASH WITH
LARGE AMTS OF WATER FOR A MINUMIUM OF 15 MIN. CONSULT AN EYE
DR.,INGEST:INDUCE VOMITING & CONSULT A DR. INHAL: REMOVE TO
UNCONTAMINATED AREA ,ADMINST
ER O*2

===== Fire Fighting Measures =====

Flash Point:415 F COC

Extinguishing Media:CO*2,DRY CHEMICAL,CHEM.FOAM OR WATER-FOG MAY BE
USED

Fire Fighting Procedures:USUAL BODY PROTECTION SHOULD WORN &
SELF-CONTAINED BREATH

===== Accidental Release Measures =====

Spill Release Procedures:ABOSRB IN ABSORBENT SWEEPING/CLEAN
COMPOUND(E.G."OILDRY"); REMOVE FROM AREA IN OPEN DRUMS & TREAT WITH
WATER CONTAINING 1% AMMONIA BE
FORE DISPOSAL

===== Handling and Storage =====

Handling and Storage Precautions:THIS ISOCYANATE SHOULD BE PROTECTED
FROM WATER BY DRY ATMOSPHERE AND MAINTAINED AT 65F TO 75 F.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:CANISTER TYPE GAS MASKS EQUIPPED FOR ORGANIC
VAPORS;MASKS SUPPLIED

Ventilation:LOCAL EXHAUST:TO MAINTAIN VAPOR CONCENTRATION BELOW TLV

Protective Gloves:CHEM.RESI

Eye Protection:CHEM.SAF

ETY GOGGLES

Other Protective Equipment:SAFETY SHOWERS & EYE WASH STATIONS SHOULD BE AVAILABLE

Supplemental Safety and Health

MSDS IS UNDATED. THE FORMULA WAS PREVIOUSLY CALLED FRL 6602 PART A.PROTECT FROM WATER BY A DRY ATMOSPHERE& MAINTAIN AT 65-75F.MDI IS A SENSITIZER OF THE RESP.TRACT.STORAGE CODE BASE ON TLV MDI

===== Physical/Chemical Properties =====

HCC:T4

Boiling Pt:B.P. Text:406 F

Vapor Pres:NIL

Spec Gravity:1.24

Solubility in Water:INSOLUBLE

Ap

pearance and Odor:BROWN VISCOUS LIQUIDS;ODOR-VERY SLIGHTLY AROMATIC

===== Stability and Reactivity Data =====

AVOID CONTACT WITH WATER,ALCOHOLS,STRONG BASES OR METAL CMP.

Stability Condition to Avoid:AVOID TEMP.>120F OR BELOW 32 F

Conditions to Avoid Polymerization:AVOID CONTACT W/MOISTURE & OTHER MATERIALS WHICH REACT WITH

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF WASTE IN ACCORDANCE W/FED.STATE,AND

LOCAL LAWS REGARDING ENVIRONMENTAL CONTROL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.