

EASTMAN KODAK COMPANY -- 139 5508,EKTPRNT R-1000 COLR DEVLPR,PART C --  
6750-01-112-9401

===== Product Identification =====

Product ID:139 5508,EKTPRNT R-1000 COLR DEVLPR,PART C

MSDS Date:01/01/1985

FSC:6750

NIIN:01-112-9401

MSDS Number: BGMJJ

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-515

1

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:HYDROXYLAMINE SULFATE;CAS #10039-54-0;(DISSOCIATES TO  
SULFURIC ACID 5-10%);% WT 5-10%

CAS:10039-54-0

RTECS #:NC5425000

Fraction by Wt: 7.5%

Ingred Name:A

QUEOUS SOLUTION,HAZARD INKNOWN,UNIDENTIFIED;% WT BY  
DIFFERENCE 92.5%

Fraction by Wt: 92.5%

===== Hazards Identification =====

Effects of Overexposure:EYES:CAUSES IRRITN;SKIN:MAY CAUSE IRRITN;  
REPEATD CONTACT W/SKIN MAY CAUSE ALLRGIC REACTION/TOXIC.

===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O2 IF NEED;EYES:FLUSH W  
LG AMTS H2O FOR 15 MIN;SKIN:FLUSH W LG AMTS H2O;INGEST: RINSE  
MOUTH.

===== Fire Fighting Measures =====

Flash Point:NONE  
Extinguishing Media:CO2, FOAM, DRY CHEM.  
Fire Fighting Procedures:NONE  
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS. ELIM IGNITION  
SOURCES. STOP LEAK. H2O SPRAY COOL CONT/DIVERT SPILL FROM  
FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL  
ABSORBENT,SHOVEL INTO METAL DRUMS  
: LG SPILL:DI KE W COMMERCIAL  
ABSORBENT,PUMP INTO COVERED DRUMS

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED  
AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP  
CONTAINERS TIGHTLY CLOSED  
Other Precautions:NONE KNOWN

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED  
Ventilation:NO SPECIAL REQUIREMENTS W ADEQUATE VE

NT.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED CONTACT.

Supplemental Safety and Health

MSDS FM MFR DATED:1/30/79;THIS DATA DESCRIBES PART C OF 3 PART

PRODUCT;SEE P/N IND A & B FOR OTHER PARTS,SAME NSN;STORAGE CODE C1

ASSIGNED BECAUSE SOLN GIVES H2SO4 ON DISSOCIATION;PH 3.5. KEY1:J1.

===== Physical/Chemical Properties =====

HCC:C1

Boiling Pt:B.P. Text:>212F/100C

Vapor Pres:17

Vap

or Density:0.6

Spec Gravity:1.08

Solubility in Water:COMPLETE

Appearance and Odor:PINK-PURPLE ODORLESS LIQUID.

Percent Volatiles by Volume:91.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

PER MFR, NONE

Hazardous Decomposition Products:PER MFR, NONE

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE &  
DISPOSE IN FULL COMPLIANCE WITH ALL  
APPLICABLE

INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS. MFR NOTES,FLUSH  
TO SEWER W/COPIOUS AMTS OF H2O IAW ALL EXISTING REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document

should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.