

STERLING LACQUER MFG. CO. -- EPOXY POLYAMIDE PRIMER, COMPONENT B -- 8010-01-120-5004

=====  
Product Identification  
=====

Product ID:EPOXY POLYAMIDE PRIMER, COMPONENT B

MSDS Date:01/01/1987

FSC:8010

NIIN:01-120-5004

Kit Part:Y

MSDS Number: BGMRT

=== Responsible Party ===

Company Name:STERLING LACQUER MFG. CO.

Address:3150 BRANNON AVE

City:ST LOUIS

State:MO

ZIP:63139-1422

Country:US

CAGE:22181

=== C

Contractor Identification ===

Company Name:STERLING LACQUER MFG

Address:3150 BRANNON AVE

Box:City:ST LOUIS

State:MO

ZIP:63139-1422

Country:US

CAGE:22181

=====  
Composition/Information on Ingredients  
=====

Ingred Name:AROMATIC HYDROCARBONS

Fraction by Wt: 47%

ACGIH TLV:200PPM

Ingred Name:ALCOHOLS (TYPE NOT SPECIFIED)

Fraction by Wt: 53%

ACGIH TLV:100 PPM

=====  
Hazards Identification  
=====

Effects of Overexposure:EYE & SKN CONTACT;PRIMARY IRRIT

.INHAL:IRRIT OF  
RESPIR TRACT AND/OR NARCOSIS.

=====  
First Aid Measures  
=====

First Aid:EYE CONTACT:FLUSH W/WATER F/15 MINUTES.TAKE TO PHYSICIAN.SKIN CONTACT:WASH W/SOAP & WATER.NOTIFY PHYSICIAN.INHAL:FRESH AIR & TREATMENT FOR EFFECTS OF SOLVENT FUMES.DR. CONSULTATION:DO NOT INDUCE VOMIT ING IF INGESTED.

=====  
Fire Fighting Measures  
=====

Flash Point:45 F CC/7 C CC

Lower Limits:1.0

Upper Limits:11

Extingui

shing Media:CO\*2, FOAM OR DRY CHEM(NFPA)CLASS B EXTINGUISHERS

Fire Fighting Procedures:DO NOT USE WATER.

Unusual Fire/Explosion Hazard:ISOLAT FR HEAT,ELECTR EQPMT,SPARKS & OPN FLAME.CLOS CONTNRS MAY EXPLOD WHN EXPOS TO EXTREME HEAT(SUP

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOV ALL SOURCES OF IGNITION (FLAMES,HOT SURFACES & ELECTRSTATIC OR FRICTIONAL SPARKS). AVD BREATHING VAPORS.VENTILATE AREA.REMOV W/INNER & ABSORBENT & NON SPARKING TOOLS

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120 F. STORE LG QUANTIT IN BLDGS DESIGN & PROTECTED FOR STORAGE OF NFPA CL 1B FLAMMBL LIQUIDS.

Other Precautions:DO NOT TAKE INTERNALLY. WHEN HANDLINGS LG VOLUMES GROUND CONTNRS WHN POURING & AVOID FREE FALL. POURING IN EXCESS OF A FEW INCHES.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:APPRVD

BUR OF MNES DEVICE F/TYPE

AREA(OUTDR,RESTRICT,VENT OR CONFINE

Ventilation:LOC EXHAUST-PROVID GEN. DILUT OR LOC EXHAUST VENTIL IN  
(SUP)

Protective Gloves:FOR PRLNG CONTC

Eye Protection:AGNST LIWD SPLASHES

Other Protective Equipment:PRVNT PROLNGED SKN CONTCT TO CONTAMINATED  
CLOTHING.

Supplemental Safety and Health

VENTIL;VOLUME PATTERN TO KEEP TLV BELOW ACCEPTABLE LIMIT.KEY1:F3.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:179

Vapo

r Pres:31.

Vapor Density:HEAV

Spec Gravity:0.854

Evaporation Rate & Reference:2.1 BUTYL ACETATE

Solubility in Water:SLIGHT

Appearance and Odor:AMBER LIQUID,AROMATIC HYDROCARBON ODOR

Percent Volatiles by Volume:83

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IAW LOCAL,STATE & FEDERAL  
REGULATIONS.INCINERATE IN APPROVED FACI  
LITY. DO NOT INCINERATE  
CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability

of this information to their particular situation.