View NSN Online: https://aerobasegroup.com/nsn/6850-01-263-8433

MAGNAFLUX CORPORATION -- ZL-37 ZYGLO PENETRANT(WATER WASHABLE) -- 6850-01-263-8433

============= Product Identification ========================

Product ID:ZL-37 ZYGLO PENETRANT(WATER WASHABLE)

MSDS Date:07/17/1986

FSC:6850

NIIN:01-263-8433

MSDS Number: BGRRV === Responsible Party ===

Company Name: MAGNAFLUX CORPORATION

Address:7300 W.LAWRENCE AVENUE

City:CHICAGO

State:IL

ZIP:60656-3504 Country:US

Info Phone Num:312-867-800

Ω

Emergency Phone Num:312-867-8000 Preparer's Name:BRUCE C. GRAHAM

CAGE:37676

=== Contractor Identification ===

Company Name: ILLINOIS TOOL WORKS INC MAGNAFLUX DIV

Address:3624 WEST LAKE AVENUE

Box:City:GLENVIEW

State:IL ZIP:60025 Country:US

Phone:847-657-5300/

CAGE:37676

======= Composition/Information on Ingredients ========

Ingred Name: DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE

CAS:64742-46-7 RTECS #:JN9379645 Fraction by Wt: 10.0%

Ingred Name: KEROSENE

CAS:8008-20-6 RTECS #:OA5 500000

Fraction by Wt: 05.0% ACGIH TLV:100MG/CUM

Ingred Name: UNIDENTIFIED COMPONENTS

Fraction by Wt: 200F/>93C

Extinguishing Media: CARBON DIOXIDE, FOAM

Fire Fighting Procedures: KEEP CONTAINERS COOL WITH WATER SPRAY.DO NOT

SPRAY WATER ON BURNING ZL-37

Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION,MAY EMIT TOXIC

GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.

======== Accidental Release Measures ============

Spill Release Procedures:REMOVE IGNITION SOURCES.SM QT Y:WIPE UP OR MOP

UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB LIQUID WITH COMMERCIAL ABSORBEN T.TRANSFER WASTE MATL IN SALVAGE TANKS.

============ Handling and Storage ===========================

Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions: DO NOT BREATHE

VAPORS.DO NOT SMOKE WHILE USING.DO NOT

HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.

===== Exposure Controls/Personal Protection ========

Respiratory Protection:WEAR RESPIRATOR WITH CHEMICAL CARTRIDGE IF USING IN POORLY VENTILATED AREA.AVOID BREATHING VAPOR OR SPRAY MIST.

Ventilation: GENERAL VENTILATION TO KEEP BELOW LIMITS OF TLV.

Protective Gloves: NITRILE GLOVES IF USING FREQUENTLY

Eye Protection: FULL GOGGLES WHEN SPRAYING OR POURING

Other Protective

Equipment: USE IN SPRAY BOOTH OR WHERE VENTILATION IS ADEQUATE TO CARRY VAPORS & OVERSPRAY FROM OCCUPIED AREAS.

Work Hygienic Practices: WASH OFF PROMPTLY WITH WATER. AVOID SKIN CONTACT.

Supplemental Safety and Health

NSN OF MIL-I-25135D,TYPE I,METHOD C,LEVEL 3;PER QPL-25135-15,MAGNAFLUX CORP.,MAY SUPPLY ONE OF THE FOLLOWING PENETRANTS FOR TYPE I,METHOD C,LEVEL 3,NSN:ZL-22D,ZL-27A,ZL-37,ZL-54A,ZL-55 OR ZL-66A;THIS ENTRY DESCRIBES ZL-37;PRODUCT NOT AVAILABLE IN AEROSOL CANS;SEE

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES
NONE KNOWN
Stability Condition to Avoid:HEAT,HIGH TEMPERATURES
Hazardous Decomposition P
roducts:EMITS OXIDES OF CARBON AND NITROGEN ON
COMBUSTION

Percent Volatiles by Volume:5%

======= Disposal Considerations ============

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D001 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE FEDERAL,STATE,LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.