View NSN Online: https://aerobasegroup.ae/nsn/6850-01-265-2741

MAGNAFLUX CORPORATION -- ZL-60C WATER WASHABLE PENETRANT -- 6850-01-265-2741

Product ID:ZL-60C WATER WASHABLE PENETRANT

MSDS Date:03/17/1987

FSC:6850

NIIN:01-265-2741

MSDS Number: BGRWQ === Responsible Party ===

Company Name: MAGNAFLUX CORPORATION

Address:7300 W LAWRENCE AVE

City:CHICAGO

State:IL

ZIP:60656-3504 Country:US

Info Phone Num:312-867-8000

Emergency Phon e Num:312-867-8000

Preparer's Name: BRUCE C. GRAHAM (CHEMIST)

CAGE:37676

=== Contractor Identification ===

Company Name: ILLINOIS TOOL WORKS INC MAGNAFLUX DIV

Address:3624 WEST LAKE AVENUE

Box:City:GLENVIEW

State:IL ZIP:60025 Country:US

Phone:847-657-5300/

CAGE:37676

======= Composition/Information on Ingredients ========

Ingred Name: HYDROTREATED MIDDLE PETROLEUM DISTILLATE

CAS:64742-46-7 RTECS #:JN9379645 Fraction by Wt: 40%

Other REC Limits: NONE ESTABLISHED

Ingred Name: ALIPHATIC

PETROLEUM SOLVENT CAS:8008-20-6 RTECS #:OA5500000 Fraction by Wt: 10% Other REC Limits: NONE ESTABLISHED ========== Hazards Identification ================= Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: IRRITATES EYES. Effects of Overexposure: INHALATION: CAUSES DIZZINESS, DROWSINESS, NAUSEA: SKIN:LIQUID IRRITATES BY DISSOLVING SKIN OIL; EYES:VAPORS/LIQUID CAUSES IRRITATION. Medi cal Cond Aggravated by Exposure: NOT KNOWN First Aid:INHALATION:REMOVE TO FRESH AIR.IF BREATHING IS DIFFICULT, GIVE OXYGEN; SKIN:REMOVE CONTAMINATED CLOTHES.WASH OFF WITH FLOWING WATER.USE SOOTHING LOTION.IF IRRITATION PERSISTS, GET MEDICAL ATTN: EYES: IMM EDIATELY RINSE/FLUSH WITH COPIOUS AMOUNT OF RUNNING WATER, AND GET MEDICAL ATTENTION; INGESTION: NOT NOTED BY THE MANUFACTURER.HOWEVER,GET MED ATTN IMMEDIATEL Y IF INGESTED. ============ Fire Fighting Measures ========================= Flash Point Method:PMCC Flash Point:>200F/>93C Lower Limits:6.0 Upper Limits: 1.0 Extinguishing Media: CARBON DIOXIDE, FOAM Fire Fighting Procedures: KEEP CONTAINERS COOL WITH WATER SPRAY. DO NOT SPRAY WATER ON BURNING PRODUCT. Unusual Fire/Explosion Hazard: WHEN INVOLVE IN COMBUSTION, MAY EMIT TOXIC GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.

======== Accidental Release Measures ==========

S	pill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP
	UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG
	QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB
	LIQUID WITH COMMERCIAL ABSORBEN T.TRANSFER WASTE MATERIAL TO
	SALVAGE TANKS.

=========== Handling and Storage =================

Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP

CONTAINERS TIGHTLY CLOSED.

Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.

===== Exposure Controls/Personal Protection ========

Respiratory Protection:WEAR A RESPIRATOR WITH ABSORBENT CARTRIDGE IN POORLY VENTILATED AREAS.IN CONFINED,UNVENTILATED SPACES,WEAR FULL MASK WITH AIR SUPPLY.

Ventilation: GENERAL VENTILATION TO KEEP BELOW TLV LIMITS.

Protective Gloves:NITRILE RUBBER GLOVE

S

Eye Protection: CHEMICAL SPLASH/FULL GOGGLES

Work Hygienic Practices: WASH HANDS WITH SOAP/WATER AFTER HANDLING/USE. Supplemental Safety and Health

ITEM IS ONE PART;NSN ESTABLISHED IN 1987 WAS FOR TYPE I,METHOD C,LEVEL 2 MATERIALS;THIS ENTRY DESCRIBES ZL-60C PENETRANT WHICH IS TYPE I,METHOD C,LEVEL 2 ITEM AS SPECIFIED BY QPL-25135-15 FOR MIL-I-25 135,REV "D";SEE OTHER PNI OF THIS NSN FOR OTHER PRODUCTS OF MAGNAFLUX FOR THE SAME TYPE,METHOD & LEVEL.

===	==	=====	=======	Physical/C
		. —		

hemical Properties ========

HCC:N1

Boiling Pt:B.P. Text:410F/210C

Vapor Pres: 0.5 @ 100F

Vapor Density:>1.0

Spec Gravity:0.88

Solubility in Water: NEGLIGIBLE

Appearance and Odor:GREEN OILY LIQUID,PETROLEUM HYDROCARBON ODOR Percent Volatiles by Volume:5.0%

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid: HEAT, HIGH TEMPERATURES.

Hazardous Decomposition Products: EMITS OXIDE

S OF CARBON WHEN BURNING.

======= Disposal Considerations ============

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D001 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE FEDERAL,STATE,LOCAL REGULATIONS;IF LOCAL REGS PROHIBIT DUMPING RINSINGS DOWN THE SEWER,PURIFY R INSINGS WITH MAGNAFLUX WASTEWATER TREATMENT SYSTM.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.