View NSN Online: https://aerobasegroup.ae/nsn/6850-01-266-4548

Product ID:ZR-10B REMOVER (HYDROPHILIC EMULSIFIER) MSDS Date:07/17/1986 FSC:6850 NIIN:01-266-4548 Kit Part:Y MSDS Number: BGRYG === Responsible Party === Company Name: MAGNAFLUX CORPORATION Address:7300 W.LAWRENCE AVENUE City:CHICAGO State:IL ZIP:60656-3504 Country:US Info Phone N um:312-867-8000 Emergency Phone Num:312-867-8000 Preparer's Name: BRUCE C. GRAHAM CAGE:37676 === Contractor Identification === Company Name: ILLINOIS TOOL WORKS INC MAGNAFLUX DIV Address:3624 WEST LAKE AVENUE Box:City:GLENVIEW State:IL ZIP:60025 Country:US Phone:847-657-5300/ CAGE:37676

Ingred Name:HEXYLENE GLYCOL CAS:107-41-5 RTECS #:SA0810000 Fraction by Wt: 65.0%

Health Hazards Acute and Chronic:IRRITATES YES.
Explanation of Carcinogenicity:PER MFR,CONTAINS NO KNOWN OR SUSPECTED CARCINOGEN LISTED WITH OSHA.
Effects of Overexposure:NOT KNOWN.
Medical Cond Aggravated by Exposure:NOT KNOWN

First Aid:INHALATION:REMOVE TO FRESH AIR.IF BREATHING IS DIFFICULT,GIVE OXYGEN; SKIN:REMOVE CONTAMINATED CLOTHES.WASH OFF WITH FLOWING WATER.USE SOOTHING LOTION.IF IRRITATION PERSI STS,GET MEDICAL ATTN; EYES:IMM EDIATELY RINSE/FLUSH WITH COPIOUS AMOUNT OF RUNNING

WATER, AND GET MEDICAL ATTENTION.

Flash Point Method:PMCC Flash Point:>200F/>93C Extinguishing Media:CARBON DIOXIDE, FOAM, WATER Fire Fighting Procedures:KEEP CONTAINERS COOL WITH WATER SPRAY. Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION,MAY EMIT TOXIC GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.

====== Acci

Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB LIQUID WITH COMMERCIAL ABSORBEN T.TRANSFER WASTE MATL IN SALVAGE TANKS.

Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL VENTILATED AREA.AVOID AGAINST
PHYSICAL DAMAGE TO CONTAINERS.KEEP CONTAINERS TIGHTLY CLOSED.
Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:WEAR A RESPIRATOR WITH CHEMICAL CARTRIDGE. IN CONFINED AREAS,WEAR A FULL MASK WITH SEPARATE AIR SUPPLY. Ventilation:GENERAL VENTILATION TO KEEP BELOW TLV LIMITS. Protective Gloves:NITRILE RUBBER GL OVES

Eye Protection: FULL GOGGLES

Other Protective Equipment: EITHER USE IN A SPRAY BOOTH OR NEXT TO AN EXHAUST VENT.

Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

NSN FOR SET/KIT OF MIL-I-25135D, TYPE I,METH D,LEVL 2;SET MAY CONSIST OF ZL-2C,OR ZL-2D PENETRANT AND ZR-10A OR ZR-10B EMULSIFIER OF 20% CONCENTRATION AS SPECIFIED IN QPL-25135-15;ZR-10A/ZR-10B REMVR IS HYDROPHILIC EMULSIFIER;THIS EN

TRY OFZR-10B;ALSO AVAILABLE AS

INDEPENDENT ITEM;KEY1:N1;FOR PENETRANTS,SEE PNI A & B.

HCC:N1 Boiling Pt:B.P. Text:400F/204C Vapor Pres:1.0 Spec Gravity:0.9 pH:7.0 Solubility in Water:COMPLETE Appearance and Odor:PINK OILY LIQUID

Stability Indicator/Materials to Avoid:YES NOT KNOWN TO MFR. Stability Condition to Avoid:HEAT,HIGH TEMPERATURES Hazardous Dec omposition Products:EMITS OXIDES OF CARBON AND NITROGEN.

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D001 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE FEDERAL,STATE,LOCAL REGULATIONS.IF LOCAL AUTHORITIES PROHIBIT DUMPING RINSINGS DOWN THE SEWER,P URIFY RINSINGS WITH MAGNAFLUX WASTEWATER SYSTEM.

Disclaimer (provided with this information by the compiling agencies): This infor

mation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.