View NSN Online: https://aerobasegroup.ae/nsn/6850-01-269-4151

Product ID:ZL-15B ZYGLO WATER WASH PENETRANT MSDS Date:01/29/1987 FSC:6850 NIIN:01-269-4151 MSDS Number: BGSGD === Responsible Party === **Company Name: MAGNAFLUX CORPORATION** Address:7300 W.LAWRENCE AVENUE City:CHICAGO State:IL ZIP:60656 Country:US Info Phone Num:312-867-8000 **Emergency Ph** one Num:312-867-8000 CAGE:37676 === Contractor Identification === Company Name: ILLINOIS TOOL WORKS INC MAGNAFLUX DIV Address:3624 WEST LAKE AVENUE Box:City:GLENVIEW State:IL ZIP:60025 Country:US Phone:847-657-5300/ CAGE:37676

Ingred Name:DISTILLATES, (PETROLEUM) HYDROTREATED MIDDLE CAS:64742-46-7 RTECS #:JN9379645 Fraction by Wt: 93C Lower Limits:6.0 Upper Limits:1.0 Extinguishing Media:CARBON DIOXIDE,FOAM Fire Fighting Proce

dures:KEEP CONTAINERS COOL WITH WATER SPRAY.DO NOT SPRAY WATER ON BURNING PRODUCT. Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION,MAY EMIT TOXIC GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.
======================================
Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB LIQUID WITH COMM ERCIAL ABSORBEN T.TRANSFER WASTE MATERIAL TO SALVAGE TANKS.
======================================
Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP CONTAINERS TIGHTLY CLOSED.
Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.
======================================
Respiratory Protection:WEAR A RESPIRATOR WITH ABSORBENT CARTRIDGE IN POORLY VENTILATED AREAS.IN CONFINED,UNVENTILATED SPACES,WEAR FULL MASK WITH AIR SUPPLY.
Ventilation: GENERAL VENTILATION TO KEEP BELOW TLV LIMITS. Protective Gloves: NITRILE RUBBER GLOVES
Eye Protection:CHEMICAL SPLASH/FULL GOGGLES
Work Hygienic Practices:WASH HANDS WITH SOAP/WATER AFTER HANDLING/USE. Supplemental Safety and Health
ZL-15B WATER WASH PENETRANT IS ONE PART ITEM; QPL-25135-15 QUALIFIED ZL-15
B UNDER TYPE I,METHOD C,LEVEL 1/2(LEVEL 1 OR 2) OF
MIL-I-25135,REVISION D; NSN ESTABLISHED IN 1987 WAS FOR TYPE I,METHOD C,LEV EL 2;THE QPL ALSO QUALIFIED OTHER PRODUCT OF
MAGNAFLUX UNDER SAME TYPE, METHOD & LEVEL. SEE OTHER PNIS.
======================================
HCC:N1
Boiling Pt:B.P. Text:410F/210C Vapor Pres:0.5 @100F
Vapor Density:>1.0 Spec Gravity:0.88
opoo oravity.o.oo

Spec Gravity:0.88 Solubility in Water:NEGLIGIBLE Appearance and Odor:GREEN OILY LIQUID,PETROLEUM HYDROCARBON O

DOR Percent Volatiles by Volume:5.0%

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:HEAT,HIGH TEMPERATURES Hazardous Decomposition Products:EMITS OXIDES OF CARBON WHEN BURNING.

Waste Disposal Methods: INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D001 (IGNITABLE WASTE), IN ACCORDANCE WITH ALL APPLICABLE

FEDERAL, STATE, LOCAL REGULATIONS; IF LOCAL REGS PROHIBIT DUMPING RINSINGS DOWN THE SEWER, PURIFY R INSINGS WITH MAGNAFLUX WASTEWATER TREATMENT SYSTM.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.