View NSN Online: https://aerobasegroup.ae/nsn/6810-00-973-6472

SIGMA CHEMICAL CO -- CHLOROFORM, ACS GRADE -- 6810-00-973-6472

Product ID:CHLOROFORM, ACS GRADE MSDS Date:12/04/1989 FSC:6810 NIIN:00-973-6472 MSDS Number: BGSQV === Responsible Party === Company Name: SIGMA CHEMICAL CO Address:3050 SPRUCE ST City:ST LOUIS State:MO ZIP:63103 Country:US Info Phone Num:800-325-8070 Emergency Phone Num:314-771-5765 CAGE:21076 === Contr actor Identification === Company Name: SIGMA CHEMICAL COMPANY Address:3050 SPRUCE ST Box:14508 City:ST LOUIS State:MO ZIP:63178 Country:US Phone:314-771-5765 CAGE:21076 Ingred Name:CHLOROFORM (SARA III) CAS:67-66-3 RTECS #:FS9100000 Fraction by Wt: >99% Other REC Limits:NONE RECOMMENDED **OSHA PEL:C 50 PPM** ACGIH TLV:10 PPM; A2; 9394 EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

LD50 LC50 Mixture:LD50 ORAL RAT=908MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO Health Hazards Acute and Chronic:SEE SIGNS AND SYMPTOMS OF OVEREXPOSURE FOR ACUTE EFFECTS; CHRONIC EFFECTS: DAMAGE TO LIVER, KIDNEY, HEARING. Explanation of Carcinogenicity: CHLOROFORM IS A SUSPECTED HUMAN CARCINOGEN. Effects of Overexposure: EYE: IRRITATION, SKIN: IRRITATION, INHALATION: NAUSEA, IRRITATION TO MUCOUS MEMBR ANCES & UPPER RESPIRATORY TRACT. Medical Cond Aggravated by Exposure: ALCOHOL CONSUMPTION INCREASES TOXIC EFFECTS. First Aid:EYES:FLUSH LARGE AMOUNTS OF WATER;SKIN:FLUSH WITH PLENTY OF WATER WHILE REMOVING CLOTH & SHOES; INHALATION: REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NEEDED.SEE DOCTOR. Flash Point:NONE Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard: FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS, SUCH AS HYDROGEN GAS, PHOSGENE GAS, CARBON MONO & DIOXIDES. Spill Release Procedu res: EVACUATE PERSONNEL. WEAR SCBA & PERSONAL **PROTECTIVE CLOTHING & BOOTS.ABSORB IN INERT MATERIAL &** CONTAINERIZE.FLUSH AREA WITH LARGE AMOUNT OF WATER. Handling and Storage Precautions: USE IN CHEMICAL FUME HOOD. DO NOT BREATHE VAPOR. AVOID ALL CONTACT. KEEP TIGHTLY CLOSED. PROTECT FROM LIGHT.STORE IN COOL, DRY PLACE.

Respiratory Protection:NIOSH/MS

HA APPROVED RESPIRATORY DEVICE I/A/W EXPOSURE OF CONCERN. Ventilation:USE CHEMICAL FUME HOOD WITH EXHAUST VENTILATION. Protective Gloves:RUBBER Eye Protection:SPLASH GOGGLES Other Protective Equipment:EYE BATH,SAFETY SHOWER,APRON. Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING-LAUNDER CONTAMINATED CLOTHING BEFORE REUSE Supplemental Safety and Health

HCC:T4

Boiling Pt:B.P. Text:141F,61C Melt/Freeze Pt:M.P/F.P T ext:-81F,-63C Vapor Pres:160 Vapor Density:4.1 Spec Gravity:1.492 Solubility in Water:SLIGHT Appearance and Odor:COLORLESS LIQUID WIYH SWEET ODOR.

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, BASES AND ALUMINUM. Stability Condition to Avoid:EXPOSURE TO LIGHT, HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES Hazardous Decomposition Products:HCL,PHOSGENE,CO,CO2.

======= Disposal Considerations

Waste Disposal Methods:IGNITE IN PRESENCE OF SODIUM CARBINATE & CALCIUM HYDROXIDE.MATERIAL SHOULD BE MIXED WITH ABSORBENT & THEN WITH DRY CAUSTICS, WRAPPED IN PAPER & BURNED IN A CHEMICAL INCINERATOR WITH AFTERBURNER & SCRU BBER,OBSERVE FEDERAL,STATE & LOCAL LAWS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner

whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.