

UNION CARBIDE CORP, LINDE DIV. -- HELIUM -- 6830-01-008-3431

===== Product Identification =====

Product ID:HELIUM

MSDS Date:09/01/1985

FSC:6830

NIIN:01-008-3431

MSDS Number: BGSQX

=== Responsible Party ===

Company Name:UNION CARBIDE CORP, LINDE DIV.

Address:39 OLD RIDGEBURY RD

City:DANBURY

State:CT

ZIP:06817-0001

Info Phone Num:304-744-3487

Emergency Phone Num:304-744-3487

CAGE:36346

=== Contracto

r Identification ===

Company Name:UNION CARBIDE CORP LINDE DIV

Address:39 OLD RIDGEBURY RD

Box:City:DANBURY

State:CT

ZIP:06817-0001

Country:US

Phone:800-822-4357; 304-744-3487

CAGE:36346

===== Composition/Information on Ingredients =====

Ingred Name:HELIUM

CAS:7440-59-7

RTECS #:MH6520000

Fraction by Wt: 100%

OSHA PEL:SIMPLE ASPHYXIAN

ACGIH TLV:SIMPLE ASPHYXIAN

===== Hazards Identification =====

LD50 LC50 Mixture:SIMPLE ASPHYXIAN

Routes

of Entry: Inhalation: YES Skin: NO Ingestion: NO
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO
Health Hazards Acute and Chronic: ACUTE: ASPHYXIAN. MODERATE
CONCENTRATIONS MAY CAUSE HEADACHE, DROWSINESS, DIZZINESS,
EXCITATION, EXCESS SALIVATION, VOMITING AND UNCONSCIOUSNESS.
CHRONIC: NO EVIDENCE OF ADVERSE EFFECTS FROM AVAILABL E
INFORMATION.

Explanation of Carcinogenicity: NOT LISTED
Effects of Overexposure: INHALATION: ASPHYXIAN. MODERATE CONCENTRATIONS
MAY CAUSE HEADACHE, DROWSINESS, DIZZINESS, EXCITATION, EXCESS
SALIVATION, VOMITING AND UNCONSCIOUSNESS.
Medical Cond Aggravated by Exposure: OVEREXPOSURE IS UNLIKELY TO
AGGRAVATE EXISTING MEDICAL CONDITIONS.

=====
===== First Aid Measures =====

First Aid: INHALATION: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION
IF NOT BREATHING. GIVE OXYGEN IF BREATHING IS DIFFICULT. CALL A
PHYSICIAN. EYES: FLUSH WITH WATER. SKIN: WASH WITH SOAP AND WATER.
NOTE TO PHYSICIAN: THERE IS NO SPECIFIC ANTIDOTE. THIS PRODUCT IS
INERT. TREATMENT OF OVEREXPOSURE SHOULD BE DIRECTED AT THE CONTROL
OF SYMPTOMS AND THE CLINICAL CONDITION.

=====
===== Fire Fighting Measures =====

Flash Point: NONE
Extinguishing Media: HELIUM CANNOT CATCH FIRE. USE MEDIA APPROPRIATE FOR
SURROUNDING FIRE.
Fire Fighting Procedures: EVACUATE ALL PERSONNEL FROM DANGER AREA.
IMMEDIATELY DELUGE CONTAINERS WITH WATER SPRAY FROM MAXIMUM
DISTANCE UNTIL CONTROL, THEN MOVE CONTAINERS AWAY FROM AREA.
Unusual Fire/Explosion Hazard: HELIUM CANNOT CATCH FIRE. CONTAINER MAY
RUPTURE DUE TO HEAT OF FIRE. KEEP TEMPERATURE BELOW 125F. MOST
CONTAINERS HAVE A PRESSURE RELIEF VALVE TO VENT CONTENTS.

=====
===== Accidental Release Measures =====

Spill Release Procedures: EVACUATE ALL PERSONNEL FROM DANGER AREA. USE
SELF-CONTAINED BREATHING APPARATUS WHERE NEEDED. SHUT OFF LEAK IF
WITHOUT RISK. VENTILATE AREA OF LEAK OR MOVE LEAK AWAY FROM AREA.

EAKING CONTAINERS TO
WELL-VENTILATED AREA. TEST AREA FOR SUFFICIENT OXYGEN PRIOR TO
ENTRY.

Neutralizing Agent:NONE

=====
Handling and Storage
=====

Handling and Storage Precautions:NEVER WORK ON A PRESSURIZED SYSTEM. IF
THERE IS A LEAK, CLOSE THE CYLINDER VALVE, BLOW DOWN THE SYSTEM BY
VENTING TO A SAFE PLACE, THEN REPAIR LEAK.

Other Precautions:CAUTION:HIGH PRESSURE GAS. USE PIPING & EQUIPMENT
ADEQUATELY DESIGNED TO WITHSTAND PRESSURES T
O BE ENCOUNTERED. CAN
CAUSE RAPID SUFFOCATION DUE TO OXYGEN DEFICIENCY. STORE & USE WITH
ADEQUATE VENTILAT ION. CLOSE VALVE WHEN NOT IN USE/EMPTY.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR IN ACCORDANCE
WITH OSHA 29 CFR 1910.134.

Ventilation:LOCAL EXHAUST PREFERRED, MECHANICAL ACCEPTABLE.

Protective Gloves:WORK GLOVES FOR CYLINDER HANDLING.

Eye Protection:SELECT GOGGLES I/A/W OSHA 29 CFR1910.133

Oth

er Protective Equipment:METATARSEL SHOES FOR CYLINDER HANDLING (OSHA
29 CFR 1910.132 & 133).

Work Hygienic Practices:NONE

Supplemental Safety and Health

DO NOT STRIKE ARC ON CYLINDER. FOR SAFETY INFORMATION ON GENERAL
HANDLING OF COMPRESSED GAS CYLINDERS, OBTAIN A COPY OF PAMPHLET
P-1, "SAFE HANDLING OF COMPRESSED GASES IN CONTAINERS" FROM THE
COMPRES SED GAS ASSOCIATION, INC. 1235 JEFFERSON DAVIS HIGHWAY,
ARLINGTON, VA 22202.

=====
Physical/Chemical Properties
=====

HCC:G3

Boiling Pt:B.P. Text:-452F,-269C

Vapor Pres:GAS

Vapor Density:0.138

Spec Gravity:GAS

Solubility in Water:NEGLIGIBLE

Appearance and Odor:COLORLESS GAS AT NORMAL TEMPERATURE AND PRESSURE;
ODORLESS.

Percent Volatiles by Volume:100

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

NONE CURRENTLY KNOWN. HELIUM IS CHEMICALLY INERT.

Stability Condition to Avoid:HIGH TEMPERATURES ABOVE 125F.

Hazardous Decompo

sition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:SLOWLY RELEASE INTO ATMOSPHERE OUTDOORS. DISCARD ANY PRODUCT, RESIDUE, DISPOSABLE CONTAINER OR LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER, IN FULL COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.