View NSN Online: https://aerobasegroup.ae/nsn/6850-01-265-7233

Product ID: VP-30 PENETRANT MSDS Date:10/24/1986 FSC:6850 NIIN:01-265-7233 MSDS Number: BGSRQ === Responsible Party === Company Name: MET-L-CHEK COMPANY Address:1639 EUCLID STREET **City:SANTA MONICA** State:CA ZIP:90404-3770 Country:US Info Phone Num:213-450-1111 Emergency Phone Num:213-450-1111 CAGE:98733 === Contractor Identification === Company Name:MET-L-CHEK COMPANY Address:1639 EUCLID ST Box:00000 **City:SANTA MONICA** State:CA ZIP:90404 Country:US Phone:310-450-1111/FAX 310452-4046 CAGE:98733 Ingred Name:SOLVENT NAPHTHA (PETROLEUM) MEDIUM ALIPHATIC CAS:64742-88-7 **OSHA PEL:500PPM** ACGIH TLV:100PPM Ingred Name:SOLVENT NAPHTHA (PETROLEUM) LIGHT AROMATIC CAS:64742-95-6 **OSHA PEL:500PPM** ACGIH TLV:100PPM

Ingred Name: ISOBUTANE/PROPANE

MIXTURE (AS PROPELLANT) OSHA PEL:1000PPM (PROPANE) ACGIH TLV:ASPHYXIANTS

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:UNKNOWN IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY CAUSE MILD IRRITATION TO SKIN & RESP TRACT SYSTEM.
Explanation of Carcinogenicity:NO
Effects of Overexposure:INHALATION:MAY CAUSE IRRITATION TO NOSE AND RESPIRATORY SYSTEM.EARLY TO MODERATE CNS
DEPRESSION MAY BE
EVIDENCED BY DIZZ,GIDDINESS,HEADACHE,NAUSEA;EYES:VAPOR MAY CAUSE IRRITATION;SKIN:LIQUID CONTACT M AY IRRITATE MILDLY;INGESTION:NOT LISTED.
Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN,EYE,AND RESPIRATORY DISORDERS MAY BE AGGRAVATED.

First Aid:INHALATION:REMOVE TO FRESH AIR.GIVE CPR IF NEEDED;EYES/SKIN:FLUSH WITH RUNNING WATER FOR AT LEAST 15 MINUTES.GET MEDICAL HELP IF IRRITA TION OCCURS OR PERSISTS; INGESTION:IF VICTIM IS CONSCIOUS,GIVE WA TER.DO NOT INDUCE VOMITING.NOTHING BY MOUTH IF UNCONSCIOUS.GET MEDICAL ATTN.

Flash Point:N/R (AEROSOLS) Lower Limits:2.0 (LIQ) Upper Limits:12.0 (LIQ) Extinguishing Media:WATER FOG,"ALCOHOL" FOAM,DRY CHEMICAL OR CO*2. Fire Fighting Procedures:CONTAINERS EXPOSED TO INTENSE HEAT FROM FIRES SHOULD BE COOLED WITH WATER SPRAY TO PREVENT VAPOR PRESSURE

BUILD-UP.DON'T STORE ABOVE 120F. Unusual Fire/Explosion Hazard:AEROSOL CANS MAY RUPTURE/EXPLODE DUE TO VAPOR PRESSURE BUILDUP IF EXPOSED TO INTENSE HEAT.

Spill Release Procedures: ELIMINATE IGNITION SOURCES WEAR PROTECTIVE CLOTHING & APPROPRIATE RESPIRATOR.SOAK UP RESIDUE WITH ABSORBENT CLAY,SAND,EARTH, OR OTHER MATERIAL.PLACE RAGS & ABSORBED WASTE AND DAMAGED BUT EMPTY CANS IN DOT COVERED NON-LEAKING CONTAIN ERS.

======================================
Handling and Storage Precautions:STORE AWAY FROM HOT PLACES & IGNITION SOURCES.DO NOT STORE OR HANDLE IN ALUMINUM EQUIPMENT AT TEMP ABOVE 120F.
Other Precautions:DURING TRANSFER OF LIQUID IN BULK,GROUND THE HANDLING EQUIPMENT.
======================================
Respiratory Protection:USE NIOSH APPROVED RESPIRATOR IF EXPOSURE EXCEEDS TLV LIMIT. Ventilation:PER MFR,LOCAL EX HAUST OR MECH(GEN) TO MAINTAIN TLV. Protective Gloves:CHEMICAL RESISTANT. Eye Protection:GOGGLES. Other Protective Equipment:EYE WASH FOUNTAINS AND SAFETY SHOWERS. Work Hygienic Practices:WASH WITH SOAP & WATER BEFORE EATING,DRINKING,SMOKING OR USING TOILET FACILITIES. Supplemental Safety and Health NSN FOR AEROSOL CAN OF MIL-I-25135,REV D TYPE II,METHOD C;I/A/W QPL-25135-15,MFR MAY SUPPLY EITHER VP-30 OR VP-31A PENETRANT FOR THIS NSN; THIS ENTRY IS OF VP-30.
======================================
HCC:V3 Spec Gravity:0.8 (BULK) Evaporation Rate & amp; Reference:1.4 OF LIQ(ETHYL AC=1.0)

Solubility in Water: APPRECIATE

Appearance and Odor:LIQUID BEFORE FILLING IN AEROSOL CANS IS DEEP RED COLORED LIQ;HYDROCARBON ODOR.

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING MATERIALS. Stability Condition to Avoid:HEAT,SPARKS,IGNITION SOURCES. Hazardous Decomposition Produ

cts:CARBON MONOXIDE & UNIDENTIFIED ORGANIC COMPOUNDS.

Waste Disposal Methods:DISPOSE OF AS EPA HAZARDOUS WASTE #D001,IGNITABLE WASTE.EMPTY AEROSOL CAN BEFORE DISPOSING OF THEM.PRESSURIZED AEROSOL CANS ARE NOT ACCEPTABLE WASTE,COMPLY ALL FEDERAL,STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.