

MOBIL OIL CORP -- MOBIL DTE-26 -- 9150-01-112-9410

===== Product Identification =====

Product ID:MOBIL DTE-26

MSDS Date:09/21/1990

FSC:9150

NIIN:01-112-9410

MSDS Number: BGSXL

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:3225 GALLONS ROAD

City:FAIRFAX

State:VA

ZIP:22037-0001

Country:US

Info Phone Num:800-424-9300/800-227-0707 S.CASTILL

Emergency Phone Num:703-849-3265 OR 212-883-4411

Preparer's Name:MOBIL OIL CORP

CAGE:3U728

=== Contractor Identification ===

Company Name:CONVOY OIL CORP

Address:1410 N FRONT STREET

Box:29366

City:PHILADELPHIA

State:PA

ZIP:19125

Country:US

Phone:215-739-5281

CAGE:6A438

Company Name:HURON INDUSTRIES INC

Address:2301 16TH ST

Box:610104

City:PORT HURON

State:MI

ZIP:48061-0104

Country:US

Phone:810-984-4213

CAGE:03432

Company Name:MAZZONI BROTHERS CHEMICAL INC

Address:SOUTH RAILROAD BLVD.

Box:297

City:MINOTOLA

State:NJ

ZIP:08341

Country:US

Pho

ne:(SANLO PRODUCTS) 201-348-1684

CAGE:77506

Company Name:MOBIL OIL CORP ENVIRONMENTAL AFFAIRS & TOXICOLOGY

Address:PENNINGTON-ROCKY HILL RD

Box:City:PENNINGTON

State:NJ

ZIP:08534

Country:US

CAGE:0AHK0

Company Name:MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Address:3225 GALLOWS ROAD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525/ 856-224-4644

CAGE:3U728

=====  
===== Composition/Information on Ingredients =====

Ingred Name:DISTILLATES, HYDROTREATED HEAVY

PARAFFINIC

CAS:64742-54-7

RTECS #:PY8035500

Fraction by Wt: >95%

Other REC Limits:NONE SPECIFIED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY

PARAFFINIC

CAS:64742-65-0

RTECS #:PY8038500

Fraction by Wt: SEE #1%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:ADDITIVES PACKAGE

Fraction by Wt: 400F,>204C

Lower Limits:0.6

Upper Limits:7.0

Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL & WATER FOG.

Fire

Fighting Procedures:WATER OR FOAM MAY CAUSE FROTHING.USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL.FIRE FIGHTERS SHOULD WEAR SELF CONTAINED BREATHING APPARATUS.PREVENT RUNOFF.

Unusual Fire/Explosion Hazard:NONE STATED. CONTAINERS MAY RUPTURE/EXPLODE IN HEAT OF FIRE. PRODUCT MAY BE DECOMPOSED TO DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB ON FIRE RETARDANT TREATED SAWDUST,DIATOMACEOUS EARTH,ETC . SHOVEL UP & DISPOSE OF AT AN APPROPRIATE WASTE DISPOSAL FACILITY.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A DRY,COOL,AND VENTILATED AREA.DO NOT STORE IN DIRECT SUNLIGHT.KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE.PROTECT FROM PHYSICAL DAMAGE.

Other Precautions:THE SELECTION OF PERSONAL PROTECTIVE EQUIPMENT SHOULD BE MADE BY THE MATERIAL USER BASED ON THE PARTICULAR CONDITIONS WHERE THE MATERIAL IS TO BE USED TOGETHER WITH INFORMATION CONTAINED IN THIS MSDS. GROUND/BOND ALL EQUIPMENT WHEN TRANSFERG

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHEN NEEDED,USE NIOSH APPROVED RESPIRATOR.IN CONFINED OR POORLY VENTILATED AREAS OR FOR EMERGENCY AND OTHER CONDITIONS WHERE THE EXPOSURE LIMITS ARE EXCEEDE,USE AN APPROVED POSITIVE-PRESSURE,SELF-CONTAINED BREATHING APPARATUS.

Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY A DEQUATE.

Protective Gloves:USUALLY NONE

Eye Protection:USUALLY NONE.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:PRACTICE GENERAL INDUSTRIAL HYGEIN PRACTICE.KEEP AREA CLEAN.WASH THOROUGHLY AFTER EACH USE OR HANDLING.AVOID CONTACT.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>600F/316C

Melt/Freeze Pt:M.P/F.P Text:-10F,-23C

Vapor Pres: