

MET-L-CHEK COMPANY -- VP-30 PENETRANT -- 6850-01-264-8677

=====
Product Identification
=====

Product ID:VP-30 PENETRANT

MSDS Date:10/24/1986

FSC:6850

NIIN:01-264-8677

MSDS Number: BGTBB

=== Responsible Party ===

Company Name:MET-L-CHEK COMPANY

Address:1639 EUCLID STREET

City:SANTA MONICA

State:CA

ZIP:90404-3770

Country:US

Info Phone Num:213-450-1111

Emergency Phone Num:213-450-1111

CAGE:98733

===

Contractor Identification ===

Company Name:MET-L-CHEK COMPANY

Address:1639 EUCLID ST

Box:00000

City:SANTA MONICA

State:CA

ZIP:90404

Country:US

Phone:310-450-1111/FAX 310452-4046

CAGE:98733

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENT NAPHTHA (PETROLEUM) MEDIUM ALIPHATIC

CAS:64742-88-7

OSHA PEL:500PPM

ACGIH TLV:100PPM

Ingred Name:SOLVENT NAPHTHA (PETROLEUM) LIGHT AROMATIC

CAS:64742-95-6

OSHA PEL:500PPM

ACGIH TLV:100PPM

=====
Hazards
=====

Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY CAUSE SLIGHT SKIN
IRRITATION;VAPORS OR OIL MIST MAY CAUSE MILD IRRITATION OF UPPER
RESPIRATORY TRACT,AND CAUSES CNS DEPRESSION.
Effects of Overexposure:EYES/SKIN:LIQUID IS MINIMALLY IRRITATING TO THE
EYES AND SLIGHTLY IRRITATING TO THE SKIN.VAPORS CAUSE EYES
IRRITATION; INHALATION:VAPORS CAUSE IR
RITATION TO NOSE,THROAT AND
RESPIRATORY TRACT,AND CAUSE CNS DEPRESSION;INGESTION:MAY CAUSE
NAUSEA,GIDDINESS OR HEADACHE,AND POSSIBLE VOMITING.
Medical Cond Aggravated by Exposure:PREEXISTING EYE,SKIN AND
RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS
PRODUCT.

===== First Aid Measures =====

First Aid:EYES/SKIN:FLUSH WITH PLENTY OF RUNNING WATER.REMOVE
VONTAMINATED CLOTHS,AND WASH SKIN WITH SOAP & WATER GET MEDICAL
ASST
IF IRRITATION PERSISTS;INHALATION:REMOVE TO FRESH AIR.PROVIDE
OXYGEN IF BREATHI NG IS DIFFICULT.GIVE ARTIFIICAL RESPIRATION IF
REQUIRED.GET MED HELP IF NEEDED;INGESTION:DO NOT INDUCE
VOMITNG.NOTHING BY MOUTH IF VICTIM IS UNCONSCIOUS;GET MEDICAL
ASSISTANCE IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:140F/60C
Lower Limits:1.0
Upper Limits:6.0
Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXIDE OR FOAM
;DO
NOT USE DIRECT STREAM OF WATER.
Fire Fighting Procedures:IN CONFINED AREA,DO NOT ENTER WITHOUT A FULL
BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED
SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:CONTAINERS EXPOSED TO INTENSE HEAT FROM
FIRE SHOULD BE COOLED WITH WATER SPRAY TO PREVENT VAPOR PRESSURE
BUILDUP WHICH COULD RUPTURE CONTAINER.

===== Accidental Release Measures =====

Spill Release Procedures:ELIM IGNITIO

